(Ab)Using Route Servers

Elisa Jasinska <elisa.jasinska@ams-ix.net>
Chris Malayter <cmalayter@switchanddata.com>

Agenda

- Why Route Servers?

- What do Route Servers do?

- Current implementations and Route Server Working Group

- Functionality and scalability testing

Agenda

- **Why Route Servers?**

- What do Route Servers do?

- Current implementations and route Server Working Group

- Functionality and scalability testing

Why Route Servers?

- Internet Exchange (e.g. AMS-IX, DE-CIX, LINX)

- Peering Platform for many Parties

- Route Servers for the Participants

Why Route Servers?

- Peer with as many parties as possible

➡ Maintaining lots of BGP Sessions

Why Route Servers?

- Reach a lot of Parties with just one BGP session

Why Route Servers?

- Redundancy ... in case your sessions die ...

Why Route Servers?

- Redundancy ... in case the Route Server dies ...

Why Route Servers?

- Easy entry point for new Members to the Exchange - immediate traffic

Agenda

- Why Route Servers?

- **What do Route Servers do?**

- Current implementations and route Server Working Group

- Functionality and scalability testing

What do route servers do?

- Receive UPDATEs from every participant

```
19:58:33.721679 IP (tos 0x0, ttl 64, id 44576, offset 0, flags [DF], proto TCP (6), length 117)
10.23.0.5.58880 > 10.23.0.1.179: P, cksum 0xb892 (correct), 48:113(65) ack 61 win 1460
<nop,nop,timestamp 1976783474 3177206804>: BGP, length: 65
        Update Message (2), length: 65
...
        AS Path (2), length: 10, Flags [T]: 65499 11 12 13
...
        Next Hop (3), length: 4, Flags [T]: 10.23.0.5
...
        Updated routes:
          2.0.5.0/24
19:58:33.723897 IP (tos 0x0, ttl 64, id 42762, offset 0, flags [DF], proto TCP (6), length 117)
10.23.0.4.33349 > 10.23.0.1.179: P, cksum 0xb033 (correct), 48:113(65) ack 61 win 1460
<nop,nop,timestamp 1976783474 1916183085>: BGP, length: 65
        Update Message (2), length: 65
...
        AS Path (2), length: 10, Flags [T]: 65500 11 12 13
...
        Next Hop (3), length: 4, Flags [T]: 10.23.0.4
...
        Updated routes:
          2.0.4.0/24
```

What do route servers do?

- Apply filters for the receiving peers

```
from AS65500 accept ANY
to AS65500 announce AS65499

from AS65499 accept ANY
to AS65499 announce AS65500
```

What do route servers do?

- Perform "best path" selection for every peer

- Store Routing Information Base (RIB) for every peer

```
   flags destination          gateway          lpref    med aspath origin
   *>      2.0.4.0/24          10.23.0.4        100      200 65500 11 12 13 i
   *>      2.0.5.0/24          10.23.0.5        100      200 65499 11 12 13 i
```

What do route servers do?

- Forward the RIB contents to the desired peer

```
19:58:33.901718 IP (tos 0xc0, ttl 1, id 15745, offset 0, flags [DF], proto TCP (6), length 103)
10.23.0.1.179 > 10.23.0.4.33349: P, cksum 0x2b21 (correct), 61:112(51) ack 114 win 17376
<nop,nop,timestamp 1916183105 1976783474>: BGP, length: 51
        Update Message (2), length: 51
...
        AS Path (2), length: 10, Flags [T]: 65499 11 12 13
...
        Next Hop (3), length: 4, Flags [T]: 10.23.0.5
...
        Updated routes:
          2.0.5.0/24
19:58:33.903463 IP (tos 0xc0, ttl 1, id 12268, offset 0, flags [DF], proto TCP (6), length 103)
10.23.0.1.179 > 10.23.0.5.58880: P, cksum 0x377e (correct), 61:112(51) ack 114 win 17376
<nop,nop,timestamp 3177206824 1976783474>: BGP, length: 51
        Update Message (2), length: 51
...
        AS Path (2), length: 10, Flags [T]: 65500 11 12 13
...
        Next Hop (3), length: 4, Flags [T]: 10.23.0.4
...
        Updated routes:
          2.0.4.0/24
```

What do route servers do?

Agenda

- Why Route Servers?

- What do Route Servers do?

- **Current implementations and Route Server Working Group**

- Functionality and scalability testing

Current Implementations

- Quagga

- OpenBGPD

- BIRD

Route Server Working Group

- Andy Davidson - LONAP

- Chris Malayter - Switch & Data

- Elisa Jasinska - AMS-IX

- Mo Shivji - LINX

- Robert Wozny - PL-IX

- Sebastian Spies - DE-CIX

- Wolfgang Hennerbichler - VIX

Agenda

- Why Route Servers?

- What do Route Servers do?

- Current implementations and route Server Working Group

- **Functionality and scalability testing**

Functional Testing

AS4 / 32 Bit ASN

- All three implementations support AS4

- All three versions tested as of 12/4/2009 to properly implement AS4

IPv6

- All three implementations support IPv6

- We highly recommend running a current version of any of three implementations

- MANY bugs fixed between 10/1/2009-1/1/2010

- Running a port of a route server is ill-advised and can leave a bad taste in your mouth!

Scalability

Testing

- 100 sessions, set up from IXIA

- 500 or 1000 prefixes per session

- Additional random flapping

Quagga

- Single threaded implementation

- Issues with performing its tasks on time

- CPU thrashing during periods of instability

- Bug causing crash during flapping

Quagga CPU

Quagga cpu usage
multiple-rib; 100 sessions
IXIA vs. Quagga
500 prefixes per session with random flapping
lab4
2 x Intel(R) Xeon(R) CPU 3050 @ 2.13GHz

OpenBGPD CPU

OpenBGPd cpu usage
multiple-rib; 100 sessions
IXIA vs. OpenBGPD
1000 prefixes per session
lab2.paix.net
4 x Intel(R) Xeon(TM) CPU 3.60GHz (GenuineIntel 686-class) 3.61 GHz

BIRD CPU

BIRD cpu usage
multiple-rib; 100 sessions
IXIA vs. BIRD
500 prefixes per session with random flapping
lab6.paix.net
4 x Intel(R) Xeon(TM) CPU 3.80GHz

OpenBGPD

- Multi-threaded implementation

- Session thread keeps sessions active while instability is occurring

- 1GB memory limitation per process on i386 and a 4 GB memory limitation on amd64

OpenBGPD Mem

OpenBGPd mem usage
multiple-rib; 100 sessions
IXIA vs. OpenBGPD
1000 prefixes per session
lab2.paix.net
4 x Intel(R) Xeon(TM) CPU 3.60GHz (GenuineIntel 686-class) 3.61 GHz

mem route decision engine
mem session engine
free memory

mem usage (Mbytes)

1800
1600
1400
1200
1000
800
600
400
200
0

0   10000   20000   30000   40000   50000   60000

time (seconds)

NANOG 48

Quagga Mem

Quagga mem usage
multiple-rib; 100 sessions
IXIA vs. Quagga
500 prefixes per session with random flapping
lab4
2 x Intel(R) Xeon(R) CPU 3050 @ 2.13GHz

NANOG 48

BIRD

- Single threaded implementation

- Amazing scheduling system

- The most stable route server we tested

- Discovered odd memory freeing issues in Linux glibc

BIRD Mem

BIRD mem usage
multiple-rib; 100 sessions
IXIA vs. BIRD
500 prefixes per session with random flapping
lab6.paix.net
4 x Intel(R) Xeon(TM) CPU 3.80GHz

NANOG 48

Thank you!
Questions?

<elisa.jasinska@ams-ix.net>
<cmalayter@switchanddata.com>