

NAME

`prove` -- A command-line tool for running tests against Test::Harness

SYNOPSIS

`prove` [options] [files/directories]

OPTIONS

<code>-b, --blib</code>	Adds blib/lib to the path for your tests, a la "use blib"
<code>-d, --debug</code>	Includes extra debugging information
<code>-D, --dry</code>	Dry run: Show the tests to run, but don't run them
<code>-h, --help</code>	Display this help
<code>-H, --man</code>	Longer manpage for prove
<code>-I</code>	Add libraries to @INC, as Perl's <code>-I</code>
<code>-l, --lib</code>	Add lib to the path for your tests
<code>--perl</code>	Sets the name of the Perl executable to use
<code>-r, --recurse</code>	Recursively descend into directories
<code>-s, --shuffle</code>	Run the tests in a random order
<code>--strap</code>	Define strap class to use
<code>-T</code>	Enable tainting checks
<code>-t</code>	Enable tainting warnings
<code>--timer</code>	Print elapsed time after each test file
<code>-v, --verbose</code>	Display standard output of test scripts while running them
<code>-V, --version</code>	Display version info

Single-character options may be stacked. Default options may be set by specifying the `PROVE_SWITCHES` environment variable.

OVERVIEW

`prove` is a command-line interface to the test-running functionality of Test::Harness. With no arguments, it will run all tests in the current directory.

Shell metacharacters may be used with command lines options and will be expanded via `File::Glob::bsd_glob`.

PROVE VS. "MAKE TEST"

`prove` has a number of advantages over `make test` when doing development.

* `prove` is designed as a development tool

Perl users typically run the test harness through a makefile via `make test`. That's fine for module distributions, but it's suboptimal for a test/code/debug development cycle.

* `prove` is granular

`prove` lets you run against only the files you want to check. Running `prove t/live/t/master.t` checks every `*.t` in `t/live`, plus `t/master.t`.

* `prove` has an easy verbose mode

`prove` has a `-v` option to see the raw output from the tests. To do this with `make test`, you must set `HARNESS_VERBOSE=1` in the environment.

* `prove` can run under taint mode

`prove's` `-T` runs your tests under `perl -T`, and `-t` runs them under `perl -t`.

* `prove` can shuffle tests

You can use `prove's` `--shuffle` option to try to excite problems that don't show up when

tests are run in the same order every time.

* *prove* doesn't rely on a make tool

Not everyone wants to write a makefile, or use *ExtUtils::MakeMaker* to do so. *prove* has no external dependencies.

* Not everything is a module

More and more users are using Perl's testing tools outside the context of a module distribution, and may not even use a makefile at all.

COMMAND LINE OPTIONS

-b, --blib

Adds blib/lib to the path for your tests, a la "use blib".

-d, --debug

Include debug information about how *prove* is being run. This option doesn't show the output from the test scripts. That's handled by *-v,--verbose*.

-D, --dry

Dry run: Show the tests to run, but don't run them.

-I

Add libraries to @INC, as Perl's *-I*.

-I, --lib

Add *lib* to @INC. Equivalent to *-Ilib*.

--perl

Sets the `HARNESS_PERL` environment variable, which controls what Perl executable will run the tests.

-r, --recurse

Descends into subdirectories of any directories specified, looking for tests.

-s, --shuffle

Sometimes tests are accidentally dependent on tests that have been run before. This switch will shuffle the tests to be run prior to running them, thus ensuring that hidden dependencies in the test order are likely to be revealed. The author hopes the run the algorithm on the preceding sentence to see if he can produce something slightly less awkward.

--strap

Sets the `HARNESS_STRAP_CLASS` variable to set which `Test::Harness::Straps` variable to use in running the tests.

-t

Runs test programs under perl's *-t* taint warning mode.

-T

Runs test programs under perl's *-T* taint mode.

--timer

Print elapsed time after each test file

-v, --verbose

Display standard output of test scripts while running them. Also sets `TEST_VERBOSE` in case your tests rely on them.

-V, --version

Display version info.

BUGS

Please use the CPAN bug ticketing system at <http://rt.cpan.org/>. You can also mail bugs, fixes and enhancements to [<bug-test-harness@rt.cpan.org>](mailto:bug-test-harness@rt.cpan.org).

TODO

- Shuffled tests must be recreatable

AUTHORS

Andy Lester [<andy at petdance.com>](mailto:andy@petdance.com)

COPYRIGHT

Copyright 2004-2006 by Andy Lester [<andy at petdance.com>](mailto:andy@petdance.com).

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

See <http://www.perl.com/perl/misc/Artistic.html>.