

**RSX-11M**

**V03.2**

**Master Index**

Order No. AA-5430C-TC

To order additional copies of this document, contact the Software Distribution  
Center, Digital Equipment Corporation, Maynard, Massachusetts 01754

**digital equipment corporation · maynard, massachusetts**

The information in this document is subject to change without notice and should not be construed as a commitment by Digital Equipment Corporation. Digital Equipment Corporation assumes no responsibility for any errors that may appear in this document.

The software described in this document is furnished under a license and may only be used or copied in accordance with the terms of such license.

No responsibility is assumed for the use or reliability of software on equipment that is not supplied by DIGITAL or its affiliated companies.

Copyright © 1979 by Digital Equipment Corporation

The postage-prepaid READER'S COMMENTS form on the last page of this document requests the user's critical evaluation to assist us in preparing future documentation.

The following are trademarks of Digital Equipment Corporation:

DIGITAL	DECsystem-10	MASSBUS
DEC	DECtape	OMNIBUS
PDP	DIBOL	OS/8
DECUS	EDUSYSTEM	PHA
UNIBUS	FLIP CHIP	RSTS
COMPUTER LABS	FOCAL	RSX
COMTEX	INDAC	TYPESET-8
DDT	LAB-8	TYPESET-11
DECCOMM	DECSYSTEM-20	TMS-11
ASSIST-11	RTS-8	ITPS-10
VAX	VMS	SBI
DECnet	IAS	PDT
DATATRIEVE	TRAX	

## INTRODUCTION

This manual is a detailed index to the RSX-11M documentation set. It indicates where in the set information on a topic can be found. This index, however, is not intended to replace the indexes found in the individual RSX-11M manuals.

An acronym printed in *italic capital letters* follows each entry in this index, and represents the name of the manual in which the information can be found. Chapter and section number references follow the acronym. Some entries are followed only by the chapter number(s), for example:

PIP (Peripheral Interchange Program), *UTL 4*

This entry indicates that PIP is discussed throughout chapter 4 of the utilities manual.

Following is a list of the acronyms with the corresponding manual titles. (The *RSX-11M/RSX-11S Documentation Directory* lists the order numbers for these manuals.)

*BEG — RSX-11M Beginner's Guide*  
*CDA — RSX-11M/M-PLUS Crash Dump Analyzer Reference Manual*  
*DEV — RSX-11M/M-PLUS Guide to Program Development*  
*DRV — RSX-11M/M-PLUS I/O Drivers Reference Manual*  
*ERL — RSX-11M/M-PLUS Error Logging Reference Manual*  
*EXE — RSX-11M/M-PLUS Executive Reference Manual*  
*GEN — RSX-11M System Generation and Management Guide*  
*INT — Introduction to RSX-11M*  
*IOP — IAS/RSX-11 I/O Operations Reference Manual*  
*MAC — IAS/RSX-11 MACRO-11 Reference Manual*  
*MCR — RSX-11M/M-PLUS MCR Operations Reference Manual*  
*ODT — IAS/RSX-11 ODT Reference Manual*  
*RLN — RSX-11M/RSX-11S Release Notes*  
*RMC — RMS-11 MACRO-11 Reference Manual*  
*RMU — RMS-11 User's Guide*  
*SLR — IAS/RSX-11 System Library Routines Reference Manual*  
*SSG — RSX-11S System Generation and Installation Guide*  
*TKB — RSX-11M/M-PLUS Task Builder Manual*  
*UMD — RSX-11M/M-PLUS User Mode Diagnostics Reference Manual*  
*UTL — RSX-11 Utilities Manual*  
*WRT — RSX-11M Guide to Writing an I/O Driver*

**A**

- Absolute addresses, *MAC* 5-7, 6-14, *ODT* 2-4
  - Absolute addressing mode, *MAC* 5-5, 5-7
  - Absolute binary output, *MAC* 6-14
  - Absolute expression, *MAC* 3-15
  - Absolute loader, *SSG* 2-15
  - Absolute module, *MAC* 6-34
  - Absolute program section, *MAC* 6-37
  - Access, *RMU* 1-2, 1-4
    - controlled, *RMU* 1-2
    - direct, *DRV* 15-3, 15-8, 18-69
    - random, *RMU* 1-11, 5-1, 5-8
    - read, *IOP* 2-14, 3-3, 3-16, *RMU* 2-12
    - read-only, *MAC* 6-33
    - read/write, *MAC* 6-33
    - sequential, *RMU* 1-11
    - shared, *RMU* 2-5
    - types of, *MCR* 3-2
    - write, *IOP* 2-14, 3-3, 3-16, *RMU* 2-12
  - Access mode,
    - random, see Random access mode
    - sequential, see Sequential access mode
  - Accessing files, see Files
  - Access rights,
    - assigning, *MCR* 3-3
  - Account file (ACNT) entries,
    - maintaining, *MCR* 2-18 to 2-21
  - Account file, multiuser, *MCR* 2-17
  - Account file maintenance program, see ACNT
  - ACNT (account file maintenance program),
    - MCR* 2-17, *RLN* 2, 42
    - account entries in,
      - adding, *MCR* 2-18, 2-19
      - deleting, *MCR* 2-21, 2-22
      - examining, *MCR* 2-19, 2-20
      - listing, *MCR* 2-21
      - modifying, *MCR* 2-20
    - creating, *MCR* 2-18
    - error messages, *MCR* 2-22
    - nonprivileged account modifications in,
      - MCR* 2-22
    - sorting, *MCR* 2-21
  - ACP (Ancillary Control Processor), *MCR* 4-36, 4-65, *RLN* 2
    - dedicated, *RLN* 43
    - function mask for, *WRT* 4-12
    - function of, *WRT* 2-16
    - routing I/O requests with, *RLN* 43
  - Active Page Register (APR), *RMU* 8-3, 8-4, *TKB* 2-10
  - Active tasks, see Tasks
  - Address,
    - odd, *ODT* 3-14, 3-35
    - odd-numbered, *ODT* 3-3
  - Address boundaries, *MAC* 6-31
    - displaying, *UTL* 19-2
  - Address calculation, *ODT* 3-8
  - Address check, *WRT* 5-2
  - Addresses,
    - absolute, *MAC* 5-7, 6-14, *ODT* 2-4
    - assigning, *TKB* 2-1
    - calculating, *ODT* 3-8
    - mapping, *EXE* 3-1, 3-6, 3-7
    - odd-numbered, *ODT* 3-3, 3-14
    - physical, *INT* 3-2
    - printing task, *ODT* 3-1
    - relative, *MAC* 6-14
    - relocatable, *ODT* 3-29
    - relocating, *WRT* 6-9
    - symbolic UMR, *WRT* B-3
    - user-task, *ODT* 3-1
    - virtual, *INT* 3-1
  - Address expression, *ODT* 1-5
  - Addressing,
    - branch instruction, in MACRO-11, *MAC* 5-8
    - forms, *ODT* 1-5
      - summary, *MAC* 5-7
    - locations in a task image file,
      - with ZAP, *UTL* 19-3, 19-4
    - modes,
      - MACRO-11, *MAC* 5
        - absolute, *MAC* 5-5, 5-7
        - autodecrement, *MAC* 5-3, 5-7
        - autodecrement deferred, *MAC* 5-3, 5-7
        - autoincrement, *MAC* 5-2, 5-7
        - autoincrement deferred, *MAC* 5-3, 5-7
        - immediate, *MAC* 5-4, 5-7
        - index, *MAC* 5-4, 5-7
        - index deferred, *MAC* 5-4, 5-7
        - register, *MAC* 5-1, 5-7
        - register deferred, *MAC* 5-2, 5-7
        - relative, *MAC* 5-5, 5-7
        - relative deferred, *MAC* 5-6, 5-7
        - summary of, *MAC* 5-7
  - relative, *ODT* 3-25
  - ZAP, *UTL* 19-3
- Address limits, *ODT* 2-8, 3-21
- Address search commands,
  - effective, *ODT* 3-23, B-1
- Address space,
  - logical, *EXE* 3-2, 3-4
  - extended, *INT* 3-10
  - physical, *INT* 3-10

- Address space (Cont.),
  - user-mode, *EXE* 5-3, 5-4
  - virtual, *EXE* 3-2, *INT* 3-1, 3-10, *RMU* 6-16
    - mapped system, *TKB* 2-10
    - unmapped system, *TKB* 2-8
- Address window, see Windows
- Algorithms,
  - search, *ODT* B-1
- Allocating files, see Files
- Allocation,
  - contiguous, *RMC* 3-28, 5-10
  - hard, *RMC* 5-10
  - information, *RMC* 1-13
  - options, *RMC* 5-10
  - quantity, *RMC* 5-8
  - requirements, *MAC* 6-35
- American National Standards Institute, see ANSI
- American Standard Code for Information Interchange, see ASCII
- Ampersand (&), *MAC* 3-2
- Analog-to-digital converters, *DRV* 14-1, 15-7
  - driver for, *DRV* 14-1
- Ancillary Control Processor, see ACP
- Angle brackets, *MAC* 3-3, 3-15, 6-25, 6-28, 7-4, 7-16
  - left, *ODT* 3-8
  - right, *ODT* 3-7
- ANSI (American National Standards Institute),
  - INT* 5-5, *RMU* F-1
  - COBOL, *RMU* 5-1
  - labels and RMSDSP, *RMU* 9-53
  - magnetic tapes, *MCR* 3-1
    - data formats for, *IOP* 1-5, G-1
    - mounting, *MCR* 4-65
  - support of standard, *IOP* G
  - utilities compliance with, *RMU* 9-10
- Appending files, see Files
- Application, *RMU* 6-3
- APR, see Active Page Register
- Area, *RMC* 1-13, 5-2, 5-4, *RMU* 6-10
- Argument list, *RMC* 1-21
- Arguments,
  - complementing, *MAC* 6-27
  - integer, *EXE* 1-11
  - macro, *MAC* 7-4
    - concatenating, *MAC* 7-10
    - special characters in, *MAC* 7-6
  - optional, *EXE* 6-5
  - optional subroutine, *EXE* 1-10
  - search, *ODT* 3-21
  - subroutine, optional, *EXE* 1-10
- ANSI (Cont.),
  - substitution, *MAC* 7-15
  - special, in *ODT*, *ODT* 3-37
- Argument separator, *ODT* 2-3
- Arithmetic operations, *ODT* 3-36
- Arithmetic operators, *ODT* 2-2
  - addition, or autoincrement indicator, *MAC* 3-2
  - division, *MAC* 3-2
  - multiplication, *MAC* 3-2
  - subtraction, or autodecrement indicator, *MAC* 3-2
- Arithmetic overflow, *ODT* A-2
- Array,
  - integer, *EXE* 1-11
  - RDB integer, *EXE* 3-14
  - status, *isb*, *DRV* 14-3, 15-14, 16-8
  - WDB integer, *EXE* 3-17
- ASCII (American Standard Code for Information Interchange), *RMU* 1-12
  - byte mode, *ODT* 3-31
  - characters, *ODT* 2-6
    - print byte mode, *ODT* 3-34
    - print word mode, *ODT* 3-35
    - set, *MAC* A-1
  - conversion, *MAC* 3-14
    - characters, *MAC* 6-19
  - lowercase, *MAC* 6-14
  - to-binary conversion routines, *IOP* 4-7, 4-12, *SLR* 4-4, 4-5
  - to-binary double-word conversion routines, *SLR* 4-1 to 4-3
  - to-Radix-50 conversion routines, *SLR* 4-6
  - translation, *MAC* 6-20, 6-21
  - word mode, *ODT* 3-31
- Assembler directives, *MAC* 6-1, B-2
  - types of, *DEV* 1-3
- Assembler languages, see Languages
- Assembler, *MACRO*-11, see *MACRO*-11
- Assemblers, *INT* 2-2, *RMU* 1-28, 8-1
- Assembler version, *MAC* 6-8
- Assembly, conditional, see Conditional assembly
- Assembly language, *MACRO*-11, see *MACRO*-11
- Assembly languages, *DEV* 1-2
  - ICS/ICR and DSS/DRS, interface, *DRV* 18-8
- Assembly listing, *DEV* 2-6, 3-4 to 3-7, *MAC* 2-6
- Assembly pass, *MAC* 1-1
- Assembly process, *BEG* 2-1
- Assembly, subconditional, see Subconditional assembly

- Assign Table, *CDA* 1-7, 3-14, C-25
- AST (Asynchronous System Trap), *DRV* 1-11, 2-9, 2-10, 2-35, 3-32, *EXE* 2-1, 2-4, 2-6, *INT* 3-9, 4-2, *RMU* 1-33
- control blocks, *CDA* 3-17, B-39, C-34
- service routine, *EXE* 2-7, *IOP* 2-12, 3-34
- with I/O operations, *IOP* 2-45
- spawning with, *RLN* 40
- terminating, *DRV* 1-22
- Asterisk, *MAC* 3-2, *ODT* 3-39
- as EDT prompt, *UTL* 2-2
- convention in MCR, see Wildcards
- in cross-reference listings, *TKB* 6-11
- in global cross-reference, *TKB* 5-10
- Asynchronous line interface, *DRV* 12-2
- Asynchronous System Trap, see AST
- AT. (MCR indirect file processor), *INT* 4-2
- and block-structured files, *MCR* 5-2
- and comments in files, *MCR* 5-3
- directives,
- described, *MCR* 5-11 to 5-37
  - listed, *MCR* 5-2
- At sign (@), *MAC* 3-2, *MCR* 5-1, *TKB* 1-5
- in cross-reference listings, *TKB* 6-11
- in global cross-reference, *TKB* 5-10
- Attribute information, *RMC* 1-2
- Attributes,
- current location counter, *MAC* 3-12
  - record, *RMC* 3-44
- Audit trail,
- SLP, *UTL* 17-1, 17-16
- Autodecrement addressing mode, *MAC* 5-3, 5-7
- Autodecrement deferred addressing mode, *MAC* 5-3, 5-7
- Autoincrement addressing mode, *MAC* 5-2, 5-7
- Autoincrement deferred addressing mode, *MAC* 5-3, 5-7
- Autoload, *TKB* 5-1
- routine, *TKB* 5-4
  - vectors, *TKB* 5-5
- Autopatch, *RLN* 8
- B**
- Back-arrow commands, *ODT* 2-4, 3-6, 3-26
- Backing up files, see BRU, DSC, PRESRV
- Backslash (\), *MAC* 3-2
- command, *ODT* 3-4, 3-34
- Back-up format, *RMU* 1-26
- Back-up and Restore Utility, see BRU
- BAD (Bad Block Locator Utility),
- command format, *UTL* 9-1
- BAD (Cont.),
- error messages, *UTL* 9-8, 9-11
  - format of bad block descriptor entries, *UTL* 9-3
  - processing of bad block data, *UTL* 9-3
  - supported devices, *UTL* 9-8
  - switches, *UTL* 9-2, 9-5 to 9-8
    - new, *RLN* 33  - use with indirect command files, *UTL* 9-2
  - use with INI command, *UTL* 9-1, 9-4
  - using, *UTL* 9-4, 9-5
- Bad Block Locator Utility, see BAD
- Bad blocks,
- information on,
    - with DSC, *UTL* 11-10 to 11-13  - locating,
    - with BAD, *UTL* 9-4
- Bad sector file, *RK06*, *DRV* 3-8
- Base address, *ODT* 1-4
- BASIC-11, *INT* 2-2, 5-3, 5-4
- Basic MCR,
- building, *SSG* 4-7
  - commands,
    - initialization, *SSG* 2-1
    - system maintenance, *SSG* 2-2
    - task control, *SSG* 2-1  - error messages, *MCR* B-1, *SSG* 2-3
  - size considerations, *SSG* 4-7
  - syntax, *MCR* B-1
- BASIC-PLUS, *RMC* 5-26, *RMU* A-3
- BASIC-PLUS-2, *INT* 2-2, 5-3, 5-4, *RLN* 21, *RMU* B-1
- Baud rates, *MCR* 4-106
- Bell character, *BEG* 1-6
- Big buffer, *IOP* 2-17, 2-21, 2-39
- Binary operators, *MAC* 3-5, 3-15
- Bistable digital output, *DRV* 18-15
- Bit definitions, *DRV* 3-10, 3-13
- Bits,
- least significant, *RMC* 7-1
- Blank lines, *MAC* 2-2
- Block header formats,
- RMS-11 pool, *RMC* 2-10
- Block I/O, *RMC* 9-1
- operations, *IOP* 1-6, 2-11, 2-23, 2-24, 3-6, 3-9, 3-30 to 3-38
- Block mode, *DEV* 1-1
- Block number,
- logical, *IOP* 1-5, 5-1, *RMC* 3-48, 5-7
  - maximum virtual, *RMC* 4-4
  - Root virtual, *RMC* 5-59
  - virtual, *IOP* 1-5, 1-6, 2-23, 2-24, 3-32, 4-19, 5-1, *RMC* 3-48, 5-7, 5-38

RSX-11M V03.2 Master Index

- Block(s), *BEG* 4-5  
adding, to an RMS-11 file, *RMC* 8-10  
common, *DRV* 15-11 to 15-13, 18-71, *SSG* 2-8  
control, see Control blocks  
logical, *DRV* 1-26, 1-27, *RMU* 1-14  
physical, *RMU* 1-16  
shadow recording linkage, *CDA* C-49  
statistics, *IOP* 8-1  
storage,  
    reserving, *MAC* 6-30  
user control, *RMC* 1-2, 1-8, 1-10  
window, see Window blocks  
virtual, *DRV* 1-26, 1-27, *INT* 6-4, *IOP* 1-4,  
    3-30 to 3-37, 5-1, *RMC* 9-3, 9-5,  
    *RMU* 1-15, 2-12, 3-1, 4-1, 9-16, 9-72
- Bootstrap block, *IOP* E-1
- Bootstrapping, *WRT* 2-4, 3-26  
    baseline system, *GEN* 2-5 to 2-9  
    programs into processor memory, *GEN* 2-1,  
    2-2  
    system image, *MCR* 4-130
- BPT instruction, *RMC* A-18
- Brackets, angle, *MAC* 3-3, 3-15, 6-25, 6-28, 7-4,  
    7-16  
    left, *ODT* 3-8  
    right, *ODT* 3-7
- Branch,  
    conditional, *MAC* E-13  
    displacement, *ODT* 2-7, 3-7, 3-25, 3-26  
    instruction addressing, *MAC* 5-8  
    relative, offset, *ODT* 2-4, 3-7, 3-25
- Breakpoint, *INT* 5-6, *ODT* 1-3, 2-7, 2-8  
    address register, *ODT* 2-5, 3-13, 3-17  
    commands, task, *ODT* 3-15  
    instruction, register, *ODT* 2-5, 3-13  
    proceed count, register, *ODT* 2-5, 3-14  
    trap, *ODT* 1-3
- BRU (Back-Up and Restore Utility),  
    changes in, *RLN* 41-42  
    command line descriptions, *UTL* 10-10  
    command qualifiers, *UTL* 10-2 to 10-21  
    defaults for, *UTL* 10-1 to 10-3  
    descriptions of, *UTL* 10-13 to 10-21  
    disk and tape device information, *UTL* 10-7  
    to 10-10  
    disk volume labels and backup set names,  
    *UTL* 10-9  
    Files-11 structures, *UTL* 10-7, 10-8  
    supported devices, *UTL* 10-9, 10-10  
    error messages, *UTL* 10-28 to 10-45  
    multivolume tape operations, *UTL* 10-27  
    new switches, *RLN* 34
- BRU (Cont.),  
    tape format information, *UTL* 10-26  
    using,  
        for data transfers, *UTL* 10-24, 10-25  
        to initialize disks, *UTL* 10-8, 10-23  
        with BAD, *UTL* 10-22  
        with FMT, *UTL* 10-22
- Bucket, *RMU* 1-34  
    initialization, *RMU* 4-1  
    locking, *RMU* 2-9, 2-12  
    overhead, *RMU* 5-4, 6-2  
    pointer, *RMU* 5-6  
    size, *RMU* 6-16  
    split, *RMU* 6-2, 6-3  
    target data, *RMU* 5-10, 5-12  
    unlocking, *RMU* 2-9, 2-12
- Buffer, big, *IOP* 2-17, 2-21, 2-39
- Buffer count, *IOP* 2-18, 2-19
- Buffer(s),  
    control, *DRV* 14-9  
    data, *DRV* 14-9  
    EDT text, *UTL* 2-1  
    error log, *CDA* 1-7, 3-14  
    input, reading data from, *DRV* 16-18  
    I/O, *RMC* 1-6, *RMU* 1-29  
    multiple, *RMU* 2-19  
    record header, *RMC* 4-23  
    RMS-11, *RMU* 3-12  
        control of, *RMC* 1-6  
    text, *DEV* 1-1  
    typeahead, *BEG* 1-6, *RLN* 4  
    user, *RMC* 8-23, *RMU* 1-29  
        control of, *RMC* 1-6  
        special, *WRT* 6-9  
    user record, *IOP* 2-10, 3-6, 3-7, 3-9,  
    3-19, 3-20, 3-25
- BYE command, *MCR* 2-15, 4-27
- Byte,  
    DPB size, *DRV* 1-2, C-1  
    least significant, *RMU* 6-4, 6-5  
    most significant, *RMU* 6-4 to 6-6  
    null, *RMU* 2-5, 3-2
- Byte data,  
    allocating, *MAC* 6-17
- Byte mode, *ODT* 3-2  
    ASCII character, print, *ODT* 3-31, 3-34  
    octal, *ODT* 3-31, 3-34
- C**
- Cache, *RMU* 4-16
- Calling sequence, *RMC* 1-20

RSX-11M V03.2 Master Index

- Cancel I/O entry point, *RLN* 28, *WRT* 2-4, 3-2, 4-10
- Cancel Mark Time Requests, *EXE* 6-27
- Card reader, *DRV* 11-1
  - control characters, *DRV* 11-8
  - data formats, *DRV* 11-9
  - driver, *DRV* 11-8, 11-9
  - input errors, recovery
    - procedures for, *DRV* 11-3
- Carriage control, *RMU* 1-39
- Carriage return, *BEG* 1-4, 1-8, *MCR* 2-2, *ODT* 3-2
  - control, *RMC* 3-44
- Cassette, *DRV* 9-5, 9-6
  - block length, *DRV* 9-7
  - driver, *DRV* 9-1
  - recovery procedure, *DRV* 9-5
- CDA (Crash Dump Analyzer), *WRT* 3-17
  - analysis with,
    - optional information for, *CDA* 3-15
    - system information for, *CDA* 3-1 to 3-15
  - changes in, *RLN* 23
  - command lines, *CDA* 1-4 to 1-6
  - error messages, *CDA* A-1
  - indirect command files with, *CDA* 1-7
  - listings,
    - analyzing using, *CDA* 4-1 to 4-3
    - output, *CDA* 1-7
  - obtaining crash dumps with, *CDA* 1-3, 1-4
  - running, *CDA* 1-4
  - switches,
    - analysis, *CDA* 2-1 to 2-5
    - function, *CDA* 2-5 to 2-8
    - new, *RLN* 34
  - system requirements for, *CDA* 1-1 to 1-3
- Cell, *RMU* 1-17
- Central processing unit, see CPU
- Channels,
  - reading sequential analog input, *DRV* 14-5, 15-17, 18-39
- Characters,
  - control, see Control characters
  - double-quote, *ODT* 3-35
  - illegal, *MAC* 3-3
  - print byte mode ASCII, *ODT* 3-31, 3-34
  - print word mode ASCII, *ODT* 3-31, 3-35
  - prompting, *ODT* 3-1
  - Radix-50, *ODT* 3-36
  - separating and delimiting, *MAC* 3-2
  - set of, *MAC* 3-1
  - single-quote, *ODT* 3-34
- Characters (Cont.),
  - special, *MAC* B-1
    - in macro arguments, *MAC* 7-6
    - substitution of, *MAC* 7-16
- Checkpoint, *INT* 3-5
- Checkpointing, *EXE* 6-19, *INT* 3-5, 3-7, *RMU* 8-30
- Checkpoint space,
  - allocating dynamic, *INT* 3-6, *MCR* 4-135
  - allocating static, *INT* 3-6
- Checksum processing of files,
  - with PAT, *UTL* 18-7
  - with SLP, *UTL* 17-3, 17-16
- Circumflex (^), *ODT* 3-5
- CLI (Command Line Interpreter),
  - component of Queue Manager, *UTL* 7-1
- Clock queue, *CDA* 2-3, 3-44, B-26, C-9, *INT* 3-7
  - control blocks, *CDA* 3-44, B-26, C-9
  - entries, *MCR* 4-143
- Close, *RMC* 3-29, 8-2
- Cluster size, *RMC* 3-50
- CMP (File Compare Program),
  - command line, *UTL* 16-1
  - error messages, *UTL* 16-6
  - formats for output files, *UTL* 16-4
    - change bar format, *UTL* 16-5
    - differences format, *UTL* 16-4
    - SLP command input format, *UTL* 16-6
  - switches, *UTL* 16-2, 16-3
    - default settings for, *UTL* 16-3
- COBOL, *BEG* 2-1, *INT* 2-2, 5-3, 5-4, *RLN* 22
- Code,
  - binary, *BEG* 2-1
  - duplicating, *MAC* 7-17
  - machine-readable, *BEG* 2-11
  - object, *RMU* 1-28, 8-1
  - position-independent, see Position-independent code
  - protection, *RMC* 5-64, *RMU* 2-2, 2-6
  - shareable, *INT* 5-5
  - status, *RMC* 3-54
- Code and data,
  - separation, *MAC* 6-38
  - sharing, *MAC* 6-38
- Codes,
  - abort, *CDA* B-20, C-2
  - condition, *ODT* A-2
  - directive, *DRV* B-3, *EXE* C-1
  - error, see Error codes



- Codes (Cont.),
  - error completion, *RMC* A-1
  - I/O function, *DRV* B-3
  - I/O status, *DRV* B-1
    - error, *DRV* B-1
    - return, *DRV* 1-31
    - success, *DRV* B-3
  - magnetic tape function, *RLN* 6-7
  - op, *MAC* 2-4, C-1
  - return, *DRV* 1-28, 1-29, 1-31
  - status, see Status codes
  - success, *DRV* B-3
  - success completion, *RMC* A-1
  - task image error, *ODT* 5-2
- Coding standard, *MAC* E-1, *MCR* 2-1
- Colon, *MAC* 3-1
- Comma, *MAC* 3-2
- Command decoder routines, *ODT* 1-1
- Command files, indirect, see Indirect command files
- Command input,
  - errors, *ODT* 5-1
- Command interpreter, *RMU* 9-12, 9-21, 9-32, 9-52, 9-61, 9-68
- Command line,
  - format for *ODT*, *ODT* 4-1
  - format for utilities, *UTL* 1-4
  - MCR*,
    - examples of file name, *MCR* 3-8
    - standard format for, *MCR* 3-3 to 3-5
  - processing, *IOP* 6-1
  - subset, *ODT* 4-3
- Command Line Interpreter, see *CLI*
- Command-line processing,
  - CSI* - command string interpreter, *IOP* 6-1, 6-13 to 6-29
  - GCML* - get command line, *IOP* 6-1, 6-2 to 6-13
- Commands,
  - back-arrow, *ODT* 2-4, 3-6, 3-26
  - BASIC MCR*, *SSG* 2-1, 2-2
  - EDI*, *UTL* 3-10 to 3-49
  - EDT*, *UTL* 2-5 to 2-10, 2-20 to 2-47, 2-60, 2-61
  - effective address search, *ODT* 3-23, B-1 for utilities,
    - summary of, *UTL* A-1
  - initialization, *MCR* 4-6
  - listing, *ODT* 3-29
  - MCR*, see *MCR*
  - offset calculation, *ODT* 3-25
- Commands (Cont.),
  - privileged, *INT* 4-1
  - program execution, *ODT* 3-17
  - Queue Manager,
    - nonprivileged, *UTL* 6-9 to 6-19
    - privileged, *UTL* 7-4 to 7-11
    - set-up, *UTL* 7-2 to 7-4
  - relocation calculator, *ODT* 3-29
  - relocation register, *ODT* 3-27
  - single-instruction mode, *ODT* 3-19
  - SLP* edit, *UTL* 17-5
  - task breakpoint, *ODT* 3-15
  - word/byte search, *ODT* 3-21, 3-23, B-1
- Command string interpreter, see *CSI*
- Comment field, *MAC* 2-5
  - indicator, *MAC* 3-2
- Comments, *MAC* 6-14, E-2, *MCR* 4-3, 5-3
- Common blocks, see Blocks
- Communication, *BEG* 1-1
- Compile, *BEG* 2-1, 2-11
- Compiler, *FORTTRAN IV*, *BEG* 2-11
- Compiler languages, see Languages
- Compilers, *INT* 2-2, *RMU* 1-28, 8-1
  - defaults for, *BEG* 2-11
  - nonresident, *BEG* 2-13, 2-14
  - switches, *BEG* 2-12
- Compiler task, *FOR*, *MCR* 7-1
- Computer languages, see Languages
- Concatenate, *RMU* 8-2
- Conditional assemblies,
  - listing, *MAC* 6-4
- Conditional assembly,
  - block, *MAC* 6-41
  - directive, *MAC* 6-41, 6-42
  - immediate, *MAC* 6-46
- Conditional branches, *MAC* E-13
- Connect, *EXE* 4-1, 4-2, 6-29
- Console,
  - driver, *GEN* C-1 to C-8, *RLN* 2
  - listing device, *ODT* 3-13, 3-29
- Console log file, *RLN* 2
- Console output device (*CODRU*), *RLN* 40
- Console output task, see *COT*
- Context switching, *ODT* A-2
- Continuation Bucket, *RMU* 5-6
- Control blocks, *RMU* 2-2
  - AST*, *CDA* 3-17, B-39, C-34
  - clock queue, *CDA* 3-44, B-26, C-9
  - logical assignment, *CDA* B-25, C-25
  - task, *CDA* 2-2, 3-15, 3-17, 3-28, B-15, C-39, *MCR* 4-21, 4-146, 4-173

RSX-11M V03.2 Master Index

Control characters, *DEV* 3-5, *MCR* 2-1  
  card reader, *DRV* 11-8  
  terminal, *BEG* 1-3, 1-5, 1-6, *DRV* 2-25,  
    2-27, *MCR* 2-1 to 2-5  
Control flags, *RMU* 5-4  
Control function, *WRT* 2-16  
  mask, *WRT* 4-12  
Controller information, *CDA* 2-3, 3-45  
Controller number, *WRT* 2-13, 4-18, 4-27  
Controller Request Block, see *KRB*  
Control Status Register, see *CSR*  
Control structure, *RMU* 1-30  
Control switches,  
  function, *MAC* 8-6  
  listing, *MAC* 8-6  
Conversion routine(s),  
  date and time format, *SLR* 6-2  
  input data, *SLR* 4-1 to 4-9  
  output data, *SLR* 5-1 to 5-11  
*CORAL-66*, *INT* 2-2, 5-3, 5-5  
COT (Console Output Task), *GEN* C-1  
  to C-8, *RLN* 5-40  
Co-trees, *RMU* 8-6, *TKB* 4-28  
Count,  
  instruction, *ODT* 3-20  
  proceed, *ODT* 3-18  
Count field, *IOP* 1-6  
CPU (Central Processing Unit), *INT* 3-3  
Crash Dump Analyzer, see *CDA*  
Crash dumps,  
  analyzing with *CDA*, *CDA* 3-1 to 3-15  
  obtaining with *CDA*, *CDA* 1-3, 1-4  
  *RMS-11*, *RMU* 9-8  
CRC (Cyclic Redundancy Check), *DRV* 12-10  
CRF (Cross-Reference Processor), *MAC* 8-8,  
  *UTL* D-1  
  generating an assembly cross-reference  
    with, *MCR* 3-6  
  global cross-reference in, *DEV* 4-4  
  overview of, *DEV* 1-6  
Cross-Reference Processor, see *CRF*  
CSI (Command String Interpreter), *IOP* 2-2,  
  6-1, 6-13 to 6-29  
CSR (Control Status Register), *WRT* 4-18  
Current location counter, *MAC* 2-2, 3-11  
  to 3-13  
  directives, *MAC* 6-29  
Cyclic Redundancy Check, see *CRC*

**D**

Data, *RMU* 2-1, 5-2  
  analog, inputting, *DRV* 14-5, 15-17,  
    18-13, 18-37

Data (Cont.),  
  back-up, *RMU* 9-10  
  bases, accessing, *WRT* 2-9  
  buckets, *RMU* 5-5  
  caching, *RMU* 8-30  
  conversion routines,  
    input, *SLR* 4-1 to 4-9  
    output, *SLR* 5-1 to 5-11  
  floating-point, *MAC* 6-26  
  formats,  
    card reader, *DRV* 11-9  
    file-structured device, *IOP* 1-5, 1-6  
    *TKB* input, *TKB* A  
  integrity, *RMU* 2-9  
  mode, *MCR* 5-21  
  numeric, *RMU* 1-12  
  organization, *RMU* 1-10  
  processing, *RMU* 1-11, 1-25  
  reception, *EXE* 6-95, 6-97, 6-99  
  record, *RMU* 5-12  
  storage,  
    control in assembly language, *DEV* 1-3  
    definition of *MACRO-11*, *DEV* 2-8  
    directives, *MAC* 6-17  
    disk, *DEV* 1-10  
    mass, *RMU* 1-1  
    program section for, *DEV* 2-8  
  structures,  
    building, *TKB* 2-1  
    for I/O, *WRT* 2-5  
    interrelationships of, *WRT* 2-17  
    for I/O drivers, *WRT* 4-1 to 4-26  
    logical, *RMU* 1-14  
    overlay, *TKB* 4-20  
    RDB (Region Definition Block),  
      *EXE* 3-10 to 3-14  
    summary of, *WRT* 2-20  
    system, *WRT* C-1  
    *TKB*, *TKB* 2-14 to 2-16, 4-20, 4-21  
    user, *EXE* 3-10  
    WDB (Window Definition Block),  
      *EXE* 3-10, 3-14 to 3-18  
  transfer modes, *IOP* 1-6  
  transfers,  
    with *BRU*, *UTL* 10-24, 10-25  
    with *DSC*, *UTL* 11-23 to 11-26  
    with *FLX*, *UTL* 5-1  
  transmission, *EXE* 6-119  
Database management systems, see *DBMS*  
Dataset descriptor, *IOP* 1-9, 1-10, 2-14,  
  2-28 to 2-30, 3-4, 3-5, 3-15, 4-8 to 4-11

RSX-11M V03.2 Master Index

- Date, *MAC* 6-8
  - setting current, *MCR* 4-130
- Date and time format conversion routine,  
*SLR* 6-2
- DBMS (Database management systems),  
*RLN* 21
- DCB (Device Control Block), *CDA* 2-3, 2-4,  
3-31, 3-36, B-8, C-13, *WRT* 2-5, 2-17,  
2-19, 3-3, 4-7
  - and I/O drivers, *WRT* 2-5, 4-1, 4-7 to 4-15
- Debugging,
  - FORTTRAN IV, *DEV* 7-6, 7-7
  - location counter in, *DEV* 5-3, 5-4
  - MACRO-11, *DEV* 7-6, 7-7
  - on-line, *ODT* 1-2 to 1-4
  - tasks, *DEV* 4-5, 4-6, 7-5 to 7-7,  
*INT* 5-6
    - user-written I/O drivers, *WRT* 3-12 to 3-25
- Decimal radix, *RMC* 1-2, 1-10, *RMU* 9-29
- DECnet-11, *INT* 2-3
- DECprinters, *DRV* 2-3, 3-3, 10-2
- DEC Standard Editor, see *EDT*
- DECtape, *DRV* 6-6, 6-7
  - driver, *DRV* 6-1
  - file structure, *IOP* 5-1
  - recovery procedures for, *DRV* 1-35, 6-6
  - transfers, *DRV* 6-7
- DECtape II driver, *DRV* 7
- DECwriters, *DRV* 2-3, 3-3, 3-28
- Default values, *ODT* 4-1
- Deferred addressing indicator, *MAC* 3-2
- Delta time,
  - schedule, *EXE* 6-112
- Design, *RMU* 2-3
- Despool Prototype Task, see *LPP*
- Device (see also Devices),
  - buffer size word, *IOP* 4-10
  - characteristics, *WRT* 4-23, 4-24
  - characteristics byte, *IOP* 4-9
  - cluster number, *RMC* 5-7
  - commons, *SSG* 8-2
  - control routine, *IOP* 4-24
  - drive modification, *ERL D*
  - driver,
    - loadable, *MCR* 4-157, 4-185
    - modifying, *ERL D*-1
  - error reports, *ERL* 4-2
  - errors, *ERL* 1-2
  - ID, *RMC* 1-16, 6-2
  - independence, *INT* 6-6
  - information, *CDA* 3-31
  - interrupt entry point, *WRT* 2-3, 3-2
- Device (Cont.),
  - interrupt vector, *WRT* 2-9, 2-13, 3-3,  
3-6, 4-17, 4-26
  - mnemonics, *DRV* 1-17
  - name field, *IOP* 2-34, 4-8
  - registers, *MAC E*-2
  - sharing, *INT* 2-3
  - timeout, *WRT* 4-17
    - entry point, *WRT* 2-4, 3-2, 4-10
- Device Control Block, see *DCB*
- Devices (see also Device),
  - allocating, *INT* 4-4, *MCR* 2-16, 4-16
  - console listing, *ODT* 3-13, 3-29
  - deallocating, *MCR* 2-16, 4-31
  - dismounting, *MCR* 4-36
  - displaying status of known, *MCR* 4-32
  - file-structured,
    - data formats for, *IOP* 1-5, 1-6
  - logical, *MCR* 2-12, 2-13, *RMU* 1-14
    - assigning, *MCR* 2-13, 4-18
    - table, *MCR* 2-13
  - new, list of, *RLN* 1
  - null, *MCR* 2-12
  - peripheral, *INT* 1-1, *MCR* 2-9 to 2-11
    - supported on RSX-11S, *SSG* 1-2
  - physical, *BEG* 3-2
    - names for, *DRV* 1-17
  - print despooling, *INT* 6-3
  - private, *INT* 4-4, *MCR* 2-16
  - pseudo, *BEG* 2-15, 3-2, *MCR* 2-9, 2-11
    - names for, *DRV* 1-19
    - redirecting, *MCR* 2-11, 2-12
  - public, *INT* 4-4, *MCR* 2-16
  - redirecting, *MCR* 2-12
  - resident common, *TKB* 3-19
  - RSX-11M, *DRV* 1-2
  - tape, see *Tape devices*
  - unit record, *RMC* 3-45
  - unowned, *MCR* 2-16
  - verifying, with *BAD*, *UTL* 9-3
- Device-unit,
  - default, *MCR* 3-6
  - name, *MCR* 2-9, 2-10, 3-4
- Diagnostic error message summary, *MAC D*-1
- Diagnostics, *DRV* 7-4, *MAC* 7-14
  - disk drive compatibility, *UMD* 13-1
  - service-mode user,
    - error messages, *UMD A*-3
    - initiation of, *UMD A*-2
    - multidevice testing in, *UMD A*-5
  - user-mode,
    - error messages, *UMD* 2-4

- Diagnostics, user mode (Cont.),  
 for disk drive compatibility, *UMD* 13-1  
 for line printers, *UMD* 12-1  
 for RF11 fixed-head disks, *UMD* 4-1  
 for RK05 cartridge disk, *UMD* 5-1  
 for RK05F fixed disk, *UMD* 5-1  
 for RK06 and RK07 cartridge disk,  
     *UMD* 6-1  
 for RP02, RPR02, RP03, *UMD* 7-1  
 for RP04, RP05, RP06 pack disks,  
     *UMD* 3-1  
 for RS03 or RS04 fixed-head disk,  
     *UMD* 8-1  
 for terminals, *UMD* 12-1  
 for TU10 or TS03 magnetic tape,  
     *UMD* 11-1  
 for TU16 or TU45 magnetic tape,  
     *UMD* 10-1  
 for TU56 DECTape, *UMD* 9-1  
 initiation of, *UMD* 2-3  
 logical block numbers from physical  
     address, *UMD* 2-7  
 multidevice testing, *UMD* 2-6  
 updates in, *RLN* 39
- DIBOL, *RMU* B-1
- DIC (Directive Identification Code),  
     *EXE* 1-2, C-1
- Direct assignment operator, *MAC* 3-1
- Direct assignment statements, *MAC* 3-7
- Directive,  
     categories, *EXE* 6-1  
     codes, *DRV* B-3  
     conventions, *EXE* 6-5  
     macros,  
         executive, *DRV* 1-1, 1-8, 1-15, 1-16, 1-20,  
             1-22, 1-23  
         using, *EXE* 1-4, 1-5
- Directive Identification Code, see DIC
- Directive Parameter Block, see DPB
- Directive(s),  
     assembler, *MAC* 6-1, B-2  
         types of, *DEV* 1-3  
     data storage, *MAC* 6-17  
     event-associated, *EXE* 6-2, 6-3  
     executing, *DRV* 1-15  
     function, *MAC* 6-13  
     functions of system, *INT* 3-8  
     identification codes for, *EXE* C-1  
     indefinite repeat block, *MAC* 7-15  
     informational, *EXE* 6-2  
     intertask communications-related,  
         *EXE* 6-3
- Directive(s) (Cont.),  
     I/O-related, *EXE* 6-3  
     listing control, *MAC* 6-1  
         symbolic arguments of, *MAC* 6-3, 6-4  
     location counter, *MAC* 6-29  
     LUN reassignment, *RLN* 27  
     macro, *MAC* 7-1  
     MACRO-11, *MAC* 2-5, 5-9, 6-1, C-4  
     macro attribute, *MAC* 7-11  
     macro library, *MAC* 7-18  
     .MCALL, *RMC* 1-2, 1-3, 1-4  
     MCR AT.,  
         described, *MCR* 5-11 to 5-37  
         listed, *MCR* 5-3 to 5-5  
     memory management, *EXE* 3-1, 6-3, 6-4,  
         *INT* 3-1, 3-10  
     nested conditional, *MAC* 6-43  
     numeric, *MAC* 6-26  
     ODL for, *TKB* 4-22  
     parent/offspring tasking, *EXE* 4-1, 4-2, 6-4  
     PLAS, *INT* 1-2  
     processor, *MCR* 5-2  
     program boundaries, *MAC* 6-31  
     QIO, *EXE* 6-90, *WRT* 2-2, 2-16  
     recommended use of, *DEV* 2-3, 2-5 to 2-8  
     repeat block, *MAC* 7-17  
     STOP bit synchronization, *RLN* 2, 6  
     summary of, *EXE* A-1  
     symbol control, *MAC* 6-39  
     system,  
         definition of, *EXE* 1-1  
         DIR\$ macro, *EXE* 1-7  
         error returns, *EXE* 1-3  
         FORTRAN subroutines, *EXE* 1-9 to 1-16  
         functions of, *EXE* 1-1, *INT* 3-7 to 3-9  
         get LUN information, *IOP* 2-18  
         implementing, *EXE* 1-1  
         I/O-related, *IOP* C-1  
         macro name conventions for,  
             *EXE* 1-5 to 1-7  
         processing of, *EXE* 1-2  
         restrictions for nonprivileged task,  
             *EXE* 1-18, 1-19  
         summary of, *EXE* 6-2 to 6-4, A-1  
         task states, *EXE* 1-16 to 1-18  
         task execution control, *EXE* 6-1, 6-2  
         task status control, *EXE* 6-2  
         trap-associated, *EXE* 6-3
- Directive Status Word, see DSW
- Directory,  
     device, *RMU* 1-37  
     entries, *IOP* 5-2

- Directory (Cont.),
  - files, *IOP* 5-2
  - identification information, *IOP* 4-10, 4-16
- Disk drive compatibility, diagnostics for, *UMD* 13-1
- Disks, *RMU* 1-11
  - backing up, with BRU, *UTL* 10-24
  - drivers for, *DRV* 5-1
  - file structure of, *IOP* 5-1
  - powerfail recovery for, *DRV* 1-35
  - private, *DEV* 1-10
  - public, *DEV* 1-10
  - RF11/RS11 fixed-head, *DRV* 5-1
  - RK11/RK05 cartridge, *DRV* 5-3
  - RK611/RK06 cartridge, *DRV* 5-3
  - RP04, RP05, RP06 pack, *DRV* 5-3
  - RP11/RP02 pack, *DRV* 5-1
  - RS03 fixed-head, *DRV* 5-1
  - RS04 fixed-head, *DRV* 5-1
  - RX10/RX01 flexible, *DRV* 5-3
- Disk Save and Compress Program, see DSC
- Disk Volume Formatter, see FMT
- Dispatching,
  - executive-level, *EXE* 5-5, 5-6
- Displacements,
  - branch, *ODT* 2-7, 3-7, 3-25, 3-26
- DMP (File Dump Utility),
  - command line, *UTL* 15-2
  - error messages, *UTL* 15-6
  - mode,
    - device, *UTL* 15-1
    - file, *UTL* 15-1
    - switches, *UTL* 15-2 to 15-6
    - new, *RLN* 34
- DOS-11, *INT* 6-1
  - format, *MCR* 3-1
- Double ASCII character indicator, *MAC* 3-2
- DPB (Directive Parameter Block), *DRV* 1-12, *EXE* 1-2, 1-4, 1-6, *WRT* 2-5, 2-8, 2-16 and I/O drivers, *WRT* 4-5
- Drivers,
  - analog-to-digital converter, *DRV* 14-1
  - card reader, *DRV* 11-1
  - cassette, *DRV* 9-1
  - DECtape, *DRV* 6-1
  - DECtape II, *DRV* 7-1
  - disk, *DRV* 5-1
  - graphics display, *DRV* 20-1
  - industrial control subsystems, *DRV* 18-1
  - I/O, *INT* 6-6
    - code for, *WRT* 3-2, 3-3
- Drivers, I/O (Cont.),
  - data structures for, *WRT* 4-1, 4-2
  - debugging, *WRT* 3-12 to 3-25
  - duplex, differences between, *RLN* 28, 29
  - entry points for, *WRT* 2-3, 2-4, 3-2
  - executive services available to, *WRT* 2-10 to 2-12
    - conditional routines, *WRT* 5-1
    - service calls, *WRT* 5-1
    - system-state register convention, *WRT* 5-1
  - fork list and, *WRT* 2-9
  - function of, *WRT* 1-1
  - I/O packet and, *WRT* 2-8, 2-16, 4-2, 4-18
  - I/O queue and, *WRT* 2-8, 2-16
  - loadable, *WRT* 3-3, 3-8 to 3-10, 4-26
    - assembling, *WRT* 3-10
    - loading, *WRT* 3-12
    - rebuilding, *WRT* 3-27
    - source code for, *WRT* 3-2, 3-3
    - specifying support for, *WRT* 3-2
    - task-building, *WRT* 3-10 to 3-12
  - message-oriented communication, *DRV* 12-1
  - multicontroller, *WRT* 2-13, 4-27
  - non-MASSBUS NPR, *WRT* B-1
  - NPR device, *WRT* 4-25, B-1
  - paper tape punch, *WRT* 6-3
  - resident, *WRT* 3-2, 3-3, 3-6, 3-25, 4-26
  - RSX-11S, *INT* 1-1
  - UCB and, *WRT* 2-6, 2-18, 2-19, 3-3, 4-19
  - user-written,
    - changes in, *RLN* 37
    - debugging, *WRT* 3-12 to 3-25
    - inclusion of,
      - data base and driver source in, *WRT* 6-2 to 6-8
      - device description in, *WRT* 6-1
      - special user buffers in, *WRT* 6-8 to 6-10
    - loadable, *WRT* 3-8 to 3-12
    - overview of, *WRT* 3-1 to 3-5
    - rebuilding, *WRT* 3-25 to 3-27
    - resident, *WRT* 3-1 to 3-5
  - writing,
    - data structures in, *WRT* 4-1 to 4-26
    - INTSV\$ macro and, *WRT* 4-28, 4-29
    - multicontroller, *WRT* 4-27, 4-28
  - XDT and, *WRT* 3-14, 3-15, 3-18
- K-series peripheral support routine, *DRV* 22-1

## Drivers (Cont.),

- laboratory peripheral accelerator, *DRV* 21-1
  - laboratory peripheral systems, *DRV* 16-1
  - line printer, *BEG* 4-11, *DRV* 10-1, *RLN* 1  
KMC11, *RLN* 7, 32
  - magnetic tape, *DRV* 8-1
  - message-oriented communication, *DRV* 12-1
  - null device, *DRV* 19-1
  - paper tape reader/punch, *DRV* 17-1
  - PCL11 parallel communications link,  
*DRV* 13-1
  - terminal, see Terminal drivers
  - unibus switch, *DRV* 23-1
  - universal digital controller, *DRV* 15-1
- DSC (Disk Save and Compress Program), *MCR* 4-147
- bad block information with, *UTL* 11-10  
to 11-13
  - command format, *UTL* 11-7
  - error messages, *UTL* 11-26 to 11-39
  - file label, *UTL* 11-8, 11-9
  - initiating,
    - on-line, *UTL* 11-6
    - stand-alone, *UTL* 11-6
  - merge mode operation, *UTL* 11-19
  - operation,
    - data transfers, *UTL* 11-23 to 11-26
  - options, *UTL* 11-8
  - supported volumes for, *UTL* 11-5
  - switches, *UTL* 11-8, 11-10 to 11-16,  
11-18 to 11-22
    - new, *RLN* 34
    - stand-alone, *UTL* 11-20
  - terminating,
    - on-line, *UTL* 11-6
    - stand-alone, *UTL* 11-6
- DSW (Directive Status Word), *EXE* 1-2,  
*IOP* 2-41, I-1
- register, *ODT* 2-5, 3-11
- Dumps,
- file, with DMP, *UTL* 15-1
  - panic, *WRT* 3-16, 3-17, 3-19
  - system crash,
    - analyzing, with CDA, *CDA* 3-1 to 3-15
    - obtaining, with CDA, *CDA* 1-3, 1-4
  - task,
    - postmortem (PMD), *INT* 5-7, *MCR* 4-10,  
*RLN* 36, *TKB* 8-1 to 8-5
    - snapshot, *INT* 5-6, 5-7, *RLN* 36,  
*TKB* 8-5 to 8-11

## E

- EDI (Line Text Editor), *BEG* 2-1, *INT* 5-1
- command conventions, *UTL* 3-8
  - commands, basic, *BEG* 2-3 to 2-9,  
*UTL* 3-10 to 3-49
    - function summary of, *UTL* 3-20 to 3-26
    - reference summary of, *UTL* 3-27 to 3-49
  - creating files with, *BEG* 2-2, *UTL* 3-1
  - editing files with, *BEG* 2-4
  - error messages, *UTL* 3-50
  - examples of, *UTL* B-1
  - file names, *BEG* 2-2
  - file specifications, *UTL* 3-2
    - defaults for, *UTL* 3-2, 3-3
  - file specifier, *BEG* 2-2
  - file type, *BEG* 2-2
  - file version numbers, *BEG* 2-7
  - invoking, *BEG* 2-2, *UTL* 3-1, 3-2
  - modes,
    - control,
      - edit mode, *BEG* 2-4, *UTL* 3-3
      - input mode, *BEG* 2-3, *UTL* 3-3
    - text access,
      - block mode, *UTL* 3-4
      - line by line mode, *UTL* 3-4
  - notes on using, *UTL* 3-49
- Editors,
- batch,
    - SLP, *UTL* 17
  - interactive,
    - EDI, *INT* 5-1, *UTL* 3
    - EDT, *INT* 5-2, *UTL* 2
  - text, *DEV* 1-1
- EDT (DEC Standard Editor),  
*INT* 5-1, 5-2
- buffers,
    - text,
      - alternate, *UTL* 2-1
      - main, *UTL* 2-1
  - command line, *UTL* 2-2, 2-4
  - commands,
    - back-up, *UTL* 2-1
    - described, *UTL* 2-20
  - I/O,
    - buffer, *UTL* 2-2
    - file, *UTL* 2-2
    - summary of, *UTL* 2-60, 2-61
    - table of, *UTL* 2-5, 2-6
  - error messages, *UTL* 2-62
  - files,
    - creating with, *UTL* 2-1
    - editing with, *UTL* 2-1

- EDT (Cont.),  
 file specifications for, *UTL* 2-2, 2-3  
 defaults for, *UTL* 2-4  
 invoking, *UTL* 2-2  
 modes,  
     character mode, *UTL* 2-1, 2-21,  
         2-48, 2-59  
     command mode, *UTL* 2-1 to 2-3,  
         2-20, 2-60  
         asterisk prompt for, *UTL* 2-2  
 options, *UTL* 2-19  
 range specifications, *UTL* 2-10  
 Effective address search command,  
     *ODT* 3-23, B-1  
 EFN (Event Flag Number), *EXE* 2-2, 6-5  
 EMT (emulator trap), *EXE* 1-1, 1-2, 1-4,  
     *MAC* 5-8  
 Emulator trap, see EMT  
 Entry points,  
     I/O initiator, *WRT* 2-4, 2-11, 3-2, 4-10  
     routine, *EXE* 2-4  
 Entry point table, *DEV* 6-4  
 ERF (error logging shutdown task), *ERL* 3-8  
     error messages, *ERL* 5-8, 5-9  
 ERL (error logger task), *ERL* A-1  
 ERRLOG (error logger), *ERL* 1-3, 2-1, 2-4,  
     3-1, 3-2, *INT* 4-5  
     error messages, *ERL* 5-1 to 5-9  
 Error codes,  
     directive, *DRV* B-3  
     executive, *EXE* B-1  
     IE.PRI, *RLN* 38  
     installation verification, *GEN* 10-14 to 10-16  
     I/O status, *DRV* B-1  
     MACRO-11, *MAC* D-1  
     mapping, *RMU* B-4  
     ODT, *ODT* 3-14, 5-2  
     standard, *EXE* 1-3, B-1  
 Error conditions, *IOP* 1-12  
     FORTRAN, *EXE* 1-15  
     severe, *RMC* A-2  
 Error detection, *ERL* 1-1  
     and recovery, *DRV* 18-66  
     by ODT, *ODT* 5  
         command input error, *ODT* 5-1, 5-2  
         task image error codes, *ODT* 5-2, 5-3  
 Error handling routines, *IOP* 1-12, 3-2, 3-19,  
     3-23, 3-31  
 Error log,  
     buffers, *CDA* 1-7, 3-14  
     file, *ERL* 1-3  
 Error log (Cont.)  
     preformatter task, see PSE  
     report generating task, see SYE  
     reports, *ERL* 4-1  
 Error logging, *INT* 4-4, 4-5, *WRT* 3-3  
     classes, *ERL* 3-5, 3-6  
     data formats, *ERL* B-1  
     device drive modification, *ERL* D  
 ERF (shutdown task),  
     messages, *ERL* 5-8  
     running, *ERL* 3-8  
 ERL (error logger task),  
     modifying at task build, *ERL* A-1  
 ERRLOG (error logger),  
     files, *ERL* 2-5  
     formats, *ERL* B  
     messages, *ERL* 5-1 to 5-4  
     running, *ERL* 3-1, 3-2  
 error log file, *ERL* 1-3  
 executive features of,  
     error message formatting routines,  
         *ERL* 2-3  
     error message queuing routine,  
         *ERL* 2-3  
     memory allocation routines, *ERL* 2-3  
 functions of, *ERL* 1-1  
 individual reports, *ERL* 4-1, 4-2  
 information from, *ERL* 1-3  
 interrupt reports, *ERL* 4-1, 4-2  
 interrupt timeouts, *ERL* 1-2  
 interrupts, undefined, *ERL* 1-2  
 messages, *ERL* 5-1 to 5-9  
 operating procedures, *ERL* 3-1  
 options, *ERL* 1-2  
 PSE (pre-formatter), *INT* 4-5  
     file, *ERL* 2-5  
     formats, *ERL* C-1  
     message, *ERL* 5-4 to 5-6  
     running, *ERL* 3-2, 3-3  
 purposes of, *ERL* 1-1  
 reports,  
     device error, *ERL* 4-2 to 4-5  
     device interrupt timeout, *ERL* 4-5  
     formatting, *ERL* 1-3  
     generating, *ERL* 1-3, 3-3, 4-1  
     individual, *ERL* 4-1 to 4-6  
     memory parity error, *ERL* 4-5  
     summary, *ERL* 4-8 to 4-12  
     undefined interrupt, *ERL* 4-1, 4-2  
     unexpected trap or interrupts, *ERL* 4-1,  
         4-2  
 subsystem, *INT* 4-4, 4-5

RSX-11M V03.2 Master Index

- Error logging (Cont.),
  - SYE (report generator), *ERL* 1-3, 2-6, *INT* 4-5
    - command line, *ERL* 3-4 to 3-8
    - invoking, *ERL* 3-3, 3-4
    - messages, *ERL* 5-6 to 5-8
    - modifying at task build, *ERL* A-1 to A-3
    - options for RP switch, *ERL* 4-6 to 4-8
    - report files, *ERL* 2-6
    - using, *ERL* 3-3 to 3-8
  - task interaction with, *ERL* 2-4
  - tasks, *ERL* 1-2
- Error messages,
  - ACNT, *MCR* 2-22, 2-23, *RLN* 42
  - BAD, *UTL* 9-8, 9-11
  - Basic MCR, *MCR* B-1, *SSG* 2-3
  - BRU, *UTL* 10-28
  - CDA, *CDA* A
  - CMP, *UTL* 16-6
  - command-related, *MCR* 4-9
  - command utilities, *RMU* E-9
  - DMP, *UTL* 15-6
  - DSC, *UTL* 11-26 to 11-39
  - EDI, *UTL* 3-50
  - EDT, *UTL* 2-62
  - ERF, *ERL* 5-8, 5-9
  - ERRLOG, *ERL* 5-1 to 5-4
  - error logging, *ERL* 5-1 to 5-9
  - FLX, *UTL* 5-16
  - FMT, *UTL* 8-8 to 8-12
  - formats for, *BEG* 1-12
  - FORTTRAN IV, *DEV* 7-4
  - LBR, *UTL* 14-33
  - MACRO-11, *DEV* 3-1, 3-2, *MAC* 8-14
  - MCR, *BEG* 1-12, *MCR* A-1
  - ODT, *DEV* 5-3, *ODT* 5-1 to 5-3
  - OTL, *SSG* 2-9
  - PAT, *UTL* 18-7 to 18-13
  - PIP, *UTL* 4-38
  - PRESRV, *UTL* 12-27
  - PRI and QUE, *UTL* 6-18 to 6-23
  - PSE, *ERL* 5-4 to 5-6
  - Queue Manager, *GEN* D-1, *UTL* 7-11
  - RMS-11, *RMU* 9-5
    - utilities, *RMU* E-1
  - RMSDEF, *RMU* E-1
  - RSX-11S, *SSG* A-1
  - service-mode user diagnostic, *UMD* A-3
  - SIP, *SSG* 2-16
  - SLP, *UTL* 17-20 to 17-24
  - SYE, *ERL* 5-6 to 5-8
  - TKB, *DEV* 4-1, *TKB* F-1
- Error messages (Cont.),
  - TKTN, *DEV* 4-6, *MCR* A-1, *RLN* 2-17, *SSG* 2-17
    - user-mode diagnostic, *UMD* 2-4
  - VMR, *GEN* 8-53 to 8-66
  - ZAP, *UTL* 19-16
- Error reporting, *DRV* 18-29, 18-30
- Error reports, see Error logging, reports
- Error routine address, *EXE* 1-7
- Error routines, executive, *ERL* 1-2, 1-3, 2-1
- Errors,
  - card input, *DRV* 11-3
  - detecting, see Error detection
  - device, *ERL* 1-2
  - hard, *ERL* 4-11
  - loggable, *ERL* 1-2
  - memory parity, *ERL* 1-2
    - reports on, *ERL* 4-5, 4-6
  - nonrecovered, *ERL* 4-11
  - recoverable, *INT* 4-5
  - recovered, *ERL* 4-11
  - reporting, see Error reporting
  - serial line, *DRV* 18-66
  - soft, *ERL* 4-11
- Error status, *EXE* 1-3
- Escape (<ESC>), *BEG* 1-8
- ESCAPE code conversion, *DRV* 3-29
- Escape sequences, terminal,
  - definition of, *DRV* 2-29, 3-22
- Event Flag Number, see EFN
- Event flags, *EXE* 2-1, *INT* 3-9, *IOP* 2-12, 2-17, 2-42, 2-43, 3-30
  - common, *EXE* 2-2
  - group global, *EXE* 2-2, 6-34, 6-53, 6-103, *RLN* 2
  - in I/O operations, *IOP* 2-42
  - local, *EXE* 2-2
  - setting, *EXE* 6-123
  - waiting for, *DRV* 1-23
- Events,
  - significant, *DRV* 1-10, *EXE* 1-3, 2-1, 6-45, *INT* 3-7
- Executive, *INT* 3-1, 3-3 to 3-5, *RMU* 1-14
  - building, *SSG* 4-6
  - control,
    - checkpoint, *INT* 3-5, 3-6
    - priority, *INT* 3-5
    - round robin scheduling, *INT* 3-6
    - significant events, *INT* 3-7
    - swapping, *INT* 3-6
    - task state, *INT* 3-4, 3-5
  - enhancements, *RLN* 2



Executive (Cont.),  
 error codes, *EXE* B-1  
 error routines, *ERL* 1-2, 1-3, 2-1, D-2  
 features for error logging, *ERL* 2-3  
 internal task scheduling, *INT* 4-2  
 object modules, *SSG* 4-6  
 region, *INT* 3-7  
 services and I/O drivers, *WRT* 2-10 to 2-12,  
 5-1  
 source file, updating, *RLN* 10-12  
 task-build command file, *SSG* 4-6  
 Executive Debugging Tool, see *XDT*  
 Executive directives, see Directives  
 Executive macro library (EXEMC.MLB),  
*DEV* 1-8  
 Exit, *EXE* 6-61  
 Extended Attribute Block, *RMC* 1-1, 1-13, 5-1  
 Extended Buffer Pool, *RMU* 8-28, 8-30

## F

F11ACP, *RMU* 1-33  
 file systems, *RLN* 42-43  
 correcting, *RLN* 15-18  
 FAB (File Access Block), *RMC* 1-1, 1-8, 3-1,  
*RMU* C-2  
 internal, *RMC* 1-8, 2-3, 3-34  
 Fast delete, *RMC* 4-25  
 Fast Task Builder (FTB), *DEV* 4-3  
 Fatal error crash routine, *RMC* A-2, A-18  
 Fault isolation, *WRT* 3-18 to 3-20  
 Fault tracing, *WRT* 3-20  
 FCB (File Control Block), *RMU* 8-27,  
*WRT* 2-17, 2-19  
 FCP (File Control Primitives), *RLN* 15-18,  
*WRT* 2-3  
 FCS (File Control Services), *INT* 1-2, 6-4,  
*IOP* 1-1, *RMC* 5-26, *RMU* 3-2, A-1, A-2,  
*WRT* 2-1, 2-2  
 for RSX-11S, *SSG* 2-21  
 library system generation options, *IOP* K  
 resident library,  
 building 4K, *GEN* G  
 spooling from user-written tasks with,  
*UTL* 6-17, 6-18  
 FCSRES resident library, changes in,  
*RLN* 37, 38  
 FDB (File Descriptor Block), *IOP* 1-2, 1-9,  
 1-10, 2-3 to 2-33, A-1  
 offsets, *IOP* 2-25 to 2-27  
 Fields,  
 access, in user control blocks, *RMC* 1-2  
 modify contents of, *RMC* 1-18, 7-6, 7-7, 7-9  
 FIFO, *RMU* 5-6, 5-11, 6-8  
 File, *INT* 6-1, *RMU* 1-1  
 File access,  
 methods of, *IOP* 1-2  
 optimizing, *IOP* 2-33 to 2-36  
 File Access Block, see FAB  
 File attributes, *RMU* 1-37  
 File back-up, *RMU* 9-10  
 File cluster with buckets, *RMU* 5-2, 6-17  
 File Compare Program, see CMP  
 File contents section, *DEV* 4-5  
 File contiguity, *RMU* 3-4, 3-6, 4-3, 4-5, 8-31,  
 D-2  
 File Control Block, see FCB  
 File Control Primitives, see FCP  
 File control routines, *IOP* 4-1  
 ASCII-to-binary UIC conversion, *IOP* 4-7  
 default directory-string, *IOP* 4-2, 4-3  
 default file-protection word, *IOP* 4-4, 4-5  
 default UIC, *IOP* 4-3, 4-4  
 device control, *IOP* 4-24  
 directory entry, *IOP* 4-13 to 4-15  
 file deletion, *IOP* 4-22 to 4-24  
 file extension, *IOP* 4-21  
 filename block, *IOP* 4-7 to 4-12, 4-16, 4-17  
 file owner word, *IOP* 4-5, 4-6  
 file pointer, *IOP* 4-17 to 4-19  
 file truncation, *IOP* 4-21  
 queue I/O function, *IOP* 4-19, 4-20  
 rename file, *IOP* 4-20  
 File Control Services, see FCS  
 File, data records in a, number of, *RMU* 6-18  
 File Descriptor Block, see FDB  
 File design, *RMU* 3-3, 3-4, 4-2, 4-3, 6-1, 6-2  
 File directory, *RMU* 1-33, 1-39, 3-1, 3-2, 3-5,  
 4-1, 8-26  
 master, see MFD  
 user, see UFD  
 File Dump Utility, see DMP  
 File extension, *IOP* 2-7, 3-35, 4-20, 4-21  
 File format, *MCR* 3-1  
 File header, *RMU* 8-26  
 File-header block format, *IOP* 3-4, 5-3, 5-4,  
 F-1  
 File-ID, *RMC* 1-16, 3-29, 6-6, *RMU* 8-31  
 File identification field, *IOP* 2-34, 3-4, 4-9,  
 4-12  
 File management, *RMU* 1-33, 3-1  
 File medium, *RMU* 1-37

RSX-11M V03.2 Master Index

- Filename block, *IOP* 1-10, 2-34 to 2-36, 3-4, 3-14 to 3-16, B-1
  - routines, *IOP* 4-7 to 4-12, 4-16, 4-17
- File names, *MCR* 3-4, 3-6
  - directory, *RLN* 42
- File number, *IOP* 5-2, 5-3
- File operation, *RMC* 1-2, 1-19, *RMU* 1-36
  - macros, *RMC* 1-21, 8-1
  - valid, *RMC* 3-23
- File organization, *INT* 6-5, *RMC* 3-43, *RMU* 1-5, 1-6, 1-7, 1-11, 1-16, 1-17, 1-37, 2-12, 2-14, 9-19, D-2
- File owner word format, *IOP* 4-5
- File pointer routines, *IOP* 2-9, 3-29, 4-17 to 4-19
- File processor, *RMU* 1-12
- File Processor, *RMU* 1-33
- File protection, *INT* 6-2, *MCR* 3-1, 3-2, *RMU* 1-37
  - access type, *MCR* 3-2, 3-3
  - assigning access rights, *MCR* 3-3
  - user groups, *MCR* 3-3
  - with PIP, *UTL* 4-25 to 4-27
- Files, *INT* 6-1
  - accessing, *MCR* 3-2, 3-3, *IOP* 1-2, 2-33
  - adding records to RMS-11, *RMC* 8-27
  - allocating, *IOP* 2-6 to 2-8, 3-11
  - appending, *UTL* 4-13
  - backing up, see BRU, DSC, PRESRV
  - checkpoint, *INT* 3-6, *MCR* 4-135
  - closing, *IOP* 3-18, *RMU* 1-37
    - RMS-11, *RMC* 8-2
  - command, indirect, see Indirect command files
  - comparing, *UTL* 16-1
  - container, *RMU* 9-13
  - contiguous, *BEG* 4-5
  - copying, *BEG* 4-10
    - DOS-11, *UTL* 5-3, 5-4
    - Files-11, with PIP, *UTL* 4-6
    - RT-11, *UTL* 5-3, 5-4
    - with FLX, *UTL* 5-3
  - correction, PAT, *UTL* 18-3
  - creating, *BEG* 2-2, 4-1, *IOP* 3-4, 3-8, 3-9, *RMU* 1-36
    - library,
      - macro, *DEV* 6-1, 6-2
      - object, *DEV* 6-4, 6-5
    - RMS-11, *RMC* 8-4
    - source, *DEV* 2-11, 7-2
    - with EDI, *BEG* 2-2, *UTL* 3-1
- Files, creating (Cont.),
  - with EDT, *UTL* 2-1
  - with SLP, *UTL* 17-14
  - creation date of, *RMC* 5-23
  - defining, *RMU* 1-10, 1-27
  - deleting, *BEG* 4-1, *UTL* 5-6
    - on system, *UTL* 4-16
    - on volumes, *UTL* 5-10, 5-11
  - RMS-11, *RMC* 8-8
  - despooling, *UTL* 6-1, 6-17, 7-1, C-1
  - directory, *IOP* 5-2
    - listings of, *DEV* 3-7
  - displaying, *BEG* 4-3, 4-4
  - dumping, with DMP, *UTL* 15-1
  - editing, *BEG* 2-4
    - source, *DEV* 2-11 to 2-17
    - with EDI, *UTL* 3-1
    - with EDT, *UTL* 2-1
    - with SLP, *UTL* 17-1
  - erasing, *RMU* 1-37
  - ERRLOG, *ERL* 2-4
  - error log, *ERL* 1-3
  - executable task image, *ODT* 4-1
  - extending, *RMU* 1-36
  - HELP,
    - creating, *MCR* 4-46
    - text, *GEN* H-1, H-2
  - index, see Index files
  - indexed, see Indexed files
  - indirect, *RMU* 9-6, 9-29
  - indirect command, see Indirect command files
  - input, *MCR* 3-3
  - library, format of, *UTL* 14-4
  - list, *RMU* 1-10
  - listing, see Listing files
  - load, *RMU* 6-30
  - locked, *BEG* 4-5, *IOP* 2-15, 2-16, *RMC* 3-30
  - logical beginning of, *RMC* 8-29
  - manipulating, *INT* 6-3
  - marking, for deletion, *IOP* 3-13
  - memory allocation (map), *ODT* 4-1
  - merging, *UTL* 4-7
  - noncontiguous, *BEG* 4-5
  - opening, *IOP* 3-2 to 3-11, *RMU* 1-36
    - by File-ID, *IOP* 2-13, 2-33 to 2-35, 3-13, 3-14
    - by filename block, *IOP* 3-14 to 3-16
  - output, see Output files
  - owning, *INT* 6-1, *MCR* 3-1
  - printing, *BEG* 4-11, *UTL* 4-33, 6-1, 7-1
  - processing, options for, *RMC* 3-28

- Files (Cont.),
- protecting, see File protection
  - purging, *BEG* 4-8, *DEV* 3-7, *UTL* 4-27
  - relative, organization of, *RMU* 1-17
  - renaming, *BEG* 4-10, 4-11, *UTL* 4-3, 4-28
  - secondary, *MCR* 5-31
  - sequential,
    - end-of-file for, *RMU* 3-2, 3-11
    - organization of, *RMU* 1-17
  - sharing, *INT* 2-3, *RMC* 1-22, 3-52, *RMU* 2-5
  - source, see Source files
  - spooling, *DEV* 3-6, *UTL* 4-33, 6-1, 6-17, 7-1, C-1
  - summary listing, *RMU* 9-12
  - superseding, *RMC* 3-29
  - SYE report, *ERL* 2-6
  - task image, see Task image files
  - task image symbol table, *ODT* 4-1
  - temporary, *IOP* 2-14, 3-12, 3-13, 3-17, 4-22, *RMC* 3-29
  - text, *BEG* 2-1
  - transferring,
    - with BRU, *UTL* 10-24
    - with DSC, *UTL* 11-23 to 11-26
    - with FLX, *UTL* 5-1
    - with PIP, *UTL* 4-6
  - truncating, *IOP* 2-9, 2-10, 3-6, 3-9, 4-21
  - UFDs for, *BEG* 3-4
  - user, structure of, *IOP* 5-1
  - user logon text, *BEG* 1-10
  - validating (verifying) contents of,
    - with PAT, *UTL* 18-7
    - with SLP, *UTL* 17-3, 17-16
  - versions of, *RMU* 9-5
  - write-shared, sequentially reading, *RMU* 7-10
- Files-11, *INT* 6-1, 6-4, *IOP* 5-1
- copying, files with PIP, *UTL* 4-6
  - directories (UFDs) for files, *INT* 6-1, 6-2, *MCR* 3-1, 3-2
  - ownership of files, *INT* 6-1, 6-2, *MCR* 3-1, 3-2
  - protection for files, *INT* 6-2, *MCR* 3-2, 3-3, *UTL* 4-25
    - access types, *MCR* 3-2
    - assigning access rights, *MCR* 3-3
    - user groups, *MCR* 3-3
    - structures for BRU, *UTL* 10-7
    - volume, *MCR* 3-1
- Files-11 Ancillary Control Processor, see F11ACP
- Files-11 ODS-1, *RMU* 1-14
- Files-11 ODS-2, *RMU* 1-14
- File sequence number, *IOP* 5-2, 5-3
- File size, *RMU* 2-3, 3-12, 4-6
- File specifications, *INT* 6-2, *IOP* 1-11, *RMC* 3-25, *RMU* 1-37
- conventions for, *TKB* 1-8
  - creating, within user program, *IOP* 2-27, 2-28
  - dataset descriptor in, *IOP* 2-28 to 2-30
  - default filename block in, *IOP* 2-31 to 2-33
  - defaults for, *TKB* 1-8
  - dynamic processing of, *IOP* 2-33
  - EDT, *UTL* 2-2
  - file name, *BEG* 3-1, 4-11
  - file type, *BEG* 3-1
  - file version, *BEG* 3-1, 4-11
  - FLX, *UTL* 5-2
  - format for IAS/RSX-11, *MAC* 8-13
  - for utilities,
    - defaults for, *UTL* 1-5, 1-6
    - format of, *UTL* 1-5
  - MCR*, *MCR* 3-3
  - PIP, *UTL* 4-1, 4-2
  - PRI and QUE, *UTL* 6-3, 6-9
  - RSX-11M, *BEG* 3-1
  - TKB*, *TKB* 1-8, 1-9
    - defaults for, *BEG* 2-15
  - UFD, *BEG* 3-1
  - UIC, *BEG* 3-1
- File storage Region, see FSR
- File structures, *IOP* 5-1, G-6, *RMU* 1-11, 1-28
- disk and DECTape (Files-11), *IOP* 5-1
    - directory files, *IOP* 5-2
    - file-header block, *IOP* 5-3, 5-4
    - index file, *IOP* 5-2
    - user file, *IOP* 5-1
  - in magnetic tape file processing, *IOP* 5-4 to 5-10
- File Structure Verification Utility, see VFY
- File system, *MCR* 3-1
- F11ACP, *RLN* 42, 43
    - correcting, *RLN* 15-18
  - Files-11, see Files-11
  - RSX-11M, *INT* 6-1
- File Transfer Program, see FLX
- File types, *BEG* 2-2, *MCR* 3-4, *ODT* 4-1
- information on, *IOP* 4-10
  - MCR* standard, *BEG* 2-12, *MCR* 3-6, 3-7
  - specifying, *BEG* 3-1
- File version number, *IOP* 3-38, 4-10, 4-12, 4-14, *MCR* 3-6

RSX-11M V03.2 Master Index

- File windows, *IOP* 2-15, 2-16
  - mapping 2-4, *RLN* 2,6
- FIP, *RMU* 1-33, 8-28
- First-in, first-out, see FIFO
- Fixed-length records, *IOP* 1-5, 1-6, 2-5, 3-8, 3-27, 4-18, *RMU* 1-37
  - format for, *RMC* 3-46
- Fixed record format, *RMU* 2-15
- Flag byte, *RMU* 5-16
- Flag polarity, reporting, *EXE* 6-102, 6-103, 6-123
- Flags,
  - control, *RMU* 5-4
  - event, see Event flags
  - task status, *MCR* 4-21
- Floating-point,
  - data, *MAC* 6-26
  - number, *MAC* 6-28
  - number specification, *MAC* 6-27
  - processor, *INT* 5-5
  - rounding, *MAC* 6-14, 6-27
  - truncation, *MAC* 6-14, 6-27
- FLX (File Transfer Program), *INT* 6-1, *MCR* 3-1, *SSG* 1-2, 2-6
  - cassette with, *UTL* 5-12
    - input files, *UTL* 5-14
    - multivolume, support, *UTL* 5-13
    - output files, *UTL* 5-13
    - TA11/TU60, support, *UTL* 5-12
  - command line, *UTL* 5-2
  - deleting files with, *UTL* 5-6
  - DOS-11 volumes, *UTL* 5-8
    - deleting files on, *UTL* 5-10
    - directory listings of, *UTL* 5-8
    - initializing, *UTL* 5-10
    - valid, *UTL* 5-1
  - error messages, *UTL* 5-16
  - file transfers,
    - command line for, *UTL* 5-2
  - paper tape support, *UTL* 5-15
  - RT-11 volumes, *UTL* 5-10
    - deleting files on, *UTL* 5-11
    - directory listings of, *UTL* 5-10
    - initializing, *UTL* 5-11
    - valid, *UTL* 5-2
  - switches, *UTL* 5-3
    - control, *UTL* 5-6
    - new, *RLN* 34
    - transfer mode, *UTL* 5-4
    - volume format, *UTL* 5-3
  - volumes,
    - deleting files from, *UTL* 5-6
- FLX, volumes (Cont.),
  - directory listings of, *UTL* 5-7
  - formatting, *UTL* 5-3
  - initializing, *UTL* 5-8
  - transferring files between, *UTL* 5-3
- Flush record operation, *RMU* 1-26
- FMT (Disk Volume Formatter),
  - error messages, *UTL* 8-8 to 8-12
  - initiating, *UTL* 8-1
  - operation modes,
    - manual, *UTL* 8-3, 8-4
    - normal, *UTL* 8-2, 8-3
  - supported devices, *UTL* 8-4 to 8-6
  - switches, *UTL* 8-6 to 8-8
  - terminating, *UTL* 8-1
- FOR compiler task, *DEV* 7-1
- Fork block, *WRT* 4-19
- Fork level, *EXE* 6-17
  - processing, *WRT* 2-9, 2-15
- Fork list, *WRT* 2-9
  - and I/O drivers, *WRT* 2-9
- Format,
  - file, *MCR* 3-1
  - file header block, *IOP* 3-4, 5-3, 5-4, F-1
  - file owner word, *IOP* 4-5
  - fixed-length record, *RMC* 3-46
  - for BRU tape devices, *UTL* 10-26
  - index file, *IOP* E
  - line, *MAC* E-1
  - MACRO-11 source file, *DEV* 2-3 to 2-8
  - mapping table, *DRV* 18-71, 81-72
  - overhead record, *RMU* 4-2, 4-4, 4-7, 5-4, 6-1, 6-2, 6-18
  - printout, *ODT* 3-1
  - QIO macro, *DRV* 1-8 to 1-10
  - RT-11, *MCR* 3-1
  - stack, *EXE* 2-5, 2-7, 2-8
  - statement, *MAC* 2-1
    - FORTTRAN IV, *DEV* 7-2
    - MACRO-11, *DEV* 2-3
  - stream record, *RMC* 3-46
  - TKB input data, *TKB* A
  - undefined record, *RMC* 3-46, *RMU* 1-40
  - variable record, *RMU* 2-15
  - vertical, controlling, *DRV* 2-31, 3-25, 10-5
- Formats,
  - block header, RMS-11 pool, *RMC* 2-10
  - card-reader data, *DRV* 11-9
  - CMP output file, *UTL* 16-4
  - data,
    - card reader, *DRV* 11-9
    - for file-structured devices, *IOP* 1-5, 1-6
    - TKB input, *TKB* A-1

Formats (Cont.),  
 error message, *BEG* 1-12  
 pool block header, *RMS-11*, *RMC* 2-10  
*PRESRV*, *UTL* 12-1, 12-9 to 12-11, 12-13,  
 12-14  
*RMS-11* pool block header, *RMC* 2-10  
 record, see Record formats

Formatting,  
 generalized, *SLR* 6-5  
 horizontal, *MAC* 2-6  
 message, routine for, *ERL* 2-3  
 page, *MAC* 2-6  
 output, routines for, *SLR* 6-1 to 6-14  
 standards, *MAC* E-9  
 volumes,  
     with *FLX*, *UTL* 5-3  
     with *FMT*, *UTL* 8

Form feed, *MCR* 2-3, *RMU* 2-16, 2-17

Forms control, *RMU* 1-39

FORTTRAN, *INT* 5-5  
 common blocks, *TKB* 4-19  
 error conditions, *EXE* 1-4  
 interface, *DRV* 14-3, 15-18, 16-8, 18-31,  
 21-2, 22-5  
 subroutines, *EXE* 1-9  
 subroutine summary, *DRV* 14-4, 15-15,  
 16-10, 18-31

FORTTRAN IV, *BEG* 2-1, *INT* 2-2, 5-2, 5-5  
 compiler, *BEG* 2-11  
 compiler task, *DEV* 7-1  
 debugging, *DEV* 7-6, 7-7  
 error messages, *DEV* 7-4  
 formatting of source statements, *DEV* 7-2  
 object modules, output of, *DEV* 7-4, 7-5

OTS, *BEG* 2-15  
 specifying to *TKB*, *DEV* 7-5

source files,  
 adding debugging statements to,  
     *DEV* 7-6  
 creating, *DEV* 7-2

FORTTRAN IV-PLUS, *INT* 2-2, 5-3, 5-5

FSR (File Storage Region), *IOP* 1-3, 1-11,  
 2-18, 2-37 to 2-43  
 initializing, *IOP* 2-37 to 2-40  
 size of, *IOP* 2-40 to 2-42

FTB, see Fast Task Builder

Full duplex,  
 considerations, *DRV* 2-36, 12-11  
 terminal driver, *RLN* 1, 2, 4  
 differences from half duplex driver,  
     *RLN* 28, 29

Function control switches, *MAC* 8-6  
 Function directives, *MAC* 6-13  
 Function keys, *BEG* 1-3, 1-4  
 Function mask values, I/O, *WRT* 4-14  
 Function(s),  
     QIO, see QIO functions  
     summary of I/O, *DRV* A-1  
     system directive, *EXE* 1-1  
     transfer, *WRT* 2-16

## G

General-purpose registers, *MAC* E-2

Generating an RSX-11M system, see System  
 generation, *RSX-11M*

Generating an RSX-11S system, see System  
 generation, *RSX-11S*

Get command line routine, *IOP* 2-2, 6-1  
 to 6-13

Get LUN information system directive,  
     *IOP* 2-18

Get Space Address, see GSA

Global assignment, *MCR* 4-18

Global common block, *DRV* 15-11

Global cross-reference listing, generating,  
     *DEV* 4-4

Global default, disabling in *MACRO-11*,  
     *DEV* 3-1

Global label, *MAC* 6-40,  
     *RMC* 1-10

Global logical name, *MCR* 2-13

Global references, *MAC* 6-15, *RMU* 8-1, 8-20,  
 8-22

Global symbol directory, *MAC* 1-2

Global symbol mode, *MCR* 5-20

Global symbols, *MAC* 2-3, 3-6, 6-40,  
     *RMC* 1-10  
     ambiguously-defined, *TKB* 2-8, 4-7  
     as entry points, *DEV* 6-4  
     multiply-defined, *TKB* 2-8, 4-7  
     resolving, *TKB* 2-7, 4-16  
         by co-trees, *TKB* 4-19  
         summary of, *TKB* 4-17  
     undefined with library, *DEV* 6-6  
     undefined, *TKB* 2-8

Graphics display driver, *DRV* 20

Graphics subsystems, *DRV* 20-1

Group global event flags, *EXE* 2-2, 6-35, 6-53,  
 6-103, *RLN* 2

GSA (Get Space Address), *RMC* 1-7  
 routine, *RMC* 2-8 to 2-12

## H

Half duplex,  
 considerations, *DRV* 12-11  
 terminal driver, *CDA* 3-34, *RLN* 1  
 differences from full duplex driver,  
*RLN* 28, 29  
 Hardware, *RMU* 9-15, 9-72  
 interrupt vectors, *INT* 2-1  
 program development, *DEV* 1-10  
 Hardware registers, *MAC* E-2  
 Header, *TKB* 2-15  
 HELLO command, *BEG* 1-7 to 1-10, *MCR* 2-14,  
 4-41, *RLN* 3  
 HELP command, *BEG* 1-6, 1-8, *MCR* 4-46  
 HELP file, creating, *MCR* 4-46  
 HELP text files, *GEN* H-1, H-2  
 High memory limit register, *ODT* 2-5, 2-8,  
 2-9, 3-12, 3-21, 3-24  
 Hold-screen mode, *MCR* 4-97  
 Home block, *IOP* E-2, E-3  
 Horizontal formatting, *MAC* 2-6  
 Horizontal tab, *MCR* 2-3  
 Host system, *INT* 1-1, *TKB* 7-1

## I

IAS,  
 command string format, *MAC* 8-10  
 indirect command files, *MAC* 8-12  
 ICB (Interrupt Control Block), *WRT* 4-28,  
 4-29  
 ICS/ICR address assignments, *DRV* 18-2  
 ICS/ICR and DSS/DRS assembly language  
 interface, *DRV* 18-8  
 Immediate addressing mode, *MAC* 5-4, 5-7  
 Immediate conditional assembly, *MAC* 6-46  
 Immediate expression indicator, *MAC* 3-2  
 Indefinite repeat block directives,  
*MAC* 7-15  
 Index addressing mode, *MAC* 5-4, 5-7  
 Index deferred addressing mode, *MAC* 5-4, 5-7  
 Indexed file(s), *RMU* 1-18  
 organization, *RMU* 1-18  
 Index file(s), *IOP* 5-2, E-1  
 format, *IOP* E  
 bit map in, *IOP* E-2  
 bootstrap block in, *IOP* E-1  
 home block in, *IOP* E-2  
 predefined file header blocks in,  
*IOP* E-2 to E-4

Indirect command files, *CDA* 1-7, *INT* 4-2,  
*TKB* 4-27  
 IAS, *MAC* 8-12  
 MCR, *INT* 4-2, *MCR* 5-1  
 AT. (indirect file processor),  
*INT* 4-2, *MCR* 5-2, *RLN* 25, 26  
 default file type for, *MCR* 5-1  
 directives, *MCR* 5-2  
 example of, *MCR* 5-38, 5-39  
 initiating, *MCR* 5-1  
 multilevel, *MCR* 5-11  
 switches, *MCR* 5-10  
 symbols, *MCR* 5-5  
 task, *MCR* 5-1, *TKB* 1-5 to 1-7  
 with BAD, *UTL* 9-2  
 with CDA, *CDA* 1-7  
 with SLP, *UTL* 17-8, 17-9  
 with utilities, *UTL* 1-9, 1-10  
 Indirect file, *RMU* 9-6, 9-29  
 Industrial control subsystems drivers,  
*DRV* 18  
 Initial argument or expression indicator,  
*MAC* 3-2  
 Initialization commands, *MCR* 4-6  
 Initialize, *INT* 6-1  
 Initialize dynamic memory routine, *SLR* 7-2  
 Initialize virtual memory routine, *SLR* 8-5 to  
 8-7  
 Initial register indicator, *MAC* 3-2  
 Input,  
 reading digital, *DRV* 16-17  
 solicited, *MCR* 2-7  
 unsolicited, *MCR* 2-7  
 Input data conversion routines, *SLR* 4-1 to 4-9  
 Input file, *MCR* 3-3  
 Input file type default value, *ODT* 4-1  
 Input prompt, *MCR* 2-7, 4-1, 4-2  
 Install-run-remove tasks, *MCR* 4-5  
 Instruction count, *ODT* 3-20  
 Instruction set, *MAC* C-1  
 Instructions, illegal, *ODT* 3-15  
 Integer arguments, *EXE* 1-11  
 Integer arithmetic routines, *SLR* 3-1  
 Integer array, *EXE* 1-11  
 RDB, *EXE* 3-14  
 WDB, *EXE* 3-17  
 Internal registers, *ODT* 3-10  
 Interrupt Control Block, see ICB  
 Interrupted sequence, *ODT* 3-8  
 return to, *ODT* 3-8  
 Interrupts, *ODT* A-2  
 connect to contact, *DRV* 15-19

Interrupts (Cont.),

- connect to counter, *DRV* 18-19, 18-53
- connect to digital, *DRV* 18-18, 18-48
- connect to terminal, *DRV* 18-21, 18-56
- connect to timer, *DRV* 15-19
- disconnect from contact, *DRV* 15-20
- disconnect from digital, *DRV* 18-19, 18-52
- disconnect from terminal, *DRV* 18-22, 18-58
- disconnect from timer, *DRV* 15-20
- error logging, undefined, *ERL* 1-2
- report on unexpected, *ERL* 4-1, 4-2
- software, *EXE* 2-3
- UNIBUS switch, *DRV* 23-1
- unlink a task from, *DRV* 18-26, 18-63

Interrupt vectors, hardware, *INT* 2-1

Intervals, time, *EXE* 6-88

Interpreter, *INT* 5-4

I/O, *INT* 6-4

- block, see Block I/O
- data structures for, *WRT* 2-5
  - DCB, *WRT* 2-5
  - device interrupt vector, *WRT* 2-9
  - fork list, *WRT* 2-9
  - interrelationships, *WRT* 2-17
  - I/O packet, *WRT* 2-8
  - I/O queue, *WRT* 2-8
  - SCB, *WRT* 2-6
  - UCB, *WRT* 2-6
- logical, *DRV* 1-2
- philosophy of, *WRT* 2-1
- physical, *DRV* 1-2
- process control, *DRV* 14-3, 15-4, 18-32
- programming standards for, *WRT* 2-12 to 2-15
- RSX-11M, *DRV* 1-1
- structure of, *WRT* 2-1 to 2-5
- virtual, *DRV* 1-2

I/O active bit map, *ERL* 2-1

I/O buffer, *RMC* 1-6, *RMU* 1-29

I/O completion, *DRV* 1-28

I/O drivers, see Drivers

I/O exerciser, see IOX

I/O function codes, *DRV* B-3

I/O function mask values, *WRT* 4-14

I/O functions,

standard, *DRV* 1-24, B-4

summary of, *DRV* A-1

I/O hierarchy, *WRT* 2-1

I/O initiator entry point, *WRT* 2-4, 2-11, 3-2, 4-10

I/O operations, *INT* 6-7, *RMU* 1-34, 2-3, 3-5  
block, *IOP* 1-6

I/O operations (Cont.),

- coordinating, *IOP* 2-42
  - AST service routine, *IOP* 2-45
  - event flags, *IOP* 2-42
  - I/O status block, *IOP* 2-44, 2-45
- physical, *INT* 6-6, 6-7
- record, *IOP* 1-5, 1-6, 2-8 to 2-10
- task, *INT* 6-4 to 6-6

I/O packet,

and I/O drivers, *WRT* 2-8, 2-16, 4-2, 4-18

I/O page,

- accessing, *DRV* 18-71
- global definitions, *DRV* 18-72
- overlapping, *TKB* 3-63

I/O philosophy, *WRT* 2-1

I/O processing, optimizing, *MCR* 4-112

I/O queue,

and I/O drivers, *WRT* 2-8, 4-16

I/O request packets, *CDA* 3-36, B-40, C-35

I/O requests,

- ACP routing of, *RLN* 43
- cancelling, *DRV* 1-25
- flow of, *WRT* 2-15 to 2-17
- issuing, *DRV* 1-6
- overhead of, *RMU* 8-31
- queuing, *EXE* 6-90, 6-93
- redirecting, *MCR* 4-169

I/O rundown, *DRV* 18-30, *MCR* 4-10

IOSB, see I/O status block

I/O status block, *DRV* 1-19, 16-31, 21-25, 22-25, *IOP* 2-12, 2-44, 2-45, 3-32, 3-33, *WRT* 2-10, 2-16, 2-17, 4-4, 4-7

I/O status codes, *DRV* B-1

I/O status condition, *DRV* 1-31, 11-6

I/O status return codes, *DRV* 1-31

I/O structure, *WRT* 2-1 to 2-5

I/O techniques, *RMU* 2-17

I/O unit (bucket), *RMU* 1-29

IOX (I/O exerciser), *GEN* E-1 to E-47, *RLN* 7

**K**

Kernel data space, *CDA* 3-48

Kernel mode, *ODT* A-1

Kernel instruction space, *CDA* 3-50

Kernel stack, *CDA* 1-7, 3-5, 4-1, 4-2

Key,

- characteristics, *RMC* 5-39, *RMU* 6-7
- field, *RMU* 1-22, 5-1
- index, *RMU* 1-19, 6-2
- number, *RMU* 1-19, 1-22, 1-38, 2-3, 6-2

Key (Cont.),  
 position, *RMU* 6-6  
 selection, *RMU* 6-2  
 size, *RMC* 5-60, *RMU* 6-3  
 string, *RMU* 6-4  
 type, *RMC* 5-28  
 value, *RMU* 1-22, 1-38, 5-13  
 Keyboard,  
 for terminals, *BEG* 1-3  
 sequences, elements of, *ODT* 1-4  
 Key of reference, *RMU* 5-13, 9-20  
 Keys,  
 function, *BEG* 1-3, 1-4  
 segmented, *RMC* 5-52, 5-56  
 Keyword, *MCR* 4-3  
 Keyword arguments, *MAC* 7-4, 7-9  
 KMC11 line printer driver, *RLN* 7, 32  
 KRB (Controller Request Block), *CDA* 3-46,  
 C-23  
 K-Series call, *RLN* 36  
 K-Series laboratory peripherals, *DRV* 22-1  
 K-Series laboratory support routines,  
 building, *SSG* 4-8  
 K-Series peripheral support routines drivers,  
*DRV* 22  
 KT11 memory management unit, *EXE* 3-1,  
*INT* 3-1, 3-2, *TKB* 2-10

## L

Label(s), *RMU* F-2  
 branching to a, *MCR* 5-25, 5-30  
 command file, *MCR* 5-12  
 global, *MAC* 6-40, *RMC* 1-10  
 multi-defined, *MAC* 2-4  
 multiple, *MAC* 2-4  
 Label field, *MAC* 2-2  
 Label terminator, *MAC* 3-1  
 Laboratory peripheral accelerator,  
 driver, *DRV* 21-1  
 LPA11-K, *RLN* 28  
 Laboratory peripheral systems drivers,  
*DRV* 16-1  
 Language translator, *BEG* 2-1  
 Languages,  
 assembler, *BEG* 2-1, *DEV* 1-2  
 compiler, *BEG* 2-1  
 computer, *DEV* 2-2  
 programming, *INT* 5-3  
 supported, *INT* 2-2, 2-3  
 LBN (Logical Block Number), *IOP* 1-5, 5-1,  
*MCR* 4-146, 4-173, *RMC* 3-48, 5-7,  
*RMU* 1-15, 6-23, 9-42

LBR (Librarian Utility Program), *DEV* 1-7,  
 6-1, 6-2, 6-4, 6-5, 6-7, 6-8  
 changes in, *RLN* 27  
 combining library functions, *UTL* 14-31  
 command line, *UTL* 14-2  
 error messages, *UTL* 14-33  
 examples of, *UTL* B-1  
 file specifiers, defaults for, *UTL* 14-2  
 format of library files, *UTL* 14-4  
 library restrictions, *UTL* 14-32  
 switches, *UTL* 14-3, 14-4, 14-10 to 14-13  
 Least significant bits, *RMC* 7-1  
 Least significant byte, *RMU* 6-4, 6-5  
 LED lights, displaying in, *DRV* 16-18  
 Left parenthesis ( ), *MAC* 3-2  
 Legal function mask, *WRT* 4-11  
 Level 0, *RMU* 5-5  
 Level 1, *RMU* 5-4  
 Level 2, *RMU* 5-5  
 Level count, listing, *MAC* 6-2  
 Levels 1+, *RMU* 6-17  
 Levels 2+, *RMU* 6-10, 6-11  
 Librarian utility, *RMU* 8-14  
 Librarian Utility Program, see LBR  
 Libraries,  
 DIGITAL-supplied, *DEV* 1-7 to 1-9  
 object,  
 designating in TKB, *DEV* 6-5, 6-6, 7-5  
 system, *DEV* 1-9  
 using, to resolve undefined symbols,  
*DEV* 6-6, 6-7  
 shareable, *DEV* 7-1, 7-2  
 squeezing, *DEV* 6-2  
 system, *SSG* 8-1  
 default search of,  
 by MACRO-11, *DEV* 1-3, 1-8, 2-6, 2-7  
 by TKB, *DEV* 1-10, 4-1, 4-2  
 macro, *SSG* 8-2  
 user,  
 maintaining, *DEV* 6-7, 6-8  
 obtaining information about, *DEV* 6-8  
 Library,  
 executive macro, see Executive macro  
 library  
 macro, see Macro  
 object module, see Object module library  
 OTS, *DEV* 7-1  
 resident, see Resident library  
 system macro, see System macro library  
 system object module, see System object  
 module library



Library (Cont.),

- system, routines, see System library routines
- user macro, see User macro library
- user object, see User object library
- Line feed, *ODT* 3-2, *RMU* 1-39, 2-16, 2-17
- Line format, *MAC* E-1
- Line printer driver, *BEG* 4-11, *RLN* 1
  - diagnostics, *UMD* 12-1
  - driver, *DRV* 10-5, 10-6
    - KMC11*, *RLN* 7, 32
  - spooling, *RLN* 1
- Lines, *MCR* 2-5
  - blank, *MAC* 2-2
  - truncating (terminal), *DRV* 3-29
- Line terminator options, *MCR* 4-166
- Line Text Editor, see EDI
- Linking, *BEG* 2-1, 2-14, *INT* 5-1, *MAC* 4-1, 6-39
  - tasks, *DRV* 15-13, 18-23 to 18-25, 18-60, 18-70
- Links, physical, *INT* 2-3
- Listing commands, *ODT* 3-29
- Listing control, *DEV* 1-3, 2-6
  - directives, *MAC* 6-1
  - symbolic arguments of, *MAC* 6-3, 6-4
- Listing files, *BEG* 2-13
  - CDA output, *CDA* 1-7, 4-1 to 4-3
  - creating, *BEG* 2-12
  - in queue, *BEG* 4-12
  - sending messages to, *MAC* 7-14
  - with *FLX*, *UTL* 5-8
  - with *PIP*, *UTL* 4-33, 4-34
- Listing output,
  - spooling, *MAC* 8-7
- Listings,
  - assembly, *DEV* 2-6, 3-4 to 3-7, *MAC* 2-6
  - cross-reference, *DEV* 3-6, 4-4, *MAC* 8-9, I-1
    - MACRO-11*, *DEV* 1-3
  - examining, at a terminal, *DEV* 3-5, 4-5
  - generating,
    - assembly, *DEV* 3-4
    - cross-reference, *DEV* 3-6
    - FORTTRAN IV*, *DEV* 7-3, 7-4
    - global cross-reference, *DEV* 4-4
  - spooling, *DEV* 3-6, 3-7
  - use of, in debugging, *DEV* 5-3, 5-4
- Loader,
  - absolute, *SSG* 2-15
  - OTL*, *SSG* 2-5
- Loading, *BEG* 2-14
  - asynchronous, *TKB* 5-8

Loading (Cont.),

- downline, *SSG* 1-2
- manual, *TKB* 5-1
- system, *SSG* 8-3
- task, *SSG* 8-3
- Local assignment, *MCR* 4-18
- Local event flags, *EXE* 2-2
- Local symbol block, *MAC* 6-14
  - delimiters, *MAC* 3-10
- Local symbols, *MAC* 3-6, 3-10, 3-11
  - creating automatically, *MAC* 7-7
  - defining, *DEV* 2-7
  - multiple definitions of, *MAC* 3-11
- Locate mode, *IOP* 1-7
- Location counter, *DEV* 1-3, *MAC* 6-36
  - changing value of, *MAC* 3-12
  - control directives, *MAC* 6-29
  - current, *MAC* 2-2, 3-11, 3-14
  - use in debugging, *DEV* 5-3, 5-4
- Location, current, *ODT* 2-1
  - indicator, *ODT* 3-37
  - operator, *ODT* 2-2
- Locations,
  - in a task image file,
    - changing contents of, with *ZAP*, *UTL* 19-11
    - closing, with *ZAP*, *UTL* 19-11 to 19-13
    - displaying contents of, with *ZAP*, *UTL* 19-3, 19-4, 19-15
    - opening, with *ZAP*, *UTL* 19-10
    - verifying contents of, with *ZAP*, *UTL* 19-15
  - open, see Open locations
- Logging off a terminal, *MCR* 2-13, 2-15, 4-27
- Logging on a terminal, *BEG* 1-10, *MCR* 2-13, 2-15, 4-41
- Logical address space, *EXE* 3-2, 3-4
  - extended, *INT* 3-10
- Logical AND operator, *MAC* 3-2, 6-42
- Logical assignments, *MCR* 4-18
  - control blocks for, *CDA* B-25, C-25
- Logical Block Number, see LBN
- Logical blocks, see Blocks
- Logical channel, *RMC* 3-35
- Logical device(s), see Devices
- Logical end-of-file, *RMU* 9-24
- Logical inclusive OR operator, *MAC* 3-2, 6-42
- Logical I/O, *DRV* 1-2
- Logical names, *MCR* 2-12, *RMC* 3-21
  - global, *MCR* 2-13
  - local, *MCR* 2-12
  - login, *MCR* 2-13

Logical records, *INT* 6-4, *IOP* 1-1, 1-5,  
3-18 to 3-30  
 Logical symbols, *MCR* 5-5, 5-6  
 Logical Unit Number, see LUN  
 Logical units, *DRV* 1-5 to 1-7  
 Logical Unit Table, see LUT  
 Login assignment, *MCR* 4-18  
 Logons, *MCR* 4-112  
 Logon UIC, *MCR* 3-5  
 Low memory limit register, *ODT* 2-5, 2-8, 2-9,  
3-12, 3-21, 3-24  
 LPA11-K laboratory peripheral accelerator,  
*RLN* 28  
 LPP (Despool Prototype Task),  
as component of Queue Manager, *UTL* 7-1  
 LUN (Logical Unit Number), *DRV* 1-5,  
*EXE* 6-5, 6-11, *INT* 6-6, *IOP* 2-13, 3-4,  
3-5, 3-9, *MCR* 2-11, *ODT* 3-29  
 assigning physical devices to, *TKB* 6-51  
 information register, *ODT* 2-9, 3-13, 3-29  
 reassign directive, *RLN* 27  
 reassigning, *DRV* 1-6, *MCR* 4-168  
 terminal device, *ODT* 3-13  
 TKB default, *DEV* 4-3, 4-4  
 LUT (Logical Unit Table), *DRV* 1-6,  
*WRT* 2-18, 4-4

## M

### Macro,

arguments, *MAC* 7-4  
 special characters in, *MAC* 7-6  
 attribute directives, *MAC* 7-11  
 calls, see Macro calls  
 definition, *MAC* 7-1, 7-15  
 arguments, *MAC* 7-4  
 formatting, *MAC* 7-3  
 termination, *MAC* 7-2  
 definitions and expansions, *MAC* E-2  
 directives, *MAC* 7-1  
 expansions, *EXE* 1-8  
 expansion termination, *MAC* 7-3  
 library, *MAC* 8-6  
 adding modules to a, *DEV* 6-7  
 creating a user, *DEV* 6-1, 6-2  
 default search of system, *DEV* 1-3, 1-8,  
2-6, 2-7  
 DIGITAL-supplied, *DEV* 1-8  
 listing information on a, *DEV* 6-8  
 replacing modules in a, *DEV* 6-7, 6-8  
 using definitions from a, *DEV* 6-3

### Macro (Cont.),

library directive, *MAC* 7-18  
 name, *MAC* 7-1, 7-4  
 conventions, *EXE* 1-5 to 1-7  
 nesting, *MAC* 7-5  
 qualifiers, *MAC* 8-10  
 QIO, format, *DRV* 1-8 to 1-10  
 symbol table, *MAC* 3-5  
 MACRO-11, *INT* 2-2, 5-3, *RMU* 2-2, B-1  
 addressing,  
 branch instruction, *MAC* 5-8  
 addressing modes,  
 absolute, *MAC* 5-5, 5-7  
 autodecrement, *MAC* 5-3, 5-7  
 autodecrement deferred, *MAC* 5-3, 5-7  
 autoincrement, *MAC* 5-2, 5-7  
 autoincrement deferred, *MAC* 5-3, 5-7  
 immediate, *MAC* 5-4, 5-7  
 index, *MAC* 5-4, 5-7  
 index deferred, *MAC* 5-4, 5-7  
 register, *MAC* 5-1, 5-7  
 register deferred, *MAC* 5-2, 5-7  
 relative, *MAC* 5-5, 5-7  
 relative deferred, *MAC* 5-6, 5-7  
 summary of, *MAC* 5-7  
 assembler, *INT* 2-2, 5-3  
 assembly and cross-reference listing,  
 sample of, *MAC* I-1  
 assembly language, *MAC* B-1  
 changes to, *RLN* 38, 39  
 character sets, *MAC* 3-1 to 3-5, A-1  
 coding standard,  
 sample of, *MAC* E  
 command line format, *MAC* 8-3 to 8-5  
 cross-reference listing, *DEV* 1-3, 3-6  
 current location symbol in, *DEV* 1-3,  
*MAC* 3-11 to 3-13  
 data storage definition, *DEV* 2-3, 2-9  
 debugging, *DEV* 7-6, 7-7  
 default search of system library, *DEV* 1-3,  
1-8, 2-6, 2-7  
 direct assignment statements for, *MAC* 3-7,  
3-8  
 directives, *MAC* 2-5, 5-9, C-4  
 conditional assembly, *MAC* 6-41 to 6-46  
 data storage, *MAC* 6-17 to 6-24  
 function, *MAC* 6-13 to 6-16  
 listing control, *MAC* 6-1 to 6-13  
 location counter control, *MAC* 6-29  
 macro, *MAC* 7  
 attribute, *MAC* 7-11 to 7-14  
 calling macros with, *MAC* 7-3, 7-4  
 arguments in, *MAC* 7-4 to 7-11

- MACRO-11 (Cont.),
- defining macros with, *MAC* 7-1 to 7-3
  - arguments in, *MAC* 7-4 to 7-11
  - indefinite repeat block, *MAC* 7-15 to 7-17
  - macro library, *MAC* 7-18, 7-19
  - repeat block, *MAC* 7-17, 7-18
  - .ERROR, *MAC* 7-14, 7-15
  - .PRINT, *MAC* 7-14, 7-15
  - program boundaries, *MAC* 6-31, 6-32
  - program sectioning, *MAC* 6-32 to 6-39
  - summary of, *MAC* B
  - symbol control, *MAC* 6-39, 6-40
  - symbol evaluation, *DEV* 1-2, 3-1
  - terminating, *MAC* 6-31
  - types of, *DEV* 1-3
- error codes, *MAC* D-1
- error messages, *DEV* 3-1, 3-2, *MAC* 8-14
- summary of diagnostic, *MAC* D
- expressions, *MAC* 3-15, 3-16
- file specification format, *MAC* 8-13, 8-14
- file specification switches, *MAC* 8-5 to 8-8
- generating,
- listings, *DEV* 3-4
  - object modules, *DEV* 3-4
  - table of contents, *DEV* 2-6
- global defaults, disabling in, *DEV* 3-1
- initiating,
- under IAS, *MAC* 8-10
  - under RSX-11, *MAC* 8-1
- location counter, *DEV* 1-3, *MAC* 3-11 to 3-13
- macro cross-reference, *DEV* 3-6
- macro library usage in, *DEV* 6-3
- name conventions for system directives, *EXE* 1-5 to 1-7
- numbers, *MAC* 3-13, 3-14
- object modules, output of, *DEV* 1-2
- operating procedures, *MAC* 8
- overview of, *MAC* 1-1, 1-2
- Permanent Symbol Table (PST), *MAC* C
- position-independent code, *MAC* H-1
- writing, *MAC* G
- radix and numeric control facilities, *MAC* 6-24 to 6-29
- relocation and linking, *MAC* 4-1
- RMS-11,
- features available to, *RMU* B-1
  - summary information of, *RMC* 1-13
- source files,
- assembling, *DEV* 3-1, 3-2
- MACRO-11 (Cont.),
- creating, *DEV* 2-11
  - editing, *DEV* 2-11 to 2-17
  - format of, *DEV* 2-2 to 2-8
  - library call in, *DEV* 6-3, 6-5
  - preface, *DEV* 2-1
  - skeleton, *DEV* 2-1 to 2-8
  - typical errors in, *DEV* 3-6, 3-7
- source input to, *DEV* 1-2
- source programs,
- format for,
    - control of, *MAC* 2-6
    - statement, *MAC* 2-1 to 2-5  - programming standards and conventions for, *MAC* 2-1
- statement format, *DEV* 2-3
- symbols, *MAC* 3-5
- evaluating, *DEV* 1-2
  - local, *MAC* 3-10, 3-11
    - defining, *DEV* 2-7  - macro, *DEV* 1-3, 2-6, 2-7
  - register, *MAC* 3-9, 3-10
- terms, *MAC* 3-14, 3-15
- trap instructions, *MAC* 5-8
- virtual memory,
- allocating, *MAC* F
- Macro calls, *EXE* 1-5, *MAC* 2-5, 7-3, 7-5
- arguments, *MAC* 7-4
    - number of, in, *MAC* 7-7, 7-11  - cross-reference of symbols for, *DEV* 3-6
  - default resolution of, *DEV* 1-3, 1-8, 2-6, 2-7
- file-processing,
- CLOSE\$, *IOP* 3-18
  - DELET\$, *IOP* 3-38
  - GET\$, *IOP* 3-18 to 3-22
  - GET\$R, *IOP* 3-22, 3-23
  - GET\$\$, *IOP* 3-23, 3-24
  - OFID\$x, *IOP* 3-14
  - OFNB\$x, *IOP* 3-14 to 3-16
  - OPEN\$, *IOP* 3-16, 3-17
  - OPEN\$x, *IOP* 3-2 to 3-11
  - OPNT\$D, *IOP* 3-13
  - OPNS\$x, *IOP* 3-12
  - OPNT\$W, *IOP* 3-12, 3-13
  - PUT\$, *IOP* 3-24 to 3-28
  - PUT\$R, *IOP* 3-28 to 3-30
  - PUT\$\$, *IOP* 3-30
  - READ\$, *IOP* 3-30 to 3-34
  - WAIT\$, *IOP* 3-35 to 3-38
  - WRITE\$, *IOP* 3-34, 3-35
- numeric argument indicator, *MAC* 3-2
- run-time, *IOP* 1-10, 1-11

- Macro calls (Cont.),  
 subset FCS, *SSG* 2-21  
 treatment of unrecognized, *DEV* 2-7  
 user-library resolution of, *DEV* 6-3
- Macros,  
 arguments for, *MAC* 7-10, 7-15  
 calling, *MAC* 7-3  
 defining, *MAC* 7-1  
 directive,  
   executive, *DRV* 1-1, 1-8, 1-15, 1-16, 1-20,  
     1-22, 1-23  
   using, *EXE* 1-4, 1-5  
 externally-defined, *MAC* 7-18  
 file operation, *RMC* 1-21  
 I/O-related, *DRV* 1-13  
 nested, *MAC* 7-3, 7-5  
 operation, *RMC* 1-21, 1-22  
 record operation, *RMC* 1-22  
 system, retrieving, *DRV* 1-15
- MAC task, *DEV* 1-2
- Magnetic Tape Ancillary Control Processor,  
 see MTAACP
- Magnetic tapes, *DRV* 8-1, 8-2  
 accessing, *IOP* 5-4  
 ANSI, *MCR* 3-1, *RMC* 3-24  
 ANSI-D format, *RMU* F-1  
 ANSI labels for, *RMU* 9-2, 9-18  
 ANSI standard, *MCR* 3-1  
   data formats for, *IOP* 1-5, G-1  
   mounting, *MCR* 4-65  
   support of, *IOP* G  
 block size of, *RMC* 3-9, 3-10, *RMU* 9-23  
 data storage for, secondary, *RMU* 1-11  
 driver for, *DRV* 8  
 end-of-file indicators for, *RMU* 3-2  
 file processing for, *RMU* F-3  
 function codes for, *RLN* 6, 7  
 labels for, *RMU* F-2  
 multivolume,  
   files on, *RMC* 8-25  
 powerfail procedure for, *RLN* 7  
 processing, *IOP* 5-4  
   general, *RMU* F-1  
 retry procedures for, *DRV* 8-12
- Magnitude values, *EXE* 6-86, 6-112, *MCR* 4-81
- Maintenance, system features of, *INT* 4-4,  
 4-5
- Map, see Memory allocation file
- Map Address Window, *EXE* 6-83
- Mapped array area, *TKB* 3-54
- Mapped systems, *INT* 3-1, 3-2, *MCR* 1-1,  
*ODT* 1-4
- Mapped systems (Cont.),  
 task relocation on, *TKB* 2-16  
 TKB addressing on, *TKB* 2-10 to 2-14
- Mapping,  
 address, *EXE* 3-1, 3-6, 3-7  
 error code, *RMU* B-4  
 privileged task, *EXE* 3-18  
 virtual-to-logical block, *RMU* 3-6, 4-6, 8-1,  
 8-26
- Mapping table format, *DRV* 18-71, 18-72
- Mark Time, *EXE* 6-86
- Masks,  
 control function, *WRT* 4-12  
 I/O function, *WRT* 4-11  
   establishing, *WRT* 4-14  
 protection, *MCR* 3-2  
 search, *ODT* 2-8, 3-21, 3-22, 3-23
- Mass data storage, *RMU* 1-1
- Mass Insert, *RMC* 4-26, *RMU* 6-33
- Master File Directory, see MFD
- Match criteria, *RMC* 4-13, *RMU* 1-21, 1-22,  
 5-13
- Maximum Record Number, see MRN
- Maximum Record Size, *RMU* 4-2, 6-2
- MBC (Multi-Block Count), *RMU* 2-19, 3-15
- MBF (Multiple Buffers), *RMU* 2-19
- .MCALL directives, *RMC* 1-2, 1-3, 1-4
- MCR, *BEG* 1-5, 1-6, *INT* 1-4, 4-1
- Basic,  
   messages, *MCR* B-1  
   syntax, *MCR* B-1
- changes in, *RLN* 23-27
- command file syntax, *MCR* 5-11
- command line, *MCR* 3-3 to 3-8
- commands, *BEG* 1-6 to 1-12  
   description of format and syntax,  
     *MCR* 4-8, 4-9
- format for, *MCR* 4-1, 4-2
- issuing, *MCR* 4-1, 4-2
- line terminators for, *MCR* 4-2
- nonprivileged, *MCR* 4-10 to 4-134
- parameters for, *MCR* 4-1
- privileged, *INT* 4-1, *MCR* 4-134 to 4-186
- RSX-11S, *MCR* B-1
- summary of, *MCR* 4-6  
   informational, *MCR* 4-6, 4-7  
   initialization, *MCR* 4-6  
   multiuser protection, *MCR* 4-8  
   system maintenance, *MCR* 4-7, 4-8  
   task control, *MCR* 4-7
- syntax of, *MCR* 4-4
- enhancements, *RLN* 2, 3

- MCR (Cont.),
  - file specifiers,
    - defaults for, *MCR* 3-3, 3-6
    - file types (standard), *BEG* 2-12, *MCR* 3-6, 3-7
    - format for, *MCR* 3-4
    - UICs, *MCR* 3-5
    - wildcard (asterisk) convention in, *MCR* 3-8
  - indirect command files, see Indirect command files
  - indirect file processor, *INT* 4-2, *MCR* 5-2, *RLN* 25, 26
  - messages, *BEG* 1-12, *MCR* A-1
  - new switches, *RLN* 35
  - options,
    - backspace, *MCR* 2-2
    - delete, *MCR* 2-21
    - examine, *MCR* 2-19
    - list, *MCR* 2-21
    - modify, *MCR* 2-20
    - switch, *MCR* 3-4
  - prompt, *MCR* 2-3, 2-7, 2-8
  - RUN command, *INT* 5-6
  - source files, updating, *RLN* 12-15
  - task scheduling, *INT* 4-2
- MCR interface, *INT* 1-2, *MCR* 4-2
  - command references to active tasks,
    - install-run-remove tasks, *MCR* 4-5
    - task-naming convention, *MCR* 4-3, 4-4
  - comments, *MCR* 4-3
  - keywords, *MCR* 4-3
- Medium, *RMU* 1-17
- Memory, *INT* 3-1, *MCR* 4-165, *RMU* 1-33
  - dynamic, allocating, *MAC* F-1
  - organization of, *INT* 3-1
    - mapped systems, *INT* 3-1, 3-2
    - partition types, *INT* 3-2
    - subpartitions, *INT* 3-2
    - unmapped systems, *INT* 3-1, 3-2
- Memory allocation, *MAC* 6-32, 6-33, 6-38
  - file (map), *DEV* 4-4, 4-5, 5-2, 5-8, *ODT* 4-1, *RMU* 8-14, C-1
    - contents of, *TKB* 6-29
    - description of, *TKB* 6-32 to 6-35
    - general, *TKB* 1-1
    - routine, *ERL* 2-3
- Memory dumps, *RLN* 36, *TKB* 8-1 to 8-11
- Memory image, *TKB* 2-16
- Memory layout, *INT* 3-7
- Memory limit, high and low, *ODT* 2-8, 2-9, 3-12, 3-21, 3-24
- Memory management,
  - directives, *EXE* 3-1, 6-3, 6-4, *INT* 3-1, 3-10
  - dynamic, routines, *SLR* 7-1 to 7-4
  - option modes, *ODT* A-1
  - virtual, routines, *SLR* 8-1 to 8-20
- Memory management unit (KT11), *EXE* 3-1, *INT* 3-1, 3-2, *TKB* 2-10
- Memory map, *ODT* 1-4
- Memory parity errors, *ERL* 1-2
  - reports on, *ERL* 4-5, 4-6
- Memory partitions, *INT* 3-1
- Memory protect violation, *ODT* 3-15
- Merging files, see Files
- Message formatting routine, *ERL* 2-3
- Message queuing routine, *ERL* 2-3
- Message-oriented communication driver, *DRV* 12-1
- Messages, see Error Messages
- MFD (Master File Directory), *INT* 6-2, *IOP* 5-2, *MCR* 3-2
- Microfiche, *RLN* 3
- Minus sign, *MAC* 3-2
- Mode,
  - ASCII,
    - byte, *ODT* 3-31
    - word, *ODT* 3-31
  - ASCII character,
    - print byte, *ODT* 3-34
    - print word, *ODT* 3-35
  - block, *DEV* 1-1
  - byte, *ODT* 3-2, 3-4
  - data, *MCR* 5-21
  - DMP device, *UTL* 15-1
  - DMP file, *UTL* 15-1
  - DSC merge, *UTL* 11-19
  - EDT character, *UTL* 2-1, 2-21, 2-48, 2-59
  - EDT command, *UTL* 2-1 to 2-3, 2-20, 2-60
  - escape recognition, *MCR* 5-20
  - global symbol, *MCR* 5-20
  - hold-screen, *MCR* 4-97
  - kernel, *ODT* A-1
  - locate, *IOP* 1-7
  - lower-case, *MCR* 5-20
  - move, *IOP* 1-7
  - octal,
    - byte, *ODT* 3-31
    - word, *ODT* 3-31
  - query, *RMU* 9-11, 9-67
  - Radix-50,
    - word, *ODT* 3-31
  - Radix-50 characters,
    - print word, *ODT* 3-36
    - word, *ODT* 3-31

- Mode (Cont.),
    - random access, see Random access mode
    - Record Transfer, *RMC* 4-20
    - sequential access, see Sequential access mode
    - single-instruction, commands for, *ODT* 3-19
    - substitution, *MCR* 5-20
    - teleprinter, *MAC* 6-4
    - user, *ODT* A-1
    - word, *ODT* 3-2
  - Modes,
    - access, *RMU* 1-19
    - addressing, see Addressing
    - data transfer, *IOP* 1-6
    - DMP, *UTL* 15-1
    - EDI, *BEG* 2-3, 2-4, *UTL* 3-3, 3-4
    - EDT, *UTL* 2-1 to 2-3, 2-20, 2-21, 2-48, 2-59, 2-60
    - FMT operation, *UTL* 8-2 to 8-4
    - for reading logical records, *IOP* 3-18 to 3-24
    - for writing logical records, *IOP* 3-24 to 3-30
    - MACRO-11 addressing, *MAC* 5
    - memory management option, *ODT* A-1
    - output listing, *ODT* 3-31
    - ZAP addressing, *UTL* 19-3
  - Modularity, *MAC* E-8
  - Module checking routines, *MAC* E-9
  - Module name, *DEV* 2-3, 5-2, 5-3, 6-5
  - Module preface, *MAC* E-5
  - Module(s),
    - absolute, *MAC* 6-34
    - control of input to TKB, *TKB* 6-7
    - object, see Object modules
    - program, *MAC* E-5
    - relocatable, *MAC* 6-34
    - root, *RMC* 1-5
    - supported I/O, *DRV* 1-17
  - Module table, *DEV* 6-2, 6-4
  - Module version, *DEV* 2-5
  - Monitor, *RMU* 1-12
  - Monitor console interface, *MCR* 4-2
  - Monitor Console Routine, see *MCR*
  - Most significant byte, *RMU* 6-4 to 6-6
  - MOUNT command, *MCR* 2-16, 3-1, 4-65
  - Mounting volumes, *MCR* 4-65
  - Mounts, multiple, *RLN* 2
  - MRN (Maximum Record Number), *RMU* 1-38
  - MTAACP (Magnetic Tape Ancillary Control Processor), *RLN* 30, 31
  - Multibuffer, *RMC* 4-17
  - Multiblock count, *RMC* 4-15
  - Multi-Block Count, see *MBC*
  - Multicontroller I/O drivers, *WRT* 2-13, 4-27
  - Multiple Buffers, see *MBF*
  - Multiplexer, *DRV* 2-39, 3-30
  - Multiprogramming, *INT* 1-1, 2-1, 3-3, *MCR* 1-2 applications, *MCR* 3
  - Multiuser protection system, *BEG* 1-8, 3-4, *INT* 4-3, 4-4, 6-1, *MCR* 2-13
    - commands, *MCR* 4-8
    - default UIC in, *MCR* 3-5
    - functions of, *MCR* 2-13
  - Multiuser system, task priority in, *TKB* 6-65
- N**
- Naming standards, *MAC* E-2
  - Negative numbers, *MAC* 3-14
  - Nested conditional directives, *MAC* 6-43
  - Network channels, mounting, *MCR* 4-71
  - Networks, *INT* 2-3
  - Nodes, *INT* 2-3
  - Non-MASSBUS NPR device drivers, *WRT* B-1
  - Nonmultiuser protection systems, *BEG* 1-8, *INT* 4-3
  - No-op function, *WRT* 2-16
    - mask, *WRT* 4-12
  - NPR device drivers, *WRT* 4-25, B-1
  - Null byte, *RMU* 2-5, 3-2
  - Null devices, *MCR* 2-12
    - driver for, *DRV* 19-1
  - Numbers, *MAC* 3-13
  - Number sign, *MAC* 3-2, 5-4
  - Numeric constants, *MCR* 5-9
  - Numeric control, *MAC* 6-24
    - operators, *MAC* 6-26, 6-27
  - Numeric directives, *MAC* 6-26
  - Numeric expressions, *MCR* 5-9
  - Numeric symbols, *MCR* 5-5, 5-9, 5-19, 5-29, 5-33, 5-34, 5-36
  - Numeric value, *RMC* 1-10
- O**
- Object code, *RMU* 1-28, 8-1
  - Object module library, *EXE* 1-10, *RMU* 8-1, *TKB* 6-19
    - adding modules to, *DEV* 6-7
    - creating a user, *DEV* 6-4, 6-5
    - default search of system, *DEV* 1-10, 4-1, 4-2
    - DIGITAL-supplied, *DEV* 1-9, 1-10

- Object module library (Cont.),
  - listing information on an, *DEV* 6-8
  - OTS with an, *DEV* 7-1
  - replacing modules in an, *DEV* 6-7, 6-8
  - system, *DRV* 15-11, *TKB* 2-7
    - SYSLIB.OLB*, *DEV* 1-9, 1-10
  - using, to resolve undefined global symbols, *DEV* 6-6
- Object module name, *MAC* 6-11
  - default, *MAC* 6-11
- Object Module Patch Utility, see *PAT*
- Object modules, *BEG* 2-1, 2-11, 2-14, *INT* 3-2, 5-1, *MAC* 4-1
  - concatenated, creating, with *PIP*, *DEV* 4-2, 4-3
  - contents of, *TKB* A-1
  - creating, *BEG* 2-2
  - executive, *SSG* 4-6
  - input to *TKB*, *DEV* 4-1, 4-2
  - input to user object library, *DEV* 6-4
  - linking with *TKB*, *TKB* 2-1 to 2-8
  - output of FORTRAN IV, *DEV* 7-4, 7-5
  - output of MACRO-11, *DEV* 1-2
  - overriding definitions in, *TKB* 6-57
  - patching, *RLN* 18-20
  - updating, with *PAT*, *UTL* 18-3 to 18-7
- Object Time System, see *OTS*
- Octal,
  - byte mode, *ODT* 3-31
  - word mode, *ODT* 3-31
- Octal byte value,
  - print, *ODT* 3-34
- Octal operators, *ODT* 2-6
- Octal radix, *MAC* 3-13, *RMC* 1-18, 7-1
- Octal register, *ODT* 3-20
- Odd address, *ODT* 3-14, 3-35
- Odd-numbered address, *ODT* 3-3
- ODL (Overlay Descriptor Language), *RMU* 8-4, 8-6, *TKB* 4-22
  - indirect command files with, *TKB* 4-27
  - standard files, *RMU* 8-7
  - summary of, *TKB* 4-42
- ODS (On-Disk Structure), *RMU* 1-14, 3-3
- ODS-1, *RMU* 1-14
- ODS-2, *RMU* 1-14
- ODT (On-Line Debugging Tool),
  - addresses, forming, *DEV* 5-3
  - breakpoint, *INT* 5-6, *ODT* 1-3, 2-7, 2-8
    - registers, *ODT* 2-5, 3-13, 3-14, 3-17
    - trap, *ODT* 1-3
  - commands, *DEV* 5-1 to 5-8
    - task breakpoint, *ODT* 3-15
- ODT (Cont),
  - command sequences and functions, *ODT* 3-1
    - correcting input to, *DEV* 5-3
    - error codes, *ODT* 3-14, 5-2
    - error conditions in tasks, *DEV* 5-8
    - error messages, *DEV* 5-3, *ODT* 5-1 to 5-3
    - examining locations with, *DEV* 5-4, 5-5
    - including, in a task, *DEV* 5-1
    - input files, switch options for, *ODT* 4-1
    - linking and initiating, *ODT* 4-2
    - maps, *DEV* 5-2
    - operating procedures, *ODT* 4-1
    - output file switch options, *ODT* 4-1
    - overview of, *DEV* 1-5
    - relationship to *ZAP*, *UTL* 19-1
    - source listings, *DEV* 5-3, 5-4
    - SST within, *DEV* 5-8
    - switches, *ODT* 4-1, 4-2
    - symbols and characters, *ODT* 2-2
    - tasks,
      - setting up, with, *DEV* 5-2 to 5-5
      - terminating, *DEV* 5-8
- Offset calculation commands, *ODT* 3-25
- Offline status, *DRV* 18-65
- Offsets,
  - FDB, *IOP* 2-25 to 2-27
  - PC relative, *ODT* 2-4, 2-7, 3-26
  - relative branch, *ODT* 2-4, 3-7, 3-25
  - symbolic, *EXE* 1-8, *IOP* 2-4
- Offset value, *ODT* 3-26
- Offspring,
  - spawning, *EXE* 6-131
  - starting task, *EXE* 4-1, 4-2
  - tasking support, *EXE* 4-1
- On-Disk Structure, see *ODS*
- On-Line Debugging Tool, see *ODT*
- Online status, *DRV* 18-65
- On-Line Task Loader, see *OTL*
- Op codes, *MAC* 2-4, C-1
- Open locations, *ODT* 2-1, 3-2
  - reprinting, *ODT* 3-33
- Operand field, *MAC* 2-4
  - separator, *MAC* 3-2
- Operating systems, *BEG* 1-1, 1-5, *INT* 1-1, *RMU* 1-11, 1-28, 1-33, 1-37, 2-5, 3-1, 5-12, 8-1, 8-27
  - memory layout, *RMU* 1-27
  - PDP-11, *RMC* 1-1
  - protection code, *RMU* 2-5
  - RSX-11S, *RLN* 1
- Operation macros, *RMC* 1-21, 1-22

- Operator field, *MAC* 2-4
- Operators, *INT* 4-1, 6-1
  - arithmetic, see Arithmetic operators
  - binary, *MAC* 3-5, 3-15
  - direct assignment, *MAC* 3-1
  - numeric control, *MAC* 6-26, 6-27
  - octal, *ODT* 2-6
  - Radix-50, *ODT* 2-2, 2-6, 3-39
  - register, *ODT* 2-2, 2-5
  - SLP, *UTL* 17-18, 17-19
  - unary, *MAC* 3-4
  - ZAP arithmetic, *UTL* 19-6, 19-7
- Optional arguments, *EXE* 6-5
- Optional subroutine arguments, *EXE* 1-10
- Options,
  - allocation, *RMC* 5-10
  - file processing, *RMC* 3-28
- Optimal density, *RMU* 1-34
- OTL (On-Line Task Loader), *INT* 1-2,
  - RLN* 1, *SSG* 1-1, 2-5
  - building, *SSG* 4-7
  - command line, *SSG* 2-6
  - error messages, *SSG* 2-9
  - exit from, *SSG* 2-7
  - functions, *SSG* 2-5
  - initiating, *SSG* 2-6
  - load devices supported by, *SSG* 2-5, 4-7
  - operation, *SSG* 2-7
  - size considerations for, *SSG* 4-7, 4-8
  - task loading with, *SSG* 8-3
- OTS (Object Time System), *TKB* 6-62
  - FORTRAN IV, *BEG* 2-15
  - library, *DEV* 7-1
- Output,
  - absolute binary, *MAC* 6-14
  - buffer, *DRV* 16-19
  - data conversion routines, *SLR* 5-1 to 5-11
  - formatting routines, *SLR* 6-1 to 6-14
  - listing files, *CDA*, *CDA* 1-7, 4-1 to 4-3
- Output files, *MCR* 3-3
  - formats for CMP, *UTL* 16-4, 16-5
  - RMS-11, *RMU* 9-19, 9-20, 9-21, 9-61, 9-65
  - SLP, *UTL* 17-2
  - specifiers for, *MCR* 3-3
    - defaults for, *MCR* 3-6
- Overflow,
  - arithmetic, *ODT* A-2
- Overhead,
  - activity, *RMU* 6-18
  - bucket, *RMU* 5-4, 6-2
  - deletion, *RMU* 6-18
  - duplicate, *RMU* 6-22
  - Overhead (Cont.),
    - I/O requests, *RMU* 8-31
    - record format, *RMU* 4-2, 4-4, 4-7, 5-4, 6-1, 6-2, 6-18
  - Overlay Descriptor Language, see ODL
  - Overlay, RMS-11, *RMU* 1-22
    - disk-resident, *RMU* 1-28
    - memory-resident, *RMU* 1-28
  - Overlay, *TKB*,
    - building an, *TKB* 4-34 to 4-42
    - data structures, *TKB* 4-20
    - description, effect on *TKB* performance, *TKB* D-4
    - descriptor language, *TKB* 4-22 to 4-28
      - summary of, *TKB* 4-42 to 4-44
    - error handling, *TKB* 5-8, 5-9
    - loading methods, *TKB* 5-1 to 5-8
    - operator, *TKB* 6-21, 6-27
    - programs, *TKB* 4-34
    - run-time, *TKB* 4-20
    - segments, *TKB* processing of, *TKB* 4-17
    - structures, *TKB* 4-1
    - tree, *TKB* 4-15
      - multiple-tree structures, *TKB* 4-28 to 4-33
  - Overlays, *MAC* 6-33, 6-35
    - defining multiple tree, *TKB* 4-28
    - disk-resident, *TKB* 4-2
    - loading mechanism of, *TKB* 4-16
    - loading methods of, *TKB* 5-1 to 5-8
    - memory-resident, *TKB* 4-5
    - pathloading, *TKB* 5-3
    - task, *ODT* 3-16

## P

- Pack, *RMU* 6-14
- Packet,
  - I/O, and I/O drivers, *WRT* 2-8, 2-16, 4-2, 4-18
  - I/O request, *CDA* 3-36, B-40, C-35
  - send-by-reference, *EXE* 6-138
- Page Address Register, see PAR
- Page Description Register, see PDR
- Page ejection, *MAC* 6-13, 7-3
- Page formatting, *MAC* 2-6
- Page, I/O, see I/O page
- Page management routines, *SLR* 8-21 to 8-32
- Panic dumps, *WRT* 3-16, 3-17, 3-19
- Paper tape reader/punch driver, *DRV* 17-1, *WRT* 6-3



- PAR (Page Address Register), *TKB* 2-10
- Parallel Communications Link, *DRV* 13-1
- Parameters,  
     getting issuing task, *EXE* 6-81  
     getting region, *EXE* 6-76  
     partition, *EXE* 6-74  
     RDB, *EXE* 3-18  
     time, *EXE* 6-79, 6-112  
     WDB, *EXE* 3-18
- Parentheses, *MAC* 3-2
- Parent/offspring tasking, *EXE* 4-1  
     directives for, *EXE* 4-1, 4-2, 6-4  
     relations, *RLN* 2-5  
     support of, *EXE* 4-1  
     task communication directives for,  
         *EXE* 4-2, 4-3
- Parity error reports, *ERL* 4-5, 4-6
- Parity errors, memory, *ERL* 1-2
- Parity support, vertical, *DRV* 12-11
- Partition Control Block, see PCB
- Partitions, *MCR* 1-1  
     characteristics of, *INT* 3-1  
     dynamic allocation of, *INT* 1-2  
     information on, *CDA* 3-25, B-12  
     mapped, *INT* 3-1, 3-2  
     memory, *INT* 3-1  
     naming, for target system, *TKB* 7-1  
     parameters for, *EXE* 6-74  
     subpartitions of, *INT* 3-2  
     system-controlled, *INT* 3-1, 3-2, *MCR* 1-1  
     types of, *INT* 3-2  
     user-controlled, *INT* 3-1, 3-2, *MCR* 1-1  
     unmapped, *INT* 3-1, 3-2
- Passwords, *BEG* 1-9, 1-10, *INT* 6-1, *MCR* 2-14
- PAT (Object Module Patch Utility),  
     changes in, *RLN* 27  
     checksum processing with, *UTL* 18-7  
         switch for, *UTL* 18-3  
     command line, *UTL* 18-2  
     error messages, *UTL* 18-7 to 18-13  
     files,  
         checksum processing of, *UTL* 18-3, 18-7  
         correction, *UTL* 18-3  
         input, *UTL* 18-3  
         validating contents of, *UTL* 18-7
- Task Builder and,  
     adding a subroutine to a module with,  
         *UTL* 18-5  
     overlying lines in a module with,  
         *UTL* 18-4  
     updating (patching) object modules with,  
         *UTL* 18-3 to 18-7
- Patching,  
     object modules (relocatable), with PAT,  
         *UTL* 18-3 to 18-7, *RLN* 18-20  
     segments, *TKB* 6-49  
     task image files, with ZAP, *RLN* 21,  
         *UTL* 19-1
- Patch level, *RMU* 9-7, 9-14, 9-22, 9-54, 9-62
- PC (program counter), *ODT* 2-4  
     relative location, open, *ODT* 3-6  
     relative offset, *ODT* 2-4, 2-7, 3-26  
     relative reference, *ODT* 3-6
- PCB (Partition Control Block), *CDA* 2-4, 3-25,  
     3-30, B-12, C-29, *WRT* 4-13, 4-14
- PCL11 parallel communications link driver,  
     *DRV* 13
- P command, *ODT* 3-17
- PDR (Page Description Register), *TKB* 2-10
- Percent sign, *MAC* 3-1, *ODT* 3-36
- Peripheral Interchange Program, see PIP
- Permanent Symbol Table, see PST
- Physical block, see Blocks
- Physical I/O, *DRV* 1-2  
     operations, *INT* 6-6, 6-7
- PIP (Peripheral Interchange Program),  
     *BEG* 4-1, *INT* 6-3, *MCR* 3-2  
     cleaning up a UFD with, *DEV* 3-7  
     command functions, *UTL* 4-6, 4-10  
     command line, *UTL* 4-1  
     copying Files-11 files with, *UTL* 4-6  
     creating concatenated object modules with,  
         *DEV* 4-2, 4-3  
     error messages, *UTL* 4-38  
     examining listings at a terminal with,  
         *DEV* 3-5, 4-5  
     file specifications for, *UTL* 4-1  
         defaults for, *UTL* 4-2  
         wildcards in, *UTL* 4-4  
     functions, *BEG* 4-1, 4-3 to 4-6, 4-8, 4-10,  
         4-20  
     overview of, *DEV* 1-6  
     spooling listings with, *DEV* 3-6, 3-7  
     subswitches, *UTL* 4-3, 4-10 to 4-37  
     switches, *UTL* 4-3, 4-10 to 4-37  
         new, *RLN* 35, 36
- Placement control, *RMC* 5-6, *RMU* 6-14
- PLAS (Programmed Logical Address Space),  
     *INT* 1-2, 3-10  
     directives, *INT* 1-2
- Platter, *RMU* 1-11
- Plus sign (+), *MAC* 3-1
- PMD, see Postmortem dumps

RSX-11M V03.2 Master Index

- Pointer,
  - stack, *MAC* 3-9, *ODT* 3-10
- Pointers, *IOP* 2-15, 2-16, *RMC* 3-48
  - retrieval, *RMC* 3-48
  - RMS-11*, *RMU* 5-6, 5-8, 5-17
  - SYSCM*, *WRT* 3-20, 3-23, 3-24
- Pool,
  - dump of, *CDA* 2-4, 3-38
  - free list, *CDA* 3-38
  - secondary, *CDA* 3-38
  - setting size of dynamic, *MCR* 4-118
  - statistics, *CDA* 1-7, 3-11, 3-12
- Pool block header formats, *RMS-11*,  
*RMC* 2-10
- Position-independent code, *MAC* H-1,  
*ODT* 3-28
  - writing, *MAC* G
- Postmortem dumps, *INT* 5-7, *MCR* 4-10,  
*RLN* 36, *TKB* 8-1 to 8-5
  - description of contents, *TKB* 8-4, 8-5
  - enabling with *TKB*, *DEV* 5-8, 5-9
  - overview of, *DEV* 1-5
  - PMD task for, *TKB* 8-1
  - relation to *SST*, *DEV* 1-5
  - sample of, *TKB* 8-1
- Power failure,
  - entry point, *WRT* 2-4, 3-2, 4-10
  - recovery procedures,
    - for disk and DECTapes, *DRV* 1-35
    - UNIBUS* switch, *DRV* 23-6
  - remote site, *DRV* 18-67
  - restart, *INT* 4-5
- Power recovery processor, *DRV* 18-67
- Preservation Utility, see *PRESRV*
- PRESRV* (Preservation Utility),
  - command line, *UTL* 12-10
  - computing number of blocks required for  
buffering, *UTL* 12-6, 12-25
  - error messages, *UTL* 12-27
  - formats,
    - Files-11*, *UTL* 12-1, 12-9, 12-10, 12-13,  
12-14
    - image, *UTL* 12-3, 12-9, 12-10, 12-13
    - image mode, *UTL* 12-1, 12-11, 12-14
    - logical tape, *UTL* 12-1, 12-2, 12-5, 12-8,  
12-11, 12-13, 12-15
  - operating procedures, *UTL* 12-3
  - switches, *UTL* 12-10 to 12-13, 12-16, 12-18,  
12-20, 12-21
- PRI* and *QUE* (Print and Queue Manager),
  - despooling files with, *UTL* 6-1
  - error messages, *UTL* 6-18 to 6-23
- PRI* and *QUE* (Cont.),
  - Print command,
    - command line, *UTL* 6-3
    - format, *UTL* 6-3
    - defaults for, *UTL* 6-4
    - switches,
      - file-related, *UTL* 6-8
      - job-related, *UTL* 6-4
    - print jobs, *UTL* 6-1 to 6-3
    - queue entries, *UTL* 6-2, 6-3
  - Queue Manager,
    - command format, *UTL* 6-9
    - commands,
      - nonprivileged user, *UTL* 6-9 to 6-19
      - privileged user, *GEN D*, *UTL* 7-4 to  
7-11
    - entry number, *UTL* 6-9
    - job identification, *UTL* 6-10
    - serial despooler with, *UTL* 6-1
    - spooling,
      - files with, *UTL* 6-1
      - output from user-written tasks with,  
*UTL* 6-17, 6-18
- Print and Queue Manager, see *PRI* and *QUE*
- PRINT* command,
  - format, *UTL* 6-3
  - defaults for, *UTL* 6-4
  - command line, *UTL* 6-3
  - description of, *UTL* 6-4 to 6-9
  - spooling output from user-written tasks  
with, *UTL* 6-17, 6-18
  - switches, *UTL* 6-4 to 6-8
- Printers, *DEV* 1-11
- Printing files, see *Files*
- Print jobs, *UTL* 6-1 to 6-3
  - attributes of, *ifiUTL* 6-2
  - identification, *UTL* 6-10
  - queued by user tasks, *UTL* 6-17, 6-18
  - queue entries for, *UTL* 6-2, 6-3
- Printout format, *ODT* 3-1
- Priorities, *RMU* 8-30
- Priority, *INT* 3-5, *MCR* 1-2
  - altering task, *EXE* 6-9, *MCR* 4-138
  - levels of, *ODT* A-2
  - processor, *MAC* E-3, *ODT* A-2
  - running, *MCR* 4-10
  - swapping, *INT* 3-6
- Priority level, *ODT* 1-3
- Privileges, *ODT* 1-3
- Proceed count, *ODT* 3-18
- Process, *WRT* 2-10, 2-13
- Process-control I/O, *DRV* 14-3, 15-14, 18-32

- Processing, *WRT* 2-9
  - RMS-11,
    - environment, *RMC* 1-2
    - options, file, *RMC* 3-28
    - system directive, *EXE* 1-2
    - trap, *ODT* A-2
- Process inputs, *INT* 2-2
- Processor,
  - Ancillary Control (ACP), see *ACP*
  - MCR indirect file, *MCR* 5-2
- Processor priority, *MAC* E-3, *ODT* A-2
- Processor status register, *ODT* 3-11
- Processor Status Word, see *PSW*
- Processor trap, *ODT* A-2
- Process outputs, *INT* 2-2
- Program, *RMU* 1-11, 1-25, 1-40, 2-3, 8-3
  - executable form, *RMU* 1-27
  - loadable, *INT* 2-3
  - object code, convert to, *RMU* 1-28
- Program boundaries directive, *MAC* 6-31
- Program counter, *MAC* 3-9, 5-1
- Program development, *INT* 2-2, 2-3, 5-1, *RMU* 8-1, 8-24
  - cross-reference listing in,
    - generating, *DEV* 3-6, 4-4, 4-5
  - debugging in, *INT* 5-6, 5-7, *DEV* 5
  - dumps in, *INT* 5-7, *DEV* 5-8, 5-9
  - editing utilities for, *INT* 5-1, 5-2
  - environment, *DEV* 1
    - DIGITAL-supplied system software, *DEV* 1-7 to 1-10
    - hardware, *DEV* 1-10
    - software tools, *DEV* 1-1 to 1-7
  - errors,
    - assembly, *DEV* 3-1, 3-2
    - task building, *DEV* 4-4 to 4-7
  - FORTTRAN IV, procedures, *DEV* 7
  - languages for, *INT* 5-3 to 5-5
    - supported, *INT* 2-2, 2-3
  - process, *DEV* 1-11, 1-12
  - program libraries in,
    - macro source, *DEV* 6-1 to 6-3
    - object module, *DEV* 6-4 to 6-7
  - program modules in,
    - assembling, *DEV* 3
    - correcting, *DEV* 3
  - source files in,
    - creating, from a skeleton file, *DEV* 2-9 to 2-11
    - diagnostics, performing, *DEV* 3-1, 3-2
    - editing, *DEV* 2-11
    - MACRO-11, creating, *DEV* 2
- Program development (Cont.),
  - task building in, *DEV* 4-1, *INT* 5-6, *TKB* 3-1 to 3-11
- Program execution,
  - commands for, *ODT* 3-17
- Program-local symbols, *MAC* E-4
- Programmed logical address space, see *PLAS*
- Programming,
  - development steps, *TKB* 1-1
  - languages, see *Languages*
  - protocol, *WRT* 2-13
  - standards and conventions, *MAC* 2-1, *WRT* 2-13
  - techniques, advanced, *DEV* 1-4
- Programmer number, *RMC* 5-68
- Programming languages, see *Languages*
- Program modules, *MAC* E-5
- Programs,
  - developing, see *Program development*
  - executing, *INT* 3-3
  - overlying, *TKB* 4-34
  - sectioning, *DEV* 1-3, 2-8
  - sharing, *INT* 2-3
  - source,
    - MACRO-11, see *MACRO-11*
    - system, *INT* 3-1
    - user, *INT* 3-1
    - development, overview of, *DEV* 1-11
- Program sections, see *PSECTS*
- Program source files, *MAC* E-12
- Project number, *RMC* 5-69
- Prologue, *RMU* 1-39, 4-1, 5-2, 5-4, 5-12, 5-13
- Prompting character, *ODT* 1-5, 3-1
- Prompts,
  - default, *MCR* 2-7, 4-2
  - MCR*, *MCR* 2-3, 2-7, 2-8
  - MCR* input, *MCR* 2-7, 4-1, 4-2
  - RMS-11, *RMU* 9-12, 9-21, 9-52, 9-61, 9-68
  - task, *BEG* 1-8, *MCR* 2-7
- Protecting files, see *File protection*
- Protection, *INT* 6-2
- Protection code, *RMC* 5-64, *RMU* 2-2, 2-6
- Protection information, *RMC* 1-13
- Protection mask, *MCR* 3-2
- Protection system,
  - multiuser, see *Multiuser protection system*
  - nonmultiuser, see *Nonmultiuser protection system*
- PSE (error logging pre-formatter), see *Error logging*
- PSECTS (program sections), *MAC* 3-12, 6-32, *ODT* 1-4

PSECTs (Cont.),  
 absolute, *MAC* 6-37  
 accessing, *MAC* 6-33  
 allocating, *TKB* 2-2, 4-19  
 attributes of, *TKB* 2-4  
 blank, *TKB* 2-3, 3-4, 3-13  
 creating, *MAC* 6-36, *TKB* 2-3  
 elements of, *TKB* 2-2  
 explicitly specifying, *TKB* 4-19  
 naming, *MAC* 6-33  
     restrictions on, *TKB* 3-10, 3-31, 3-38  
 ordering of, *TKB* 3-4  
 relocatable, *MAC* 6-37  
 scope of, *MAC* 6-33  
 virtual, *TKB* 3-53, 3-59  
 PST (Permanent Symbol Table), *MAC* 3-5, C-1  
 PSW (Processor Status Word), *EXE* 1-2,  
     *ODT* 3-10, 3-19, A-1, A-2  
 Purging files, see Files  
 Pyramid, *RMU* 5-4, 5-5

## Q

QIO, *IOP* 2-42 to 2-44, 4-19  
     request, *EXE* 6-90  
 QIO directive, *EXE* 6-90, *WRT* 2-2, 2-16  
 QIO functions,  
     standard, *DRV* 1-24  
     summary of ICS/ICR and DSS/DRS,  
         *DRV* 18-8  
 QIO macro, *DRV* 1-8 to 1-10  
 Quantity register, *ODT* 2-5, 3-12  
     indicator, *ODT* 3-38  
     operator, *ODT* 2-5  
 Query mode, *RMU* 9-11, 9-67  
 Queue,  
     I/O, and I/O drivers, *WRT* 2-8, 4-16  
     receive, *EXE* 6-119  
     receive-by-reference, *EXE* 6-108, 6-138  
 Queue entries, displaying clock, *MCR* 4-143  
 Queue I/O, *IOP* 2-42 to 2-44, 4-19  
     request, *EXE* 6-90  
 Queue Manager, *BEG* 4-1, 4-11, 4-12,  
     *INT* 6-3, *RLN* 2, 32, 33  
     RSX-11M V3.2, *UTL* 6-1, 7-1, *GEN D-1*  
         command descriptions, *GEN D-3* to *D-9*  
         command format, *UTL* 6-9, 7-4  
         commands,  
             nonprivileged, *UTL* 6-9 to 6-19  
             privileged, *UTL* 7-4 to 7-11  
             set-up, *UTL* 7-2 to 7-4

Queue Manager (Cont.),  
     components of, *UTL* 7-1  
     configuration control of, *UTL* 7-4  
     entry number, *UTL* 6-9  
     error messages, *GEN D-1*, *UTL* 7-11  
     installing, *UTL* 7-2 to 7-4  
     introduction, *GEN D-1* to *D-3*  
     job identification, *UTL* 6-10  
     print job entries, *UTL* 6-2, 6-3  
         attributes of, *UTL* 6-2  
     queue entries, *UTL* 6-2, 6-3  
     reference example, *UTL* 7-4  
 Queue managers, *BEG* 2-12  
 Queuing, *DEV* 1-7  
     message, routine for, *ERL* 2-3  
 Quotes,  
     double, *ODT* 3-35  
     single, *ODT* 3-34

## R

Radix,  
     changing default, *MAC* 3-13  
     decimal, *RMC* 1-2, 1-10, *RMU* 9-29  
     octal, *MAC* 3-13, *RMC* 1-18, 7-1  
     temporary, control operator, *MAC* 6-25  
 Radix-50,  
     character set, *MAC* A-4  
     characters, print word mode, *ODT* 3-36  
     control operator, *MAC* 6-23  
     data, *MAC* 6-22  
         storing, *MAC* 6-23  
     operators, *ODT* 2-2, 2-6, 3-39  
     translating to, *MAC* 6-22  
     word mode, *ODT* 3-31  
 Random access, *RMU* 1-11, 5-1, 5-8  
 Random access mode, *IOP* 1-2, 1-5, 2-9, 3-6,  
     3-9, 3-22, 3-23, 3-28 to 3-30, 4-17,  
     *RMC* 4-19, *RMU* 1-21  
 RDB (Region Definition Block), *EXE* 3-10  
     integer array, *EXE* 3-14  
     parameters, *EXE* 3-18  
 Read access, *IOP* 2-14, 3-3, 3-16, *RMU* 2-12  
 Read-only access, *MAC* 6-33  
 Read-sharing, *RMC* 3-52  
 Read-type operation, *RMU* 2-12  
 Read/write access, *MAC* 6-33  
 Record, *RMU* 1-3  
     access by contents, *RMU* 5-1  
     access, randomly, *RMU* 1-5  
     access, sequentially, *RMU* 1-4

- Record (Cont.),
- bucket spanning, *RMU* 1-34, 4-1, 6-2
  - consecutive, *RMU* 1-19
  - definition of, *RMU* 3-2, 4-2, 6-1
  - deleted, *RMU* 4-9, 6-2
  - duplicate, *RMU* 1-10
  - fixed and variable parts, *RMU* 1-16
  - fixed-length, *RMU* 1-37
  - header, *RMU* 2-5, 5-12, 7-2
    - buffers, *RMC* 4-23
  - identifier, *RMU* 1-5, 5-4
  - in a file, *RMU* 1-3, 5-1, 6-18
  - index, *RMU* 5-6
  - length, *RMU* 1-16, 1-34
  - location, physical, *RMU* 1-5
  - next, *RMC* 1-22, *RMU* 1-31
  - number, relative, *RMU* 1-7
  - operation, *RMC* 1-2, 1-19, *RMU* 1-5, 1-11, 1-16, 1-25, 2-3, 2-18, 3-6, 4-7, 8-25
    - asynchronous, *RMC* 1-22, 4-25
    - macros, *RMC* 1-22, 8-15
    - random, *RMC* 4-10, 4-14
    - synchronous, *RMC* 1-22
  - pointer, *RMU* 5-5
  - processed by RMS-11, *RMU* 1-33
  - size, *RMC* 4-28, *RMU* 1-37, 1-38, 4-4, 4-7, 6-1, 6-2, 6-9, 6-18, 9-36
  - storage, *RMU* 3-1, 4-1
  - undefined, *RMU* 1-17
    - format, *RMC* 3-46, *RMU* 1-40
  - valid, *RMU* 4-9
- Record Access Block, *RMC* 1-1, 1-10, 4-1
- internal, *RMC* 1-11, 2-4, 2-5, 4-9
- Record Access Stream, *RMC* 1-22, *RMU* 1-31
- Record attributes, *RMC* 3-44
- Record formats, *ERL* B-1, C-1, *RMC* 3-46, *RMU* 1-4, 1-11, 1-16, 1-37, 2-1, 2-14, 2-18
- overhead, *RMU* 4-2, 4-4, 4-7, 5-4, 6-1, 6-2, 6-18
- Record header buffer, *RMC* 4-23
- Record I/O operations, *IOP* 1-5, 1-6, 2-8 to 2-10
- Record length, *RMC* 5-51
- Record Management Services, see RMS-11
- Record number, relative, *RMC* 4-4, 4-10, 4-13, *RMU* 1-18
- Record operations, *RMC* 1-2, 1-19
- asynchronous, *RMC* 1-22, 4-25
  - synchronous, *RMC* 1-22
  - rewind, *RMU* 1-26
  - sequential, *RMU* 5-17
- Records,
- data, *RMU* 5-12
  - fixed-length, see Fixed-length records
  - logical, see Logical records
  - physical, *IOP* 1-4
  - replacing, *RMC* 8-31
  - size of, defining, *IOP* 2-6
  - types of, defining, *IOP* 2-5
  - undefined, format for, *RMU* 1-40
  - variable-length, *IOP* 3-27, 3-28, 4-17, *RMU* 1-37
    - format for, *RMC* 3-46, *RMU* 2-15
    - nonsequenced, *IOP* 1-5
    - sequenced, *IOP* 1-4, 2-5, 3-8
- Record storage cell, *RMU* 1-17, 1-18, 2-5, 4-1, 4-2, 9-20
- Record Transfer Mode, *RMC* 4-20
- Record's File Address (RFA), *RMC* 4-19, 4-22, 8-19, 8-23, *RMU* 1-23
- access by, *RMC* 4-19
- Recovery procedures,
- card input errors, *DRV* 11-3
  - cassette, *DRV* 9-5
  - DECtape, *DRV* 1-35, 6-6
  - disks, *DRV* 1-35
  - powerfail, *DRV* 1-35, 23-6
  - ready, *DRV* 10-5, 11-6
  - select, *DRV* 6-6, 8-12
- Reentry vector register, *ODT* 2-5, 3-12, 3-40
- Region Definition Block, see RDB
- Region(s),
- descriptors for, *TKB* 4-21
  - dynamic, *EXE* 3-4, *TKB* 3-50 to 3-53
  - executive, *INT* 3-7
  - resident shared, see Resident shared region
  - shared, *EXE* 3-5, *TKB* 3-1 to 3-11
  - static common, *EXE* 3-4
  - storage (pool), *MCR* 4-118
  - task, *EXE* 3-4
  - user, *INT* 3-7
- Register addressing mode, *MAC* 5-1, 5-7
- Register conventions, system-state, *WRT* 5-1
- Register deferred addressing mode, *MAC* 5-2, 5-7
- Register expression, *MAC* 5-1
- Register handling routines, *SLR* 2-1 to 2-5
- Register indicator,
- constant, *ODT* 3-37
  - quantity, *ODT* 3-38
- Register operator,
- constant, *ODT* 2-5
  - quantity, *ODT* 2-5
  - relocation, *ODT* 2-2

RSX-11M V03.2 Master Index

- Register(s),
  - accessing general, *ODT* 3-9
  - accessing special *ODT*, *ODT* 3-10
  - breakpoint address, *ODT* 2-5, 3-13
  - breakpoint instruction, *ODT* 2-5, 3-13
  - breakpoint proceed count, *ODT* 2-5, 3-14
  - console switch, *EXE* 6-78
  - constant, *ODT* 1-6, 2-5, 3-11, 3-37
  - default definitions for, *MAC* 6-15
  - format, *ODT* 2-5, 3-1, 3-11
  - general, *ODT* 3-18
  - general-purpose, *MAC* E-2
  - hardware, *MAC* E-2
  - internal, *ODT* 2-2
  - LUN, *ODT* 2-5, 3-13, 3-29, 3-30
  - memory limit, *ODT* 2-5, 2-8, 2-9, 3-12, 3-21, 3-24
  - octal, *ODT* 3-20
  - processor status, *ODT* 3-11
  - quantity, see Quantity register
  - reentry vector, *ODT* 2-5, 3-12, 3-40
  - relocation, *DEV* 5-2, *ODT* 1-4, 2-5, 2-7, 3-1, 3-12, 3-20, 3-37
    - commands for, *ODT* 3-27
    - operator, *ODT* 2-2
  - search argument, *ODT* 2-5, 2-7, 2-9, 2-10, 3-12, 3-21
  - search mask, *ODT* 3-11, B-1
  - SST stack contents, *ODT* 2-5, 3-15
  - SST vector, *ODT* 2-5, 3-14, 5-2
  - stack contents, *ODT* 2-5, 3-15
  - switch, getting contents of, *EXE* 6-78
  - system-state conventions for, *WRT* 5-1
  - task, *EXE* 1-2, 2-6
  - using, *IOP* 1-10, 2-23
  - volatile, *CDA* 1-7, 3-1
- Register standards, *MAC* E-2
- Register symbols, *MAC* 3-9
- Register term indicator, *MAC* 3-1
- Reject transitions,
  - example of using, *IOP* 7-18, 7-19
- Relative addresses, *MAC* 6-14
- Relative addressing, *ODT* 3-25
- Relative addressing mode, *MAC* 5-5, 5-7
- Relative branch offset, *ODT* 2-4, 3-7, 3-25
- Relative deferred addressing mode, *MAC* 5-6, 5-7
- Relative file,
  - organization of, *RMU* 1-17
- Relative record number, *RMC* 4-4, 4-10, 4-13, *RMU* 1-18
- Relative volume number, *RMU* 9-42
- Relocatability, *MAC* 6-34
- Relocatable addresses, *ODT* 3-29
- Relocatable expressions, *MAC* 3-16
- Relocatable module, *MAC* 6-34
- Relocatable program sections, *MAC* 6-37
- Relocation, *MAC* 4-1
- Relocation bias, *MAC* 2-2, 6-34, *ODT* 1-4, 3-29
- Relocation calculator,
  - commands, *ODT* 3-29
- Relocation registers, *ODT* 1-4, 2-5, 2-7, 3-1, 3-12, 3-20, 3-37
  - commands, *ODT* 3-27
  - operator, *ODT* 2-2
- Renaming files, see Files
- Repeat block directive, *MAC* 7-17
- Reports, error logging, see Error logging
- Requests,
  - I/O, see I/O requests
  - service, *RMC* 1-2
  - time-based, *MCR* 4-28
    - cancelling, *EXE* 6-44
- Reserved instruction, *ODT* 3-15
- Resident common,
  - building and linking to a, *TKB* 3-11
  - device, *TKB* 3-19
  - establishing offsets in, *TKB* 3-11, 3-16
  - loading a, *TKB* 3-14
  - typical, *TKB* 3-1
- Resident library, *RMU* 8-1, 8-3, 8-20 to 8-24, 8-31
  - building, *TKB* 3-23
  - building a 4K FCS, *GEN* G-1 to G-5
  - FCSRES, *RLN* 37, 38
  - restrictions on, *RLN* 37
  - typical, *TKB* 3-1
- Resident shared region,
  - accessing a, *TKB* 3-3
  - building a, *TKB* 3-3
  - defining a, *TKB* 3-1
  - installing a, *TKB* 3-3, 3-10
  - linking to a, *TKB* 3-6
  - position-independent, *TKB* 3-3
  - specifying partitions for a, *TKB* 3-3
  - using, to reduce *TKB* overhead, *TKB* D-5
- Restarting system,
  - after power failure, *INT* 4-5
- Retrieval pointers, *IOP* 2-15, 2-16, *RMC* 3-48
- Return (<RET>), *BEG* 1-4
- Return codes, *DRV* 1-28
  - directive condition, *DRV* 1-29
  - I/O status condition, *DRV* 1-31
- Rewind record operation, *RMU* 1-26

RSX-11M V03.2 Master Index

- RFA, see Record's File Address
- Right parenthesis ( ) , *MAC* 3-2
- RMDemo (system display program), *GEN* B-1 to B-4, *RLN* 40, 41
  - for RSX-11S, *SSG* 2-19
- RMS-11 (Record Management Services),
  - INT* 6-4, 6-5, *RLN* 21, *RMC* 1-1, *WRT* 2-1, 2-2
  - buffers, *RMC* 1-6, *RMU* 3-12
  - crash dumps, *RMU* 9-8
  - defaults, *RMC* 1-16, 3-20 to 3-22, *RMU* 2-2
  - diagnostic message, *RMU* 9-14, 9-71
  - error messages, *RMU* 9-5
    - utilities, *RMU* E-1
  - facilities, declaring, *RMC* 1-2
  - file deletion, *RMC* 8-8
  - MACRO-11, summary information, *RMC* 1-13
  - macro library (RMSMAC.MLB), *DEV* 1-8
  - nonoverlaid, *RMU* 8-2
  - overlaid, *RMU* 8-2
  - overlay, see Overlay, RMS-11
  - pointers, see Pointers
  - pool block header formats, *RMC* 2-10
  - processing,
    - environment, *RMC* 1-2
    - options, file, *RMC* 3-28
    - record, *RMU* 1-33
  - prompts, *RMU* 9-12, 9-21, 9-52, 9-61, 9-68
  - release of space, *RMC* 2-10
  - request for space, *RMC* 2-10
  - restrictions on RSX-11M, *RMU* A-3
  - routines and TKB, *RMC* 1-5, 1-22, *RMU* 8-1
  - syntax, *RMU* 9-9
  - tasks, *RMC* 1-22
  - utilities, see Utilities
  - volume initialization, *RMU* 8-27
- RMS11K, *INT* 6-4
- RMS11S.ODL, *RMU* 8-7
- RMSBCK, *RMU* 9-19
- RMSCNV, *RMU* 9-19
- RMSDEF, *RMU* 9-29
  - error messages, *RMU* E-1
- RMSDFN, *RMU* D-2
- RMSDSP, *RMU* 9-49
- RMSFAB, *RMU* 8-3, C-2
- RMSFILE, *RMU* C-2
- RMSIFL, *RMU* 1-27, 6-22, 6-30, 8-29, 9-2, 9-29, 9-57
- RMSMAC.MLB (RMS-11 macro library), *DEV* 1-8
- RMSRST, *RMU* 1-27, 9-1, 9-2, 9-10, 9-13, 9-67
- Root, *RMU* 5-5
- Root level number, *RMC* 5-50
- Root module, *RMC* 1-5
- Root segment, *TKB* 6-52, 6-63
- Root Virtual Block Number, *RMC* 5-59
- Round robin scheduling, *INT* 3-6, *RMU* 8-30
- Routine(s),
  - arithmetic,
    - double-precision, *SLR* 3-2 to 3-4
    - integer, *SLR* 3-1, 3-2
  - breakpoint, *ODT* 5-1
  - command decoder, *ODT* 1-1
  - command execution, *ODT* 1-1
  - completion, *RMC* 1-19
  - conditional, *WRT* 5-1
  - conversion,
    - ASCII-to-binary, *IOP* 4-7, 4-12, *SLR* 4-4, 4-5
    - ASCII-to-binary double-word, *SLR* 4-1 to 4-3
    - ASCII-to-Radix-50, *SLR* 4-6
    - binary-to-ASCII, general-purpose, *SLR* 5-10
    - binary-to-decimal, *SLR* 5-1 to 5-6
    - binary-to-octal, *SLR* 5-7 to 5-10
    - date and time format, *SLR* 6-2
    - input data, *SLR* 4-1 to 4-9
    - output data, *SLR* 5-1 to 5-11
    - Radix-50-to-ASCII, *SLR* 5-11
    - UIC, ASCII/binary, *IOP* 4-7
    - uppercase text, *SLR* 6-1
  - core allocation, *SLR* 8-8 to 8-15
  - core block,
    - release, *SLR* 7-4
    - request, *SLR* 7-3
  - data-organization, *RMU* 1-10
  - device control, *IOP* 4-24
  - entry points for, *EXE* 2-4
  - error handling, *IOP* 1-12, 3-2, 3-19, 3-23, 3-31
  - error logger, *ERL* 2-3
  - Executive error, *ERL* 1-2, 1-3
  - Executive stack and register dump, *WRT* 3-13, 3-14, 3-19
  - fatal error crash, *RMC* A-2, A-18
  - file close, *RMU* 8-8
  - file control, see File control routines
  - file open, *RMU* 8-7
  - file pointer, *IOP* 2-9, 3-29, 4-17 to 4-19
  - get command line, *IOP* 2-2, 6-1 to 6-13
  - K-series support, *DRV* 22-1, *SSG* 4-8
  - memory allocation, *ERL* 2-3
  - memory initialization, *SLR* 7-2, 8-5 to 8-7

RSX-11M V03.2 Master Index

Routine(s) (Cont.),

- memory management, dynamic, *SLR* 7-1 to 7-4
- memory management, virtual, *SLR* 8-1 to 8-20
- message, formatting and queuing, *ERL* 2-3
- module checking, *MAC* E-9
- nonoverlaid, *RMU* 8-2
- output formatting, *SLR* 6-1 to 6-14
- overlaid, *RMU* 8-2
- page management, *SLR* 8-21 to 8-32
- register handling, *SLR* 2-1 to 2-5
- relative file record operation, *RMU* 8-8
- sequential file record operation, *RMU* 8-8
- service,
  - AST, *EXE* 2-7
  - terminating, *EXE* 6-13
  - SST, *EXE* 2-4, 6-149, 6-151
- stack and register dump, *WRT* 3-13, 3-14, 3-19
- system library, see System library routines
- utility, *ODT* 1-2

RSX-11,

- command line format, *MAC* 8-3
- file specification switches, *MAC* 8-5

RSX-11M,

- applications of, *INT* 2-1, 2-2
  - multiprogramming, *INT* 3
  - real-time, *INT* 2-1, 2-2, 2-3
- devices, *DRV* 1-2
- file specifications, *BEG* 3-1
- file system, *INT* 6-1
- host system, copy procedures for, *SSG* 4-1, 4-2
- introduction to, *INT* 1-1
- I/O, overview of, *DRV* 1-1
- RMS-11 restrictions, *RMU* A-3
- shutting down, *MCR* 2-23
- size constraints, *RLN* 1
- system generation, see System generation, RSX-11M V3.2
- utilities, *BEG* 4-1
- 8K assembler, *MAC* G-1

RSX-11S,

- Basic MCR, see Basic MCR
- characteristics, *SSG* 1-1
- compatibility with RSX-11M, *INT* 1-1
- distribution kit contents, *SSG* 3-1
- error messages, *SSG* A-1
- FCS, *SSG* 2-21
- hardware/software configurations, *SSG* 1-2
- host/target systems, *SSG* 1-1

RSX-11S (Cont.),

- introduction to, *INT* 1-1, 1-2
- I/O drivers, *INT* 1-1
- MCR commands, *MCR* B-1
- operating system, *RLN* 1
- peripheral devices, support for, *SSG* 1-2
- software components, *SSG* 1-2
- system activity display programs, characteristics of, *SSG* 2-19
- system generation, *INT* 1-2, *SSG* 4
- tasks,
  - privileged, *SSG* 1-1
  - system, *SSG* 4-6
- RSXMAC.SML (system macro library),
  - DEV* 1-8
- RT-11, *INT* 6-1
  - format, *MCR* 3-1
- RUN command, *BEG* 2-13, 2-16, *DEV* 4-5, 7-5 to 7-7, *INT* 5-6
- Run-time macro calls, *IOP* 1-10, 1-11

S

- SCB (Status Control Block), *CDA* 3-31, 3-36, B-10, C-36, *WRT* 3-3, B-2
  - and I/O drivers, *WRT* 2-6, 2-18, 2-19, 4-46
- Search,
  - byte, *ODT* 3-21, B-1
  - effective address, *ODT* B-1
  - word, *ODT* 3-21, B-1
  - word/byte, *ODT* 3-21, B-1
- Search algorithms, *ODT* B-1
- Search argument, *ODT* 3-21
  - register, *ODT* 2-5, 2-7, 2-9, 2-10, 3-12, 3-21
- Search commands,
  - effective address, *ODT* 3-23
  - word/byte, *ODT* 3-21, 3-23
- Search limits, *ODT* 3-21
- Search mask, *ODT* 2-8, 3-21 to 3-23
  - register, *ODT* 3-11, B-1
- Search operations, *ODT* 3-21
- Sector, *RMU* 1-12
- Segments,
  - definition of, *TKB* 4-1
  - patching, *TKB* 6-49
- Semicolon (;), *MAC* 3-2, *ODT* 2-3, 3-26, 3-27
- Sequence,
  - return to interrupted, *ODT* 3-8
- Sequential access, *RMU* 1-11
- Sequential access mode, *IOP* 1-2, 1-5, 2-9, 3-6, 3-9, 3-23, 3-24, 3-30, *RMC* 4-19, *RMU* 1-19



- Serial Despooler Task, *UTL* 6-1, C-1
- Serial line errors, *DRV* 18-66
- SET command, *BEG* 2-1, 3-4, *MCR* 4-87 to 4-125
- Shareable code, *INT* 5-5
- Shadow recording linkage block, *CDA* C-49
- Shared access, *RMU* 2-5
- Shared data bases, accessing, *WRT* 2-9
- Shared Peripheral Operations On-Line, see Spool
- Sharing files, see Files
- Shutting down system, *MCR* 2-23
- SHUTUP program, *MCR* 2-23, *RLN* 2
- Significant events, *DRV* 1-10, *EXE* 1-3, 2-1, 6-45, 6-164, *INT* 3-7
- Single ASCII character indicator, *MAC* 3-2
- Single-instruction mode commands, *ODT* 3-19
- Single quote (apostrophe), *MAC* 3-1, 3-14, 6-19, 7-10, *ODT* 3-34
- SIP (System Image Preservation Program), *INT* 1-2, *SSG* 1-1, 2-12
  - building, *SSG* 4-8
  - command line, *SSG* 2-13
  - error messages, *SSG* 2-16
  - initiating, *SSG* 2-13
  - operation, *SSG* 2-14
  - size considerations, *SSG* 4-8
- Slash (/), *MAC* 3-2, *ODT* 4-3
- SLASH command, *ODT* 3-2, 3-27, 3-31
- SLP (Source Language Input Program), *BEG* 2-1, 2-2
  - audit trail, *UTL* 17-1, 17-2, 17-5, 17-6, 17-12, 17-16 to 17-19
  - changes in, *RLN* 27
  - checksum processing with, *UTL* 17-3, 17-16
  - command input, *UTL* 17-2, 17-11
  - command line, *UTL* 17-2
  - creating source files with, *UTL* 17-14
  - edit commands, *UTL* 17-5
  - editing source files with, *UTL* 17-10
  - error messages, *UTL* 17-20 to 17-24
  - indirect command files and, *UTL* 17-8
  - input files, *UTL* 17-1, 17-2
  - invoking, *UTL* 17-1
  - listing files, *UTL* 17-3, 17-10
  - operators, *UTL* 17-9
  - output files, *UTL* 17-3
  - processing, *UTL* 17-4
  - source files, *UTL* 17-2
  - switches, *UTL* 17-15, 17-16
    - new, *RLN* 36
  - updating source files with, *UTL* 17-10
- \$SNAP (snapshot dump)
  - overview of, *DEV* 1-6
  - usage as a debugging aid, *DEV* 5-9
- Snapshot dumps, *INT* 5-6, 5-7, *RLN* 36, *TKB* 8-5 to 8-11
  - example of, *TKB* 8-8
- Software,
  - changes to, *RLN* 23
    - ACNT, *RLN* 42
    - AST spawning, *RLN* 40
    - BRU, *RLN* 41, 42
    - CDA, *RLN* 23
    - console output device, *RLN* 40
    - COT, *RLN* 40
    - driver cancel I/O entry point, *RLN* 28
    - dumps, *RLN* 36
    - duplex drivers, differences between, *RLN* 28, 29
    - error code, *RLN* 38
    - FCSRES, *RLN* 37,38
    - indirect command processor (IND), *RLN* 25-27
    - KMC11 line printer driver, *RLN* 32
    - K-series call, *RLN* 36
    - LBR, *RLN* 27
    - LPA11-K laboratory peripheral accelerator, *RLN* 28
    - LUN reassign directive, *RLN* 27
    - MACRO-11, *RLN* 38, 39
    - MCR, *RLN* 23-27
    - MTAACP, *RLN* 30, 31
    - PAT, *RLN* 27
    - Queue Manager, *RLN* 32, 33
    - resident library restrictions, *RLN* 37
    - RMDemo, *RLN* 40, 41
    - SLP, *RLN* 27
    - system verification, for RK05 systems, *RLN* 32
    - tasks using floating point, *RLN* 29, 30
    - TKB, *RLN* 37
    - user-mode diagnostics, *RLN* 39
    - user-written drivers, *RLN* 37
    - utilities, new switches in, *RLN* 33-36
    - VT55 support, *RLN* 39
  - optional,
    - BASIC-PLUS-2, *RLN* 21
    - COBOL, *RLN* 22
    - DBMS, *RLN* 21
    - RMS-11, *RLN* 21
- Software interrupts, *EXE* 2-3
- Software layers, *RMU* 1-10, 1-33
- Software Performance Reports, see SPRs

- SORT-11, *RMU* 9-58
- Source files, *INT* 5-1, 5-3
  - creating, *DEV* 2-11, 7-2, *UTL* 17-14
  - executive, updating, *RLN* 10-12
  - FORTTRAN IV, see FORTTRAN IV
  - MACRO-11, see MACRO-11
  - program, *MAC* E-12
  - updating with SLP, *UTL* 17-10
- Source Language Input Program, see SLP
- Source line sequence numbers, *MAC* 6-3
- Source programs, see Programs
- Space, *MAC* 3-1
- Spawning,
  - tasks, *EXE* 4-1, 4-2, 6-131
  - with ASTs, *RLN* 40
    - changes to, *RLN* 40
- Special arguments, *ODT* 3-37
- Special characters, *MAC* B-1
  - in macro arguments, *MAC* 7-6
- Specifiers,
  - file, *MCR* 3-3, 3-4, 5-1
  - UIC, *MCR* 2-14, 3-4
- Speed, *RMU* 2-3
- Spool (Shared Peripherals Operation On-Line),
  - UTL* 6-1
- Spooling, *IOP* 8-1, *RLN* 2
  - automatic, of listing files, *BEG* 2-12
  - from user-written tasks, *UTL* 6-17, 6-18
  - listing output, *MAC* 8-7
  - with PIP, *DEV* 3-6, 3-7, *UTL* 4-33
  - with PRI and QUE, *UTL* 6-1
  - with PRINT\$ macro call, *IOP* 8-1, 8-2
  - SPRs (Software Performance Reports),
    - RLN* 8-10, *RMC* A-19
- SST (Synchronous System Trap), *DRV* 1-11,
  - EXE* 2-4, *INT* 3-9
  - effect in ODT, *DEV* 5-8
  - fault, *WRT* 3-22, 3-23
  - relation to PMD, *DEV* 1-5
  - role in task termination, *DEV* 4-5
  - service routines, *EXE* 2-4, 6-149, 6-151
  - stack contents register, *ODT* 2-5, 3-15
  - vector table, *EXE* 6-149, 6-151
- Stack and register dump routine, *WRT* 3-13,
  - 3-14, 3-19
- Stack contents registers, *ODT* 2-5, 3-15
- Stack format, *EXE* 2-5, 2-7, 2-8
- Stack pointer, *MAC* 3-9, *ODT* 3-10
- Stack structure, *WRT* 3-22, 3-23
- Statement format, *MAC* 2-1
  - FORTTRAN IV, *DEV* 7-2
  - MACRO-11, *DEV* 2-3
- Static common regions, *EXE* 3-4
- Statistics block, *IOP* 8-1
- Status,
  - nonprivileged, *MCR* 2-15
  - privileged, *MCR* 2-15
- Status array, *isb*, *DRV* 14-3, 15-14, 16-8
- Status codes, *RMC* 3-54, 4-30
  - I/O function and, *DRV* B-1
- Status Control Block, see SCB
- Status error codes, I/O, *DRV* B-1
- Status flags, task, *MCR* 4-21
- Status information, device-independent,
  - WRT* 4-22, 4-23
- Status success codes, I/O, *DRV* B-3
- Status value, *RMC* 3-55, 4-31, A-2
- .STB file, see Symbol definition file
- STD (System Task Directory), *CDA* 3-38,
  - INT* 3-4, *MCR* 1-3, 4-146
  - Queue, *INT* 3-6
- Stop, *EXE* 6-147
- Stop-bit synchronization, *EXE* 2-11, 2-12
  - directives, *RLN* 2,6
- Storage region (pool), *MCR* 4-118
- Storage space,
  - reserving, *MAC* 3-13, 6-30
- Stream record format, *RMC* 3-46
- String constants, *MCR* 5-10
- String expressions, *MCR* 5-10
- String symbols, *MCR* 5-5, 5-7, 5-9, 5-10
- Structures, data, see Data
- Subconditional assembly, *MAC* 6-43
- Subexpressions,
  - example of using, *IOP* 7-6
  - to parse complex grammars, *IOP* 7-6
- Subpartitions, *INT* 3-2, *MCR* 1-2
- Subroutine calls, *EXE* 1-11
- Subroutine arguments,
  - optional, *EXE* 1-10
- Substitution mode, *MCR* 5-20
- Substrings, *MCR* 5-10
- Subswitches, PIP, *UTL* 4-3, 4-11
- Subtitle, *MAC* 6-8
- Success codes, *DRV* B-3
- Success/failure indication, *MAC* E-9
- Swapping, *INT* 3-6
- Switches,
  - BAD, *UTL* 9-2, 9-5 to 9-8
  - BRU, *RLN* 34, *UTL* 10-2 to 10-21
  - CDA, *CDA* 2-1 to 2-8, *RLN* 34
  - CMP, *UTL* 16-2, 16-3
  - control, *MAC* 8-6
  - default, *MCR* 3-6

Switches (Cont.),

DMP, *RLN* 34, *UTL* 15-2 to 15-6  
 DSC, *RLN* 34, *UTL* 11-8, 11-10 to 11-16,  
 11-18 to 11-22  
 error logging, *ERL* 3-5 to 3-7  
 FLX, *RLN* 34, *UTL* 5-3 to 5-8  
 FMT, *UTL* 8-1, 8-2, 8-6 to 8-8  
 for utilities, summary of, *UTL* A-1  
 function control, *MAC* 8-6  
 indirect file processor, *MCR* 5-10  
 LBR, *UTL* 14-3, 14-4, 14-10 to 14-13  
 ODT, *ODT* 4-1, 4-2  
 PAT, *UTL* 18-3  
 PIP, *UTL* 4-3, 4-10 to 4-37  
 PRESRV, *UTL* 12-10 to 12-21  
 Print command, *UTL* 6-4 to 6-8  
 Queue Manager, *UTL* 6-10  
 SLP, *UTL* 17-15, 17-16  
 SYE, *ERL* 3-5  
 TKB, *TKB* 6-1 to 6-44  
 modifying defaults for, *TKB* D-7 to D-11  
 ZAP, *UTL* 19-2, 19-3  
 Switch register, getting contents of, *EXE* 6-78  
 Switch value, *MCR* 3-5  
 SYE (error logging report generator),  
 see Error logging  
 Symbol control directive, *MAC* 6-39  
 Symbol definition file (.STB file),  
*TKB* 3-3, 3-8  
 Symbol examples, *MAC* E-4  
 Symbolic definitions, *WRT* C-1  
 Symbolic offsets, *EXE* 1-8, *IOP* 2-4  
 Symbolics, standard, using, *MAC* E-3  
 Symbolic value, *RMC* 1-10  
 Symbols, *MAC* E-3, *WRT* 3-2, 3-3, 3-6, 4-7,  
 4-29, B-2, B-3  
 cross-referencing, *DEV* 3-6  
 defining local, *DEV* 2-7  
 defining macro, *DEV* 1-3  
 field size, *IOP* J-1  
 global, see Global symbols  
 in cross-reference listing, *TKB* 6-11  
 indirect command file, *MCR* 5-5  
 local, see Local symbols  
 logical, *MCR* 5-5, 5-6  
 logical test of, *MCR* 5-26  
 macro, *MAC* 3-5  
 MACRO-11 evaluation of, *DEV* 1-2, 3-1  
 numeric, *MCR* 5-5, 5-7, 5-9, 5-19, 5-29,  
 5-33, 5-34, 5-36  
 ODT characters and, *ODT* 2-2  
 program-local, *MAC* E-4  
 register, *MAC* 3-9

Symbols (Cont.),

reserved, *TKB* C  
 resolving, *BEG* 2-12  
 global, *DEV* 1-4, 4-2  
 macro, *DEV* 2-6, 6-3  
 search for undefined, *TKB* 6-16  
 special, *MCR* 5-6  
 string, *MCR* 5-5, 5-7, 5-9, 5-10  
 substituting values for, *INT* 4-3  
 undefined, *MAC* 3-7, 3-14  
 user-defined, *MAC* 3-5  
 Symbols and expressions, *MAC* 3-1  
 Symbol table file, *RMU* 8-21  
 Symbol table listing, *MAC* 1-2  
 Symbol value substitution, *MCR* 5-8  
 Synchronous System Trap, see SST  
 Syntax,  
 Basic MCR, *MCR* B-1  
 command, *MCR* 4-4  
 MCR command file, *MCR* 5-11  
 RMS-11, *RMU* 9-9  
 Syntax rules, summary of, *TKB* 1-9  
 SYSGEN, see System generation  
 SYSCM pointers, *WRT* 3-20, 3-23, 3-24  
 SYSLIB.OLB system object module library,  
*DEV* 1-9, 1-10  
 SYSPAR, *INT* 3-7  
 SYSTB, *WRT* 3-19  
 System,  
 baseline bootstrapping, *GEN* 2-5 to 2-9  
 file, see File system  
 host, *INT* 1-1  
 for TKB, *TKB* 7  
 preparing, *GEN* 3-1 to 3-7  
 maintaining, see System maintenance  
 mapped, see Mapped systems  
 multiuser, task priority in, *TKB* 6-65  
 multiuser protection, see Multiuser protec-  
 tion system  
 nonmultiuser, see Nonmultiuser protection  
 system  
 operating, see Operating systems  
 restarting, after power failure, *INT* 4-5  
 shutting down, *MCR* 2-23  
 target, for TKB, *TKB* 7  
 traps, *DRV* 1-11, *EXE* 2-4, *INT* 3-9  
 unmapped, see Unmapped systems  
 System activity display programs,  
 characteristics of, *SSG* 2-19  
 System common, *CDA* 1-7, 3-5, 3-6, 3-8 to 3-11  
 System configuration, *INT* 1-1  
 System-controlled partitions, *INT* 3-2,  
*MCR* 1-1, *TKB* 6-55

- System conventions, *GEN F*
- System crash dumps, see *Dumps*
- System data structures, *WRT C-1*
- System defaults, *RMC 1-16, 3-25*
- System directives, see *Directives*
- System disk (SY:), *BEG 2-13, 3-2, 3-4*
- System display program, see *RMDemo*
- System generation, *RLN 2, 4, 5*
  - IAS host, *SSG 4-4*
  - installation verification for, *RLN 8*
  - RSX-11M host, dialogue, *SSG 5-1*
- System generation, RSX-11M V3.2, *CDA 1-1, INT 1-1, 3-7*
  - bootstrapping baseline system for, *GEN 2-5 to 2-9*
  - command files, *GEN 1-1*
    - invoking, *GEN 1-6*
  - directive selection during, *EXE D-1*
  - distribution kit, *GEN 2-2 to 2-5*
    - backing up, *GEN 2-5 to 2-9*
  - environments, *GEN 2-1*
  - error messages, *GEN 11-1 to 11-7*
  - hardware bootstrap procedures, *GEN I-1 to I-6*
  - host system, preparing, *GEN 3-1 to 3-7*
  - installation verification,
    - error codes, *GEN 10-14 to 10-16*
    - hardware, *GEN 10-1*
    - introduction, *GEN 10-1*
    - operating procedures, *GEN 10-2 to 10-4*
    - sample console dialogue, *GEN 10-4 to 10-14*
    - software, *GEN 10-1, 10-2*
  - options, FCS library, *IOP K-1*
  - overview of, *GEN 1-1*
  - phase I,
    - details of,
      - executive questions, *GEN 5-17 to 5-35*
      - host configuration questions, *GEN 5-15 to 5-17*
      - peripheral questions, *GEN 5-43 to 5-75*
      - processing, *GEN 5-75 to 5-78*
      - set-up questions, *GEN 5-2 to 5-19*
      - steps, *GEN 5-1*
      - target configuration questions, *GEN 5-10 to 5-15*
      - terminal driver questions, *GEN 5-35 to 5-43*
    - summary of,
      - executive, *GEN 4-1 to 4-5*
      - peripherals, *GEN 4-13 to 4-24*
      - set-up, *GEN 4-1 to 4-5*
      - terminal driver, *GEN 4-11 to 4-13*
- System generation, RSX-11M V3.2 (Cont.), phase II,
  - details of,
    - loadable driver build, *GEN 7-15, 7-16*
    - processing, *GEN 7-17 to 7-23*
    - questions, *GEN 7-3 to 7-15*
  - notes on, *GEN 7-24*
  - summary of,
    - loadable driver build, *GEN 6-2, 6-3*
    - questions, *GEN 6-1, 6-2*
- phase III,
  - details of,
    - BLDUMD.COMD file, *GEN 9-11 to 9-15*
    - questions, *GEN 9-1 to 9-10*
  - questions,
    - format, *GEN 1-5*
    - logical flow of, 1-5, 1-6
    - saved answers file, symbols for, *GEN A-1 to A-7*
    - start-up display sequence, *GEN 2-9, 2-10*
    - steps in, *GEN 1-3, 1-4*
    - system conventions, *GEN F-1 to F-5*
  - VMR,
    - command descriptions, *GEN 8-5 to 8-52*
    - command summary, *GEN 8-4, 8-5*
    - error messages, *GEN 8-53 to 8-66*
    - file specifiers, *GEN 8-2 to 8-4*
    - starting, *GEN 8-1, 8-2*
- System generation, RSX-11S V2.2, *INT 1-2, SSG 4*
- System image,
  - bootable, *MCR 4-139*
  - saving, *MCR 4-172*
- System Image Preservation Program, see *SIP*
- System information, *CDA 1-7, 3-1*
- System libraries, *SSG 8-1*
  - contributions from, in maps, *DEV 4-5*
  - macro, *SSG 8-2*
- System library routines,
  - arithmetic routines, *SLR 3-1 to 3-4*
  - dynamic memory management routines, *SLR 7-1 to 7-4*
  - input data conversion routines, *SLR 4-1 to 4-9*
  - output data conversion routines, *SLR 5-1 to 5-11*
  - output formatting routines, *SLR 6-1 to 6-14*
  - register handling routines, *SLR 2-1 to 2-5*
  - summary procedures for, *SLR 9-1*
  - virtual memory management routines, *SLR 8-1 to 8-32*

System macro library, *EXE* 1-5, *MAC* 7-18,  
*SSG* 8-2  
*RSXMAC.SML*, *DEV* 1-8  
System macros, retrieving, *DRV* 1-15  
System maintenance,  
  commands, *MCR* 4-7  
  features of, *INT* 4-4, 4-5  
System message file, *BEG* 1-10  
System object module library, *DRV* 15-11,  
  *TKB* 2-7  
  *SYSLIB.OLB*, *DEV* 1-9, 1-10  
System programs, *INT* 3-1  
System protection code, *RMU* 2-5  
Systems,  
  mapped, see Mapped systems  
  operating, see Operating systems  
  unmapped, see Unmapped systems  
System-state register conventions, *WRT* 5-1  
System Task Directory, see *STD*  
System tasks, *DEV* 1-1  
  *RSX-11S*, *SSG* 4-6  
System traps, *EXE* 2-3, *INT* 3-9  
  asynchronous (ASTs), *DRV* 1-11, 2-9, 2-10,  
  2-35, 3-32, *EXE* 2-1, 2-4, 2-6  
  synchronous (SSTs), *DRV* 1-11, *EXE* 2-4  
System UIC, *MCR* 4-113

## T

Tab character, *BEG* 1-4, *MAC* 2-2, *MCR* 2-3  
Table-driven parser, see *TPARS*  
Tape,  
  characteristics of, *DRV* 8-7, 8-8  
  resetting, *DRV* 8-13  
Tape cartridge, *DRV* 7-1  
Tape devices,  
  format for BRU, *UTL* 10-26  
  multivolume operations with BRU,  
  *UTL* 10-27  
Tape volumes,  
  rewinding, *RMU* F-3  
Tapes,  
  DECtape, see DECTape  
  magnetic, see Magnetic tapes  
Target data bucket, *RMU* 5-10, 5-12  
Target system,  
  configuration, *INT* 1-1  
  for *TKB*, *TKB* 7  
Task,  
  addresses, printing, *ODT* 3-1  
  breakpoint commands, *ODT* 3-15

Task (Cont.),  
  breakpoints, user, *ODT* 1-3  
  design, *RMU* 3-6, 4-7, 7-1  
  exits, *ODT* 2-10, 4-4  
  extensions, *MCR* 4-119  
  headers, *CDA* 3-22, B-4, C-18, *TKB* 6-14,  
  6-15, 6-17, *WRT* 2-17, 2-18, 3-20, 3-21  
  interaction with error logging, *ERL* 2-4  
  I/O operation, *INT* 6-4  
  memory, *TKB* 2-15  
  prompt, *BEG* 1-8, *MCR* 2-7  
  regions, *EXE* 3-4  
  registers, *EXE* 1-2, 2-6  
  size, *RMU* 2-5  
  status flags, *MCR* 4-21  
Task Builder, see *TKB*  
Task Control Block, see *TCB*  
Task dumps, *CDA* 3-42  
  postmortem, *INT* 5-7, *MCR* 4-10, *RLN* 36,  
  *TKB* 8-1 to 8-5  
  snapshot, *INT* 5-6, 5-7, *MCR* 4-10,  
  *RLN* 36, *TKB* 8-5 to 8-11  
Task image, *RMU* 8-4, 8-21  
  building, *BEG* 2-14 to 2-16  
  checkpoint space for, *TKB* 6-6, B-7  
  creating a, *DEV* 4-1 to 4-3  
  default type for, *TKB* 1-8  
  error codes, *ODT* 5-2  
  file, structure of, *TKB* B  
  memory allocation (map) file, *BEG* 2-16  
  options, *BEG* 2-16  
  switches, *BEG* 2-16  
  symbol table file, *ODT* 4-1  
Task/Image File Patch Program, see *ZAP*  
Task image files,  
  locations in, manipulating, see Locations  
  patching, *RLN* 21, *UTL* 19-1  
Task names,  
  convention for, *MCR* 4-3  
  references to in *MCR*, *MCR* 5-36  
Task offspring, starting, *EXE* 4-1, 4-2  
Tasks, *INT* 1-1, 3-1, 5-1  
  aborting, *DEV* 4-6, *EXE* 6-7, 6-137,  
  *MCR* 4-10  
  activating, *EXE* 6-105, 6-112, 6-121, 6-131,  
  6-155, *INT* 3-5  
  active, *CDA* 2-2, 3-15 to 3-20, *INT* 3-4,  
  *MCR* 1-3  
  attached, typeahead buffering for, *RLN* 4  
  attributes of, *TKB* 6-32, 6-33  
  base address of, *INT* 3-2  
  blocked, *EXE* 1-16, *INT* 3-4

Tasks (Cont.),

blocking, *EXE* 6-166, 6-168  
 building, *DEV* 4-1 to 4-3, 7-5, *INT* 5-6,  
     *RMC* 1-2, *TKB* 3-8  
 checkpointable, *TKB* 6-9  
 checkpointing, *INT* 3-5, 3-6  
 connecting to, *EXE* 4-1 to 4-4  
 control commands for, *MCR* 4-7  
 creating, *MCR* 1-2, 1-3  
     *RMS*-11, *RMC* 1-22  
 debugging, *DEV* 4-5, 4-6, 7-5 to 7-7,  
     *INT* 5-6  
 default conditions in, *DEV* 4-3, 4-4  
 dormant, *EXE* 1-16, *INT* 3-4, *MCR* 1-3  
 dumping, *CDA* 3-42  
 error logging, *ERL* 1-2  
 examining registers and stack of, *DEV* 5-8  
 executing, *INT* 5-6, *MCR* 1-2, 1-3  
     concurrently, *INT* 2-1, 3-3, 4-3  
     scheduling for, *INT* 4-2  
     terminating, *EXE* 6-7, 6-59, 6-61, 6-137,  
         *MCR* 4-10  
 extending, *MCR* 4-119  
 exiting from, *EXE* 1-3  
     *RSX*-11M, *BEG* 1-6  
 fixed, freeing, *MCR* 4-144  
 fixing, in memory, *MCR* 4-144  
 floating point, using, *RLN* 29, 30  
 generating maps of, *DEV* 4-4, 4-5  
 global symbol references in, *TKB* 6-59  
 identifying partitions for, *TKB* 6-64  
 including ODT in, *DEV* 5-1, *TKB* 6-12  
 initiate or resume, *ODT* 3-15, 3-17  
 installed, *INT* 3-4, *MCR* 4-127, 4-171  
     removing, *EXE* 1-18, *MCR* 4-171  
 installing, *MCR* 1-3, 4-146  
     data needed by system for, *TKB* B-1  
 install-run-remove, *MCR* 4-5  
 linking, *DRV* 15-13, 18-23 to 18-25, 18-60,  
     18-70  
     to shared regions, *TKB* 3-6 to 3-11  
 loading,  
     using *OTL*, *SSG* 8-3  
     using *VMR*, *SSG* 8-3  
 macro calls in, *DEV* 6-3  
 maximum record buffer size, *TKB* 6-62  
 maximum stack size of, *TKB* 6-72  
 MCR command interface and, *MCR* 4-3 to  
     4-5  
 memory-resident, *DEV* 5-7, *INT* 3-2  
 names for, *DEV* 5-2, *EXE* 1-10, *MCR* 4-3,  
     5-36, *TKB* 6-74

Tasks (Cont.),

nonprivileged, *RLN* 1  
 directive restrictions for, *EXE* 1-18, 1-19  
 object library routines in, *DEV* 6-5, 6-6  
 ODT, see ODT  
 ODT in, including, *DEV* 5-1  
 operation of, *MCR* 1-2  
 overlaid, *INT* 3-10, *ODT* 3-16  
 parent, *EXE* 4-2  
 priority of, *INT* 3-5  
     altering, *EXE* 6-9, *MCR* 4-138  
     execution, *TKB* 6-65  
     in multiuser systems, *TKB* 6-65  
 privileged, *INT* 3-2, *RLN* 1, *TKB* 3-62 to  
     3-69  
     mapping, *EXE* 3-18  
     *RSX*-11S, *SSG* 1-1  
 prompt for, *MCR* 2-7  
 ready-to-run, *EXE* 1-16, *INT* 3-4  
 real-time, *INT* 3-5  
 relocating, *TKB* 2-10, 2-16  
 requesting, *EXE* 6-105, 6-112, 6-121  
 rescheduling, *MCR* 4-80  
*RSX*-11M, exiting from, *BEG* 1-6  
*RSX*-11S,  
     privileged, *SSG* 1-1  
     system, *SSG* 4-6  
 running, *BEG* 2-4, *DEV* 4-5, 7-5,  
     *EXE* 6-105, 6-112, *MCR* 4-80  
 scheduling, *EXE* 6-112  
     external, *INT* 4-2  
     internal, *INT* 4-2  
     round robin, *INT* 3-6, *RMU* 8-30  
     swapping, *INT* 3-6  
 spawning of, *EXE* 4-1, 4-2, 6-131  
 SST in, *DEV* 4-5, 4-6  
     vector address for, *TKB* 6-74  
 states of, *EXE* 1-16 to 1-18, *INT* 3-4  
 stopping, *EXE* 2-11, 4-4, 6-145, 6-147, 6-148  
 suspended, resuming, *EXE* 6-111,  
     *MCR* 4-79  
 suspending, *EXE* 6-128, 6-164  
 synchronizing, *EXE* 2-11  
 system, *DEV* 1-1  
     *RSX*-11S, *SSG* 4-6  
 system library contributions to, *DEV* 4-5  
 terminating, *DEV* 4-6  
 transfer (starting address) in, *DEV* 2-7, 4-2,  
     4-6  
 unstopping, *EXE* 2-11, 4-4, 6-155  
 user, running, *ODT* 3-17  
 user-written, spooling from, *UTL* 6-17, 6-18

RSX-11M V03.2 Master Index

- Task Termination Notification, see TKTN
- T-bit, *ODT* A-1
- T-bit trap, *ODT* 3-15, A-2
- TCB (Task Control Block), *CDA* 2-2, 3-15, 3-17, 3-28, B-15, C-39, *MCR* 4-21, 4-146, 4-173
- Teleprinter mode, *MAC* 6-4
- Teletypes, *DRV* 2-3, 3-2
- Terminal argument or expression indicator, *MAC* 3-2
- Terminal drivers,
  - differences between, *RLN* 28, 29
  - full-duplex, *DRV* 2-1, *RLN* 1, 2, 4
  - half-duplex, *CDA* 3-34, *DRV* 3-1, *RLN* 1
  - virtual, *DRV* 4-1
- Terminal line truncation, *DRV* 3-29
- Terminal register indicator, *MAC* 3-2
- Terminals,
  - attached, *INT* 4-3, *MCR* 2-6
  - characteristics of, *MCR* 2-5
    - getting, *DRV* 2-12, 3-10
    - setting, *DRV* 2-19, 3-14
    - side effects of, *DRV* 3-31
  - control characters on, *BEG* 1-3, 1-5, 1-6, *DRV* 2-25, 2-27, *MCR* 2-1 to 2-5
  - controlling output to, *DEV* 3-5
  - displaying messages at, *MCR* 4-24
  - displays at, *MCR* 2-3
  - escape sequences for, defining, *DRV* 2-29, 3-22
  - examining assembly listings at, *DEV* 3-5
  - function keys on, *BEG* 1-3
  - initial default values for, *BEG* 1-9
  - input from, *BEG* 1-6
  - input prompts for, *MCR* 2-7, 2-8
  - keyboard on, *BEG* 1-3
  - logging off, *MCR* 2-13, 4-27
  - logging on, *MCR* 2-13, 4-41
  - operations of, *INT* 4-3, *MCR* 2-1
  - privileged, *INT* 4-1, *MCR* 2-6
  - slave, *INT* 4-4, *MCR* 2-6, 4-105
  - special character keys on, *MCR* 2-1 to 2-5
  - state of, *BEG* 1-8
  - status of, *CDA* 3-31, B-19
  - system access through, *BEG* 1-9
  - types of operator, *BEG* 1-1, 1-2, *DEV* 1-10, *MCR* 4-8
  - UIC of, *MCR* 3-5, 4-108
  - unattached, *MCR* 2-6
  - using, *BEG* 1-1
- Terminator,
  - item or field, *MAC* 3-1
- Terminator (Cont.),
  - label, *MAC* 3-1
  - line, options for, *MCR* 4-166
- Terminator word, *EXE* 6-71
- Time,
  - current,
    - getting, *EXE* 6-79
    - setting, *MCR* 4-130
  - schedule delta, *EXE* 6-112
- Time-based requests, *MCR* 4-28
  - cancelling, *EXE* 6-44
- Time interval, *MCR* 4-80
- Time-of-day, *MAC* 6-8
- Timer, *DRV* 15-7
- Time unit value, *MCR* 4-80
- TKB (Task Builder), *BEG* 2-1, 2-12 to 2-16, *MAC* 2-2, 4-1, *ODT* 1-4, 4-1
  - and RMS-11 routines, *RMC* 1-5, 1-22, *RMU* 8-1
  - assigning addresses,
    - on mapped systems, *TKB* 2-10 to 2-14
    - on unmapped systems, *TKB* 2-8, 2-9
  - building and linking with, *TKB* 3-8
  - changes in, *RLN* 37
  - command line, *TKB* 1-2, 1-3
  - comments, *TKB* 1-7, 1-8
  - data structures,
    - building system, *TKB* 2-14 to 2-16
    - overlay, *TKB* 4-20, 4-21
  - default conditions of, *DEV* 4-3, 4-4
  - default LUN, *DEV* 4-3, 4-4
  - default search of system library by, *DEV* 1-10, 4-1, 4-2
  - default transfer address in, *DEV* 4-2
  - dynamic regions, *TKB* 3-50 to 3-53
  - error messages, *DEV* 4-1, *TKB* F
    - virtual memory, *TKB* D-5, D-6
  - errors,
    - processing of, *DEV* 4-1, 4-2
    - typical, *DEV* 4-5, 4-6
  - fast, *DEV* 4-3, *TKB* E
  - file specifications, *TKB* 1-8, 1-9
  - functions, *TKB* 1-1, 2-1
  - generation of, with,
    - cross-reference listings, *DEV* 4-4
    - full map, *DEV* 4-5
    - standard map, *DEV* 4-4
  - global symbols,
    - resolving, *TKB* 2-7, 4-16
  - host system for, *TKB* 7
  - IAS host and, *SSG* 4-5
  - improving performance of, *TKB* D-1 to D-7

RSX-11M V03.2 Master Index

- TKB (Cont.),  
indirect command files, *TKB* 1-5 to 1-7,  
4-27, 4-28  
input data formats, *TKB* A  
input to, *DEV* 1-4  
concatenated object module as, *DEV* 4-2,  
4-3  
memory dumps,  
postmortem, *DEV* 5-8, 5-9, *TKB* 8-1 to  
8-5  
snapshot, *TKB* 8-5 to 8-11  
object libraries in,  
designating, *DEV* 6-5  
dual usage of, *DEV* 6-6, 6-7  
output from, *DEV* 1-4  
object modules,  
linking, *TKB* 2-1 to 2-8  
options,  
categories of, *TKB* 6-45  
general form of, *TKB* 1-4  
processing, *TKB* 3-8  
overlay, see Overlay, *TKB*  
program sections,  
allocation of, *TKB* 2-2, 4-19  
virtual, *TKB* 3-53, 3-59  
reserved symbols, *TKB* C  
shared regions, *TKB* 3-1 to 3-11  
slow, *TKB* D-11  
summary of syntax rules, *TKB* 1-9 to 1-11  
switches, *TKB* 6-1 to 6-44  
modifying defaults for, *TKB* D-7 to D-11  
symbol definition file, *TKB* 3-3, 3-8  
symbols, undefined, in, *DEV* 4-2  
target system for, *TKB* 7  
task image file structure, *TKB* B  
task relocation, *TKB* 2-10, 2-16  
tasks,  
privileged, *TKB* 3-62 to 3-69  
use of, with PAT, *UTL* 18-4, 18-5  
TKTN (Task Termination Notification  
routine), *MCR* 4-10  
abort message from, *DEV* 4-6  
building, *SSG* 4-6  
error messages, *DEV* 4-6, *MCR* A-1,  
*RLN* 2-17, *SSG* 2-17  
functions of, *SSG* 2-17  
initiating, *SSG* 2-17  
using, with PMD, *DEV* 1-6  
TPARS (table driven parser), *IOP* 7-1  
coding, *IOP* 7-1  
command line syntax, *IOP* 7-4  
debugging routine, *IOP* 7-2, 7-6  
TPARS (Cont.),  
invoking, *IOP* 7-10  
parser program using,  
how to generate, *IOP* 7-12 to 7-14  
source programs and, *IOP* 7-1 to 7-7  
subexpressions, *IOP* 7-6  
Trace program, *ODT* 6-1  
Track, *RMU* 1-12  
Transfer (starting address),  
defining a, *DEV* 2-7  
system treatment of default, *DEV* 4-6  
Transfer function, *WRT* 2-16  
Transition definition, *IOP* 7-3  
Trap instruction, *MAC* 5-8  
Trap processing, *ODT* A-2  
Trap(s), *ODT* 3-15  
breakpoint, *ODT* 1-3  
emulator (EMT), *EXE* 1-1  
processor, *ODT* A-2  
reports on unexpected, *ERL* 4-1, 4-2  
system, *EXE* 2-3, *INT* 3-9  
asynchronous (ASTs), *DRV* 1-11, 2-9,  
2-10, 2-35, 3-32, *EXE* 2-1, 2-4, 2-6  
synchronous (SSTs), *DRV* 1-11, *EXE* 2-4  
T-bit, *ODT* 3-15, A-2  
vector table, *EXE* 2-4, 2-5  
Truncation,  
print line, *DRV* 10-6  
terminal line, *DRV* 3-29  
Typeahead buffer, *BEG* 1-6, *RLN* 4  
Types, file, *MCR* 3-4, *ODT* 4-1  
standard, *MCR* 3-6
- U
- UCB (Unit Control Block), *CDA* 3-25, 3-31,  
B-18, C-43, C-49, *MCR* 4-146  
and I/O drivers, *WRT* 2-6, 2-18, 2-19, 3-3,  
4-19  
UFD (User File Directory), *BEG* 3-4, *INT* 6-1,  
*IOP* 3-4, 5-2, *RLN* 42  
cleaning up a, with PIP, *DEV* 3-7  
command, *BEG* 1-7, 4-1  
command line, parsing a, example of,  
*IOP* 7-14 to 7-18  
creating, with PIP, *UTL* 4-35  
in Files-11 file system, *INT* 6-1, 6-2,  
*MCR* 3-1, 3-2  
UIC (User Identification Code), *BEG* 1-9, 3-4,  
*EXE* 6-74, 6-105, *INT* 4-4, *MCR* 2-14,  
3-1, 3-5



RSX-11M V03.2 Master Index

- UIC (Cont.),
  - conversion routines, ASCII/binary, *IOP* 4-7
  - default, *EXE* 6-105, 6-114
  - protection, *EXE* 6-106, 6-114
  - special formats, *BEG* 1-10, 1-11
  - specifiers, *MCR* 2-14, 3-4
  - system, *MCR* 4-113
  - terminal, *EXE* 6-81, 6-105
- UMD (User-Mode Diagnostics),
  - see Diagnostics
- UMR (UNIBUS Mapping Register), *WRT* B-1
  - symbolic addresses, *WRT* B-3
- Unary control, *MAC* 6-24
- Unary operator, *MAC* 3-4
  - ordering, *MAC* 6-28
- Unconditional assembly, *MAC* 6-43
- Undefined record format, *RMC* 3-46, *RMU* 1-40
- Undefined symbols, *MAC* 3-7, 3-14
- Underline (  ), *ODT* 2-4, 3-6, 3-26
- UNIBUS, *DRV* 13-1, 23-1
  - run, *EXE* 5-4
- UNIBUS Mapping Register, see UMR
- Unibus switch driver, *DRV* 23
- Unit Control Block, see UCB
- Unit number field, *IOP* 2-32, 4-9
- Unit record device, *RMC* 3-45
- Units, logical, *DRV* 1-5 to 1-7
- Universal digital controller driver, *DRV* 15
- Universal unary operator or argument
  - indicator, *MAC* 3-2, 3-3
- Unmapped systems, *INT* 3-2, *MCR* 1-1,
  - ODT* 1-4
  - TKB addressing on, *TKB* 2-8, 2-9
- Unstop, *EXE* 6-155
- Up-arrow, *MAC* 3-3
  - construction, *MAC* 7-5
  - or circumflex, *MAC* 3-1
- Update record operation, *RMU* 1-26
- Uppercase text conversion routine, *SLR* 6-1
- User buffer, *RMC* 1-6, 8-23, *RMU* 1-29,
  - WRT* 6-9
- User control block, *RMC* 1-2, 1-8, 1-10
- User data structures, *EXE* 3-10
- User File Directory, see UFD
- User file structure, *IOP* 5-1
- User groups, *INT* 6-2, *MCR* 3-3
- User Identification Code, see UIC
- User logon text file, *BEG* 1-10
- User macro library, *DEV* 6-1, 6-2, *MAC* 7-18
- User mode, *ODT* A-1
- User object library, *DEV* 6-4, 6-5
- User programs, *INT* 3-1
- User record buffer, *IOP* 2-10, 3-6, 3-7, 3-9,
  - 3-19, 3-20, 3-25
- User region, *INT* 3-7
- Users,
  - nonprivileged, *INT* 4-3, *MCR* 2-6, 2-15, 3-5
  - privileged, *INT* 3-5, *MCR* 2-14, 3-5
- User symbol table, *MAC* 3-5
- User task(s),
  - address, *ODT* 3-1
  - breakpoints, *ODT* 1-3
  - running, *ODT* 3-17
- User-written drivers, see Drivers
- Utilities,
  - command line format for, *UTL* 1-4, 1-5
  - editing,
    - EDI, *UTL* 3
    - EDT, *UTL* 2
  - enhancements to, *RLN* 3
  - file manipulation,
    - FLX, *UTL* 5
    - PIP, *UTL* 4
  - file specification format for, *UTL* 1-5, 1-6
  - file spooling,
    - PRI and QUE, *UTL* 6
    - Queue Manager, *UTL* 7
  - indirect command files and, *UTL* 1-9, 1-10
  - invoking, *UTL* 1-6
  - list of, *UTL* 1-1, 1-2
  - new switches for, *RLN* 33-36
  - program maintenance,
    - CMP, *UTL* 16
    - PAT, *UTL* 18
    - SLP, *UTL* 17
    - ZAP, *UTL* 19
  - programming,
    - DMP, *UTL* 15
    - LBR, *UTL* 14
  - RMS-11, *RMU* 1-26, 9-1
    - command, *RMU* 9-5
    - interactive, *RMU* 9-5
    - installed, *RMU* 9-6
    - uninstalled, *RMU* 9-6
  - RSX-11M, *BEG* 4-1
  - volume maintenance,
    - BAD, *UTL* 9
    - BRU, *UTL* 10
    - DSC, *UTL* 11
    - FMT, *UTL* 8
    - PRESRV, *UTL* 12
    - VFY, *UTL* 13
- Utility programs, general, *DEV* 1-6
- Utility routines, *ODT* 1-2

V

Valid record, *RMU* 4-9  
 Variable-length record format, *RMC* 3-46,  
*RMU* 2-15  
 VBN (Virtual Block Number), *RMC* 3-48, 5-7,  
 5-38, *RMU* 1-15  
 VCB (Volume Control Block), *MCR* 4-36,  
 4-65, *WRT* 2-18, 2-19  
 Vector table,  
     *SST*, *EXE* 6-149, 6-151  
     trap, *EXE* 2-4, 2-5  
 Verifying,  
     contents of a task image file with *ZAP*,  
         *UTL* 19-15  
     devices with *BAD*, *UTL* 9-3  
     file structures with *VFY*, *UTL* 13  
     RSX-11M system installation, *GEN* 10  
 Version number, *MAC* 6-12  
     file, *IOP* 3-38, 4-11, 4-13, 4-15  
         default, *MCR* 3-6  
         prologue, *RMC* 5-77  
         standard, *MAC* E-13  
 Vertical format control, *DRV* 2-31, 3-25, 10-5  
 Vertical parity support, *DEV* 12-11  
 VFY (File Structure Verification Utility),  
     command line, *UTL* 13-2, 13-3  
     introduction to, *UTL* 13-1  
 Virtual addresses, *INT* 3-1  
 Virtual address space, *EXE* 3-2, *INT* 3-1,  
     3-10, *RMU* 6-16  
     mapped system, *TKB* 2-10  
     unmapped system, *TKB* 2-8  
 Virtual address window, *EXE* 3-2  
 Virtual block number, see VBN  
 Virtual block, see Blocks  
 Virtual I/O, *DRV* 1-2  
 Virtual memory management routines,  
     allocation, *SLR* 8-16 to 8-20  
     initialization, *SLR* 8-5 to 8-7  
 Virtual Monitor Console Routine, see VMR  
 Virtual program sections,  
     building tasks that use, *TKB* 3-59  
     creating, *TKB* 3-53  
     support for, *TKB* 3-53  
 Virtual-to-logical block mapping, *RMU* 3-6,  
     4-6, 8-1, 8-26  
 VMR (Virtual Monitor Console Routine),  
     *SSG* 4-10, *WRT* 3-26  
     command descriptions, *GEN* 8-5 to 8-52  
     command summary, *GEN* 8-4, 8-5  
     error messages, *GEN* 8-53 to 8-66

VMR (Cont.),  
     file specifiers, *GEN* 8-2 to 8-4  
     starting, *GEN* 8-1, 8-2  
     task loading with, *SSG* 8-3  
 Volume Control Block, see VCB  
 Volume number, relative, *RMC* 5-20  
 Volumes, *BEG* 2-1  
     backing up, with *BRU*, *UTL* 10-18  
     deleting files from, with *FLX*, *UTL* 5-6  
     directory listings of, with *FLX*, *UTL* 5-7  
     foreign, *MCR* 3-1  
     formatting,  
         with *FLX*, *UTL* 5-3, 5-4  
         with *FMT*, *UTL* 8-1  
     initializing,  
         *RMS*-11, *RMU* 8-27  
         with *FLX*, *UTL* 5-8  
     mounting, *MCR* 4-65  
     preserving, with *PRESRV*, *UTL* 12  
     relative, number of, *RMU* 9-42  
     tape, rewinding, *RMU* F-3  
     transferring files between, with *FLX*,  
         *UTL* 5-1  
     unit number for, *BEG* 3-1  
 VT55 support, *RLN* 39

W

WDB (Window Definition Block), *EXE* 3-10,  
     3-14 to 3-18  
     integer array, *EXE* 3-17  
     parameters, *EXE* 3-18  
 Wildcards (asterisk), *BEG* 4-7, *IOP* 4-13 to  
     4-15, *RMU* 9-11  
     convention as file specifier, *MCR* 3-8  
     in PIP file specifications, *UTL* 4-4  
 Window blocks, *CDA* 3-42, B-5, C-19,  
     *EXE* 3-2, *TKB* 2-16, *WRT* 2-17 to 2-19,  
     4-4  
 Window Definition Block, see WDB  
 Window descriptors, *TKB* 4-21  
 Window identification, *EXE* 3-2  
 Windows, *TKB* 2-16  
     2-4 file, mapping, *RLN* 2, 6  
     address,  
         creating, *EXE* 6-31  
         eliminating, *EXE* 6-51  
         mapping, *EXE* 6-83  
         unmapping, *EXE* 6-153  
         virtual, *EXE* 3-2, 3-3, 6-31  
     file, *IOP* 2-15, 2-16  
     mapping 2-4, *RLN* 2, 6

Windows (Cont.)

- Map address, *EXE* 6-83
- retrieval, *RMU* 8-26
- size of, *RMC* 3-48
- wrap-around, *TKB* 3-56
- Word alignment, *RMU* 2-5, 3-4
- Write access, *IOP* 2-14, 3-3, 3-16, *RMU* 2-12
- Write-sharing, *RMC* 3-52
- Write-type operation, *RMU* 2-12
- Word ASCII mode, *ODT* 3-31, 3-35
- Word/byte search commands, *ODT* 3-21, 3-23,  
B-1
- Word data,
  - generating, *MAC* 6-18
- Word mode, *ODT* 3-31
  - ASCII, *ODT* 3-31
  - characters, print, *ODT* 3-35
  - octal, *ODT* 3-31
  - Radix-50, *ODT* 3-31, 3-33
  - characters, print, *ODT* 3-36
- Word search, *ODT* 3-21

**X**

- XAB, *RMU* 3-56
- XDT (Executive Debugging Tool), *CDA* 1-3,  
*MCR* 4-140, 4-142
- and I/O drivers, *WRT* 3-14, 3-15, 3-18

**Z**

- ZAP (Task/Image File Patch Program),
  - addressing locations in a task image with,  
*UTL* 19-3
  - changing contents of a location with,  
*UTL* 19-11
  - closing a location with, *UTL* 19-11 to 19-13
  - command line, *UTL* 19-5
  - commands,
    - carriage return, *UTL* 19-6
    - general-purpose, *UTL* 19-5, 19-13
    - open/close location, *UTL* 19-5, 19-9
  - displaying contents of a location with,  
*UTL* 19-15
  - error messages, *UTL* 19-16
  - exiting from, *UTL* 19-2, 19-14
  - invoking, *UTL* 19-2
  - ODT, relationship to, *UTL* 19-1
  - opening a location with, *UTL* 19-10
  - setting value of a relocation register,  
*UTL* 19-16
  - switches, *UTL* 19-2, 19-3
  - terminating, *UTL* 19-2, 19-14
  - verifying contents of a location with,  
*UTL* 19-15



READER'S COMMENTS

NOTE: This form is for document comments only. DIGITAL will use comments submitted on this form at the company's discretion. If you require a written reply and are eligible to receive one under Software Performance Report (SPR) service, submit your comments on an SPR form.

Did you find this manual understandable, usable, and well-organized? Please make suggestions for improvement.

---

---

---

---

---

---

---

---

---

---

Did you find errors in this manual? If so, specify the error and the page number.

---

---

---

---

---

---

---

---

---

---

Please indicate the type of user/reader that you most nearly represent.

- Assembly language programmer
- Higher-level language programmer
- Occasional programmer (experienced)
- User with little programming experience
- Student programmer
- Other (please specify) \_\_\_\_\_

Name \_\_\_\_\_ Date \_\_\_\_\_

Organization \_\_\_\_\_

Street \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip Code \_\_\_\_\_

or  
Country

Do Not Tear - Fold Here and Tape

**digital**



No Postage  
Necessary  
if Mailed in the  
United States

**BUSINESS REPLY MAIL**  
FIRST CLASS PERMIT NO.33 MAYNARD MASS.

POSTAGE WILL BE PAID BY ADDRESSEE

RT/C SOFTWARE PUBLICATIONS TW/A14  
DIGITAL EQUIPMENT CORPORATION  
1925 ANDOVER STREET  
TEWKSBURY, MASSACHUSETTS 01876



Do Not Tear - Fold Here

Cut Along Dotted Line