



# I.C.T 1900 SERIES

## **INTERROGATING TYPEWRITER 1938**



### DESCRIPTION

The 1938 Interrogating Typewriter is an on-line input/output device for the 1900 series. The Typewriter allows messages to be entered into an operational program via a keyboard, and at the same time to be printed on a continuous paper form. The 1938 also types out messages from the program.

A single Interrogating Typewriter may be connected directly to a Standard Interface Channel in the Processor, or a number may be connected via a 1992 Communications Multiplexor.

- Keyboard communication with operational programs
- Printed record of all messages
- Automatic code conversion between keyboard and processor
- Printing speed ten characters a second

# INTERROGATING TYPEWRITER 1938

## SPECIFICATION

*Input rate* Manual keyboard operation, maximum 10 characters per second.

*Output rate* 10 characters per second.

*Message size* Maximum 128 alphanumeric characters.

*Printing format* Maximum 74 characters per line, 10 characters per inch horizontally, 3 or 6 lines per inch vertically.

*Paper stock* Single or multiple sheet stock, up to 8½ inches wide.

*Printer characters* 26 letters of the alphabet (upper case), 10 numerals, and 28 symbols (including space) as follows:

—	minus
+	plus
,	comma
.	period
*	asterisk
/	slant
(	left parenthesis
)	right parenthesis
<	less than
=	equals
>	greater than
[	left bracket
]	right bracket
%	per cent
@	at the rate of
#	number
£	sterling
\$	dollar
&	ampersand
?	query
!	exclamation
:	colon
;	semi-colon
“	quote
’	apostrophe
↑	up arrow
←	left arrow

## PHYSICAL CHARACTERISTICS

The typewriter is mounted on a table:

Height	26 inches
Depth	26 inches
Width	48 inches

*This specification is subject to modification*

## INTERNATIONAL COMPUTERS AND TABULATORS LIMITED

Head Office I.C.T House Putney London SW15

Sales Office Bridge House Putney Bridge London SW6 Renown 3322  
and local offices throughout the United Kingdom