



**PCB LAYERS:**

- 1 ————— SIGNAL
- 2 ————— GND
- 3 ————— SIGNAL
- 4 ————— VCC
- 5 ————— VCC
- 6 ————— SIGNAL
- 7 ————— GND
- 8 ————— SIGNAL

**NOTES:**

- 1) ALL ICs GET A 0.1 uF CAP NEXT TO THEM.
- 2) MIDDLE STIFFENER BAR MAY BE MOVED VERTICALLY SLIGHTLY TO ACCOMMODATE IC ROWS.
- 3) IC E27 MUST HAVE SPECIAL GROUND LAYOUT PER THE AM29332 SPEC.
- 4) IC M22 (OSC) MUST HAVE AN EXTRA 0.1" CLEARANCE ON ALL SIDES.
- 5) IC ROW HEIGHTS ARE AS FOLLOWS:  
 1.0" - B, C, D, I  
 1.2" - E, F, H, K, L  
 1.4" - A, G, J
- 6) PUT 8 - 82 uF DECOUPLING CAPS AS SHOWN.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND PROPRIETARY TO LMI, AND IS NOT TO BE REPRODUCED, DISCLOSED TO OTHERS, OR USED WITHOUT WRITTEN PERMISSION OF AN AUTHORIZED REPRESENTATIVE OF LMI.	PREPARED	DATE	L M I	
	K. MOULT	10/10/86	LISP Machine Inc.	
	CHECKED		6 Tech Drive	
			Andover, MA 01810	
	APPROVED	FALCON PROC_BO LAYOUT INFO		
	APPROVED	SIZE CAT.	NO.	REV
	APPROVED	D		
		SCALE	SHEET 1 OF 1	