

-- BFS.Mesa Edited by Sandman on May 12, 1978 8:50 AM

DIRECTORY

```

AltoDefs: FROM "altodefs" USING [CharsPerPage, PageNumber, PageSize],
AltoFileDefs: FROM "altofiledefs" USING [
  CFA, CFP, eofDA, FA, fillinDA, FP, LD, SN, vDA, vDC],
BFSDefs: FROM "bfsdefs",
DiskDefs: FROM "diskdefs" USING [
  CBptr, CBZptr, CleanupCBqueue, DDC, DiskCheckError, DiskRequest,
  DoDiskCommand, FID, GetCB, InitializeCBstorage, lCBZ, nCB, nSectors,
  RealDA, RetryableDiskError, RetryCount, UnrecoverableDiskError,
  VirtualDA],
DiskKDDefs: FROM "diskkdefs" USING [
  AssignDiskPage, NewSN, ReleaseDiskPage],
MiscDefs: FROM "miscdefs" USING [DAYTIME, SetBlock, Zero],
SegmentDefs: FROM "segmentdefs" USING [
  DataSegmentAddress, DataSegmentHandle, DefaultBase, DeleteDataSegment,
  NewDataSegment],
StringDefs: FROM "stringdefs" USING [MesaToBcp1String];

```

DEFINITIONS FROM AltoDefs, AltoFileDefs, DiskDefs;

BFS: PROGRAM

```

IMPORTS DiskDefs, DiskKDDefs, MiscDefs, SegmentDefs, StringDefs
EXPORTS BFSDefs = BEGIN

```

```

-- These should be POINTER TO ARRAY OF ...
CAvec: TYPE = DESCRIPTOR FOR ARRAY OF POINTER;
DAvec: TYPE = DESCRIPTOR FOR ARRAY OF vDA;

```

```

ActOnPages: PUBLIC PROCEDURE [arg:POINTER TO update DiskRequest]
  RETURNS [page:PageNumber, bytes:CARDINAL] =
  BEGIN OPEN arg, DiskDefs; a: vDC; ddc: DDC;
  i: PageNumber; cb, nextcb: CBptr;
  cbzone: ARRAY [0..lCBZ) OF UNSPECIFIED;
  zone: CBZptr = @cbzone[0];
  CAs: CAvec = DESCRIPTOR[ca,lastPage+1];
  DAs: DAvec = DESCRIPTOR[da,lastPage+2];
  InitializeCBstorage[zone,nCB,firstPage,clear];
  zone.info ← da; zone.cleanup ← cleanup;
  BEGIN ENABLE RetryableDiskError => RETRY;
  cb ← GetCB[zone,clear | ANY => ERROR];
  FOR i ← zone.currentPage, i+1 UNTIL i=lastPage+1 DO
  BEGIN -- inner compound to skip DoNothing pages
  a ← IF i=lastPage THEN lastAction ELSE action;
  IF a = DoNothing THEN GOTO SkipThisPage;
  IF DAs[i] = eofDA THEN EXIT;
  IF signalCheckError AND zone.errorCount = RetryCount/2
  THEN SIGNAL DiskCheckError[i];
  nextcb ← GetCB[zone,clear];
  cb.labelAddress ← IF DAs[i+1] = fillinDA
  THEN LOOPHOLE[@nextcb.header.diskAddress]
  ELSE @nextcb.label;
  ddc ← DDC [
  cb,IF fixedCA THEN ca ELSE CAs[i],DAs[i],i,fp,FALSE,a];
  DoDiskCommand[@ddc];
  cb ← nextcb;
  EXITS
  SkipThisPage => NULL;
  END;
  ENDLLOOP;
  CleanupCBqueue[zone];
  END; -- of enable block
  RETURN[i-1,zone.currentBytes]
  END;

```

```

GetNextDA: PUBLIC PROCEDURE [cb:CBptr] =
  BEGIN
  pn: PageNumber = cb.page;
  DAs: DAvec = DESCRIPTOR[cb.zone.info,pn+2];
  IF DAs[pn+1] = fillinDA THEN
  DAs[pn+1] ← VirtualDA[cb.labelAddress.next];
  IF DAs[pn-1] = fillinDA THEN
  DAs[pn-1] ← VirtualDA[cb.labelAddress.prev];
  RETURN
  END;

```



```
-- Currently DiskRequest.action is not used by WritePages (WriteD is assumed).
-- Note also that lastAction is used only if lastPage isn't being rewritten.
```

```
WritePages: PUBLIC PROCEDURE [arg:POINTER TO extend DiskRequest]
  RETURNS [page:PageNumber, bytes:CARDINAL] = BEGIN
  aop: update DiskRequest;
  firstNewPage: PageNumber;
  local: extend DiskRequest ← arg↑;
  DAs: DAVec = DESCRIPTOR[arg.da,arg.lastPage+2];
  BEGIN OPEN local;
  IF DAs[firstPage] = fillinDA THEN firstNewPage ← firstPage
  ELSE BEGIN
    aop ← DiskRequest [
      ca, da, firstPage, lastPage, fp, fixedCA, WriteD,
      lastAction, signalCheckError, update[GetNextDA]];
    [page,bytes] ← ActOnPages[@aop];
    IF (firstPage ← page) = lastPage
    AND (lastAction # WriteD
    OR bytes = lastBytes) THEN RETURN;
    firstNewPage ← firstPage+1;
  END;
  IF firstNewPage ≤ lastPage THEN
    BEGIN aop.da ← da;
    aop.firstPage ← firstNewPage;
    aop.lastPage ← lastPage;
    AssignPages[@aop];
  END;
  [page,bytes] ← RewritePages[@local];
  RETURN
END; END;
```

```
-- Note that only da, firstPage, and lastPage are valid on entry.
```

```
AssignPages: PUBLIC PROCEDURE [arg:POINTER TO update DiskRequest] =
  BEGIN OPEN SegmentDefs, arg; i: PageNumber;
  DAs: DAVec = DESCRIPTOR[da,lastPage+2];
  sink: DataSegmentHandle = NewDataSegment[DefaultBase,1];
  arg↑ ← DiskRequest [
    DataSegmentAddress[sink],,,NIL,TRUE,ReadLD,
    ReadLD,FALSE,update[CheckFreePage]];
  UNTIL firstPage > lastPage DO
    ENABLE UNWIND => DeleteDataSegment[sink];
    FOR i IN [firstPage..lastPage] DO
      DAs[i] ← DiskKDDefs.AssignDiskPage[DAs[i-1]];
    ENDLOOP;
    i ← firstPage;
    [] ← ActOnPages[arg ! UnrecoverableDiskError--[cb]-- =>
      BEGIN -- skip bad spots and press on
        firstPage ← cb.page;
        DAs[firstPage] ← fillinDA;
        firstPage ← firstPage+1;
        RETRY
      END;
    firstPage ← i;
    FOR i IN [firstPage..lastPage] DO
      IF (DAs[firstPage] ← DAs[i]) # fillinDA
        THEN firstPage ← firstPage+1;
    ENDLOOP;
  ENDLOOP;
  DeleteDataSegment[sink];
  RETURN
END;
```

```
FreePageFID: FID = FID[-1,SN[1,1,1,17777B,-1]];
```

```
CheckFreePage: PUBLIC PROCEDURE[cb:CBptr] =
  BEGIN
  DAs: POINTER TO ARRAY [0..1) OF vDA = cb.zone.info;
  IF cb.labelAddress.fileID # FreePageFID
    THEN DAs↑[cb.page] ← fillinDA;
  RETURN
END;
```

-- Note that action and lastAction are not used (WriteLD is assumed).

```
RewritePages: PUBLIC PROCEDURE [arg:POINTER TO extend DiskRequest]
  RETURNS [PageNumber, CARDINAL] =
  BEGIN OPEN arg; i: PageNumber;
  cbzone: ARRAY [0..1CBZ] OF UNSPECIFIED;
  zone: CBZptr = @cbzone[0]; cb: CBptr;
  CAs: CAVec = DESCRIPTOR[ca,lastPage+1];
  DAs: DAVec = DESCRIPTOR[da,lastPage+2];
  ddc: DDC ← DDC[ca,,fp,FALSE,WriteLD];
  InitializeCBStorage[zone,nCB,firstPage,clear];
  BEGIN ENABLE RetryableDiskError => RETRY;
  FOR i ← zone.currentPage, i+1 UNTIL i=lastPage+1 DO
    cb ← GetCB[zone,clear];
    IF (i = lastPage AND lastBytes # CharsPerPage)
    OR DAs[i+1] = fillinDA THEN DAs[i+1] ← eofDA;
    cb.label.next ← RealDA[DAs[i+1]];
    cb.label.prev ← RealDA[DAs[i-1]];
    cb.label.bytes ←
      IF i = lastPage THEN lastBytes ELSE CharsPerPage;
    ddc.cb ← cb; ddc.da ← DAs[i]; ddc.page ← i;
    IF ~fixedCA THEN ddc.ca ← CAs[i];
    DoDiskCommand[@ddc];
  ENDLOOP;
  CleanupCBQueue[zone];
  END;
  RETURN[lastPage,lastBytes]
END;
```

jump: CARDINAL = 10\*nSectors;

```
CreatePages: PUBLIC PROCEDURE [
  ca:POINTER, cfa:POINTER TO CFA,
  lastPage:PageNumber, lastBytes:CARDINAL] =
  BEGIN
  da: vDA ← cfa.fa.da;
  arg: extend DiskRequest;
  DAs: ARRAY [-1..jump] OF vDA;
  page: PageNumber ← cfa.fa.page;
  DO -- until lastPage is written
    MiscDefs.SetBlock[@DAs[-1],fillinDA,jump+2]; DAs[0] ← da;
    arg ← DiskRequest [
      ca,@DAs[-page],page,MIN[lastPage,page+(jump-1)],
      @cfa.fp,TRUE,WriteD,WriteD,FALSE,extend[lastBytes]];
    [] ← WritePages[@arg];
    da ← DAs[arg.lastPage-page];
    page ← arg.lastPage;
    IF page = lastPage THEN EXIT;
  ENDLOOP;
  cfa.fa ← FA[da,lastPage,lastBytes];
  RETURN
END;
```

```
DeletePages: PUBLIC PROCEDURE [
  ca:POINTER, fp:POINTER TO FP, da:vDA, page:PageNumber] =
  BEGIN
  arg: update DiskRequest;
  lastPage, i: PageNumber;
  DAs: ARRAY [-1..jump] OF vDA;
  UNTIL da=eofDA DO
    MiscDefs.SetBlock[@DAs[-1],fillinDA,jump+2];
    DAs[0] ← da;
    arg ← DiskRequest [
      ca,@DAs[-page],page,page+(jump-1),fp,TRUE,
      ReadD,ReadD,FALSE,update[GetNextDA]];
    lastPage ← ActOnPages[@arg].page;
    MiscDefs.Zero[ca,PageSize];
    arg.fp ← LOOPHOLE[0];
    arg.lastPage ← lastPage;
    arg.action ← arg.lastAction ← WriteLD;
    [] ← ActOnPages[@arg];
    FOR i IN [0..lastPage-page] DO
      DiskKDDefs.ReleaseDiskPage[DAs[i]];
    ENDLOOP;
    da ← DAs[lastPage+1-page];
    page ← lastPage+1;
```

```
    ENDLOOP;
  RETURN
END;

CreateFile: PUBLIC PROCEDURE [name:STRING, fp, dirFP:POINTER TO FP] =
BEGIN OPEN SegmentDefs;
  DAs: ARRAY[-1..2] OF vDA ← [eofDA,fillinDA,fillinDA,eofDA];
  buf: DataSegmentHandle = NewDataSegment[DefaultBase,1];
  ld: POINTER TO LD = DataSegmentAddress[buf];
  arg: extend DiskRequest ← DiskRequest [
    ld,@DAs[0],0,1,fp,TRUE,WriteD,WriteD,FALSE,extend[0]];
  BEGIN ENABLE UNWIND => DeleteDataSegment[buf];
    MiscDefs.Zero[ld,PageSize];
    ld.created ← MiscDefs.DAYTIME[];
    StringDefs.MesaToBcp1String[name,LOOPHOLE[@ld.name]];
    ld.propBegin ← @ld.props[0]-ld;
    ld.propLength ← LENGTH[ld.props];
    IF dirFP # NIL THEN MakeCFP[@ld.dirFP,dirFP];
    fp↑ ← FP[DiskKDDefs.NewSN[],eofDA];
    [] ← WritePages[@arg];
  END;
  fp.leaderDA ← DAs[0];
  DeleteDataSegment[buf];
  RETURN
END;

MakeFP: PUBLIC PROCEDURE [
  fp:POINTER TO FP, cfp:POINTER TO CFP] =
  BEGIN
  fp↑ ← FP[cfp.serial,cfp.leaderDA];
  RETURN
  END;

MakeCFP: PUBLIC PROCEDURE [
  cfp:POINTER TO CFP, fp:POINTER TO FP] =
  BEGIN
  cfp↑ ← CFP[fp.serial,1,0,fp.leaderDA];
  RETURN
  END;

END.
```